



C351X00

SoftCoil Energy Absorbing Lanyards

FEATURES

- 6 foot Energy Absorbing Lanyard
- Internal energy absorbing inner core
- Tubular polyester webbing
- Visual impact indicator
- Label protection
- Meets ANSI Z359.13-2013



SPECIFICATIONS

Model No.	Harness Connector	Anchorage Connector	Material	Length	Approx. Weight
C351100	Steel Snap Hook	Steel Snap Hook	Tubular Polyester Web	6 ft (1.8 m)	3.0 lbs (1.4 kg)
C351200	Steel Snap Hook	Steel Rebar Hook	Tubular Polyester Web	6 ft (1.8 m)	4.0 lbs (1.8 kg)

COMPLIANCE STANDARDS

Meets	Average Arrest Force	Maximum Arrest Force	Free Fall Limit	Capacity
ANSI Z359.13-2013	900 lb (4 kN)	1,800 lbf (8 kN)	6 ft (1.8 m)	130 - 310 lbs (59 - 141 kg)
OSHA 29 CFR 1910.66 & 1926.502	N/A	1,800 lbf (8 kN)	6 ft (1.8 m)	130 - 310 lbs (59 - 141 kg)

*See User Instructions for more information.

⚠ WARNING: Compliant fall protection equipment must only be used as it was designed and adhere to the hierarchy of controls as discussed in ANSI Z359.2. Users MUST read and follow all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

Technical Data Sheet