




Campbell

Spin-Down™ Sediment Filters



SPIN-DOWN™ SEDIMENT FILTER (T-style)



part	flow (gpm)	connection	mesh	overall length*	width	pcs/ ctn
FT3-24	1-20	3/4 mpt	24	11-3/8	7-1/4	1
FT3-30	1-20	3/4 mpt	30	11-3/8	7-1/4	1
FT3-40	1-20	3/4 mpt	40	11-3/8	7-1/4	1
FT3-60	1-20	3/4 mpt	60	11-3/8	7-1/4	1
FT3-100	1-20	3/4 mpt	100	11-3/8	7-1/4	1
FT3-140	1-20	3/4 mpt	140	11-3/8	7-1/4	1
FT3-250	1-20	3/4 mpt	250	11-3/8	7-1/4	1
FT3-500	1-20	3/4 mpt	500	11-3/8	7-1/4	1
FT3-1000	1-20	3/4 mpt	1000	11-3/8	7-1/4	1
FT4-24	1-20	1 slip	24	11-3/8	5	1
FT4-30	1-20	1 slip	30	11-3/8	5	1
FT4-40	1-20	1 slip	40	11-3/8	5	1
FT4-60	1-20	1 slip	60	11-3/8	5	1
FT4-100	1-20	1 slip	100	11-3/8	5	1
FT4-140	1-20	1 slip	140	11-3/8	5	1
FT4-250	1-20	1 slip	250	11-3/8	5	1
FT4-500	1-20	1 slip	500	11-3/8	5	1
FT4-1000	1-20	1 slip	1000	11-3/8	5	1
FT6-24	10-50	1-1/2 slip	24	15-3/8	5-1/4	1
FT6-30	10-50	1-1/2 slip	30	15-3/8	5-1/4	1
FT6-40	10-50	1-1/2 slip	40	15-3/8	5-1/4	1
FT6-60	10-50	1-1/2 slip	60	15-3/8	5-1/4	1
FT6-100	10-50	1-1/2 slip	100	15-3/8	5-1/4	1
FT6-140	10-50	1-1/2 slip	140	15-3/8	5-1/4	1
FT6-250	10-50	1-1/2 slip	250	15-3/8	5-1/4	1
FT6-500	10-50	1-1/2 slip	500	15-3/8	5-1/4	1
FT6-1000	10-50	1-1/2 slip	1000	15-3/8	5-1/4	1
FT8-24	18-100	2 slip	24	17-7/8	5-1/2	1
FT8-30	18-100	2 slip	30	17-7/8	5-1/2	1
FT8-40	18-100	2 slip	40	17-7/8	5-1/2	1
FT8-60	18-100	2 slip	60	17-7/8	5-1/2	1
FT8-100	18-100	2 slip	100	17-7/8	5-1/2	1
FT8-140	18-100	2 slip	140	17-7/8	5-1/2	1
FT8-250	18-100	2 slip	250	17-7/8	5-1/2	1
FT8-500	18-100	2 slip	500	17-7/8	5-1/2	1
FT8-1000	18-100	2 slip	1000	17-7/8	5-1/2	1

High-impact, molded, non-corrosive filters with reusable polyester filter screens use centrifuge spin-down action to remove sand and other coarse sediment while maintaining full flow in system. Clear bowl permits monitoring of trapped sediment. Sediment can be drained through Flush Valve (PIBV2T-R included) in bottom of bowl without disconnecting system. Bowl can be easily removed without tools** for total cleaning. Includes PTFE Thread Seal Tape. Maximum pressure: 150 psi at 73°F.

SPIN-DOWN™ SEDIMENT APPLICATIONS & MESH CONVERSION CHART

sediment type	application	mesh	microns	opening
Shale, Shell, Debris	General Use	24	711	.028"
Debris	General Use	30	533	.021"
		40	381	.015"
Pipe Scale, Coarse Sand	Sprinkler Systems, Faucet Aerators, Sand-sensitive Valves	40	381	.015"
		60	254	.010"
Fine Sand, Grit from new wells	Drip Irrigation Systems, Faucet Aerators, Sand-sensitive Valves, Poultry Waterers	100	152	.006"
Fine Sand, Grit from new wells	Drip Irrigation Systems, Faucet aerators, Sand-sensitive Valves, Fogger Nozzles	140	104	.004"
Very Fine Sand and Grit	Pre-Treatment	250	61	.0024"
		500	30	.0012"
Very Fine Sand and Grit	Pre-Treatment	1000	15	.0006"
	Ultra Water Systems (R/O, etc.)			

Because of the many variations in shape, size, and specific gravity of the materials being filtered, the information shown above is general in nature.

Campbell Manufacturing, Inc.
127 East Spring Street
P.O. Box 207
Bechtelsville, PA 19505-0207
800-523-0224, Fax 610-369-3580

* Length of assembled Filter and Flush Valve
** Hand-tighten only. Using tools will void warranty.

See Flow Rates Table on page T13



FT8-100



FT6-60



FT3-100



FT4-60