

Job Name:

System Reference:

Date:

208/230V OUTDOOR VRF HEAT RECOVERY SYSTEM**ACCESSORIES**

BC Controller (Required)..... for details see BC Controller Submittals

Joint Kit..... for details see Pipe Accessories Submittal

Snow/Hail Guards Kit..... for details see Snow/Hail Guards Kit Submittal

Specifications			System
Unit Type			PURY-HP120TNU-A
Cooling Capacity (Nominal)		BTU/H	120,000
Heating Capacity (Nominal)		BTU/H	135,000
Guaranteed Operating Range	Cooling	°F [°C]	23~126 [-5.0~52.0]
	Heating	°F [°C]	-22~60 [-30.0~15.5]
Extended Operating Range	Heating	°F [°C]	-27.4~60 [-33.0~15.5]
External Dimensions (H x W x D)		In. [mm]	71-5/8 x 49-1/4 x 29-3/8 [1,818 x 1,250 x 745]
Net Weight		Lbs. [kg]	662 [300]
External Finish			Pre-coated galvanized steel sheet [MUNSELL 5Y 8/1]
Electrical Power Requirements	Voltage, Phase, Hertz, Power Tolerance		208/230V, 3-phase, 60 Hz, ±10%
Minimum Circuit Ampacity		A	47.0/44.0
Maximum Overcurrent Protection		A	70/60
Recommended Fuse Size		A	70/60
Recommended Minimum Wire Size		AWG [mm]	4/4 [21.2/21.2]
SCCR		kA	5
Refrigerant Piping Diameter	Liquid (High Pressure)	In. [mm]	3/4 [19.05] Braze
	Gas (Low Pressure)	In. [mm]	1-1/8 [28.58] Braze
Max. Total Refrigerant Line Length		Ft.	1,968
Max. Refrigerant Line Length (Between ODU & IDU)		Ft.	541
Max. Control Wiring Length		Ft.	1,640
Indoor Unit Connectable	Total Capacity		50.0~150.0% of outdoor unit capacity
	Model/Quantity		P04~P96/1.0~30.0
Sound Pressure Levels		dB(A)	64.0/65.0
Sound Power Levels		dB(A)	84.0/85.0
FAN ⁴	Type x Quantity		Propeller fan x 2
	Fan Motor Output	kW	0.46+0.46
	Airflow Rate	CFM	9,550
	External Static Pressure	In. WG	Selectable; 0.00, 0.12, 0.24, 0.32, In. WG; factory set to 0 In. WG
Compressor Operating Range			15.0% to 100.0%
Compressor	Type x Quantity		Inverter scroll hermetic compressor x 1
Refrigerant	Type x Original Charge		R410A x 23 lbs + 12.0 oz [10.8 kg]
Protection Devices	High Pressure Protection		High pressure sensor, High pressure switch at 4.15 MPa (601 psi)
	Inverter Circuit (Comp./Fan)		Over-heat protection, Over-current protection
AHRI Ratings (Ducted/Non-ducted)	EER		12.1/13.2
	IEER		19.7/24.4
	COP		3.61/4.01
	SCHE		25.3/29.1

NOTES:

Nominal cooling conditions (Test conditions are based on AHRI 1230)

Indoor: 80°F D.B./67°F W.B. (26.7°C D.B./19.4°C W.B.), Outdoor: 95°F D.B. (35°C D.B.)

Nominal heating conditions (Test conditions are based on AHRI 1230)

Indoor: 70°F D.B. (21.1°C D.B.), Outdoor: 47°F D.B./43°F W.B. (8.3°C D.B./6.1°C W.B.)

¹Harsh weather environments may demand performance enhancing equipment. Ask your Mitsubishi Electric representative for more details about your region²For details on extended cooling operation range down to -10° F DB, see Low Ambient Kit Submittal³When applying product below -4°F, consult your design engineer for cold climate application best practices, including the use of a backup source for heating⁴Unit will continue to operate in extended operating range, but capacity is not guaranteed

OUTDOOR UNIT: PURY-HP120TNU-A – DIMENSIONS

PURY-HP72, 96, 120TNU-A

Unit: mm (in.)


Note 1. At brazing of pipes, wrap the refrigerant service valve with wet cloth and keep the temperature of refrigerant service valve under 120°C(248°F).

Connecting pipe specifications

Model	Refrigerant pipe		Diameter	
	High pressure	Low pressure	High pressure	Service valve Low pressure
HP72	#15.88(5/8) Brazed*1	#10.63(3/4) Brazed*1	ø28.58(1-1/8)	ø28.58(1-1/8)
HP96	#19.05(3/4) Brazed*1	#12.7(1/2) Brazed*1	ø34.9(1-3/8)	ø34.9(1-3/8)
HP120	#25.4(1) Brazed*1	#15.88(5/8) Brazed*1	ø41.3(1-3/8)	ø41.3(1-3/8)

*1 Connect the refrigerant pipe to the service valve according to the Installation Manual.

NO.	Usage	Specifications
①	Front through hole	146(5-7/8) x 84(3-5/8) Knockout hole
②	Bottom through hole	150(5-15/16) x 94(3-3/4) Knockout hole
③	Front through hole	ø62.7(2-1/2) or ø34.5(1-3/8) Knockout hole
④	Front through hole	ø45.7(1-3/4) or ø22.7(7/8) Knockout hole
⑤	Bottom through hole	ø65(2-9/16) Knockout hole
⑥	Bottom through hole	ø52(2-1/8) Knockout hole
⑦	Front through hole	ø34(1-3/8) Knockout hole
⑧	Bottom through hole	ø34(1-3/8) Knockout hole



1340 Satellite Boulevard Suwanee, GA 30024
Toll Free: 800-433-4822 www.mehvac.com

FORM# PURY-HP120TNU-A - 202204

