CP 011

CP 11 14-DAY CLEAN REMOVAL PAINT MASKING TAPE

TYPICAL APPLICATIONS
- Interior use on painted walls, glass, vinyl, metal and wood
- Not recommended for use on wallpaper, unpainted wallboard or ceiling tile

CONSTRUCTION
Backing: Fine structured crepe

Adhesive: Synthetic rubber-based adhesive

STANDARD WIDTHS
0.94 in; 1.41 in; 1.88 in; 2.83 in

24 mm; 36 mm; 48 mm; 72 mm

STANDARD LENGTH
60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE
3 in

APPLICABLE STANDARDS
NA

STORAGE & USAGE CONDITIONS
Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR
Blue (BLU)

PHYSICAL PROPERTIES	STANDARD	METRIC
Adhesion to Stainless Steel	28 oz/in width	3.1 N/10 mm
Elongation	9%	9%
Service Temperature Range	50 F to 150 F	10 C to 66 C
Tensile	22 lbs/in width	38.5 N/10 mm
Thickness	4.8 mils	0.12 mm

Physical and performance characteristics listed are obtained from tests recommended by PSTC, ASTM, government agencies or Colonial brand's quality assurance and technical service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



Shurtape Technologies, LLC | PO BOX 1530 Hickory, NC 28603-1530 USA | Phone 1.888.442.TAPE (8273) | Fax 800.335.7651 | shurtapetech.com
ISO 9001 CERTIFIED QUALITY SYSTEM
All trademarks listed are the property of Shurtape Technologies, LLC, unless otherwise noted. Form# -CP-011-20251007