

ARCHITECTURAL & ENGINEERING SPECIFICATION

Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior. Complete with chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. The valve incorporates a 6VDC motor actuator, a battery powered automatic sensor, high impact resistant polycarbonate housing and chrome plated plastic cover with manual override push button and 10 degree angled sensor.

PRODUCT FEATURES

- Control Stop has internal siphon-guard protection, sweat solder kit, wall flange with set screw.
- High back pressure Vacuum Breaker with one piece hex coupling nut
- Chloramine resistant Internal seals
- Clog resistant, triple filtered by pass
- Adjustable tailpiece
- Spud coupling and flange for top spud connection
- True mechanical override button

COMPLIANCE AND CERTIFICATION:

- ADA Compliant
- WaterSense Compliant



This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.



FLOW OPTIONS

	FLUSH VOLUME GPF	WATERSENSE COMPLIANT
-ONE	1.1	☑
-HET	1.28	☑
-WS1	1.6	
-STANDARD	3.5	

VALVE HEIGHT OPTIONS

	DIMENSION A INCH [MM]	DIMENSION B INCH [MM]
-STANDARD	11 1/2" [292]	9 7/8" [251]
-1	16" [406]	14 3/8" [365]
-2	24" [610]	22 3/8" [568]
-3	27" [686]	25 3/8" [645]

SUFFIX OPTIONS

- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rough-in/Overview dimensions:

