



**PFC500ALU**  
**Silicone sealant**

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Manufactured By:** Waterford Plant  
260 Hudson River Rd  
Waterford NY 12188

**Revised:** 09/02/2009

**Preparer:** PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS  
**CHEMTREC** 1-800-424-9300

**Chemical Family/Use:** Sealant  
**Formula:** Mixture

**HMIS**

Flammability: 1      Reactivity: 0      Health: 1

**NFPA**

Flammability: 1      Reactivity: 0      Health: 1

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

WARNING! May be harmful if swallowed, inhaled or absorbed through skin. Irritating to eyes, respiratory system and skin. May cause central nervous system depression.

**Form:** paste      **Color:** translucent      **Odor:** Acetic acid.

**POTENTIAL HEALTH EFFECTS**

**INGESTION**

May be harmful if swallowed. May cause central nervous system effects. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

**SKIN**

Uncured product contact will irritate lips, gums and tongue. Skin irritation is possible after contact with the uncured product. May be absorbed through skin and produce effects as listed under "Ingestion".

**INHALATION**

Causes mild respiratory tract irritation. Applies in uncured state. May also cause other effects as listed under "Ingestion".

**EYES**

Eye irritation on contact with the uncured product.

**MEDICAL CONDITIONS AGGRAVATED**

Pre-existing skin or respiratory diseases.

**SUBCHRONIC (TARGET ORGAN )**

Central nervous system; Skin

# Material Safety Data Sheet

Version: 1.0  
06/03/2014

## PFC500ALU Silicone sealant

### CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

### ROUTES OF EXPOSURE

Inhalation; Eyes; Dermal; Oral.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<b><u>A. HAZARDOUS</u></b>		
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE	64742-46-7	10 - 30 %
METHYLDIACETOXYISOPROPOX YSILANE	329039-38-5	0.1 - 1 %
METHYLTRIACETOXYSILANE	4253-34-3	1 - 5 %
<b><u>B. NON-HAZARDOUS</u></b>		
Treated Filler	68611-44-9	5 - 10 %
Dimethylpolysiloxane	70131-67-8	60 - 100 %

## 4. FIRST AID MEASURES

### INGESTION

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

### SKIN

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. If skin irritation persists, call a physician.

### INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

### EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

## PFC500ALU Silicone sealant

### NOTE TO PHYSICIAN

Treatment is symptomatic and supportive.

## 5. FIRE-FIGHTING MEASURES

**FLASH POINT:** > 93.3 °C; 200 °F  
**METHOD:** estimated  
**IGNITION TEMPERATURE:** no data available  
**FLAMMABLE LIMITS IN AIR - LOWER (%):** Unknown  
**FLAMMABLE LIMITS IN AIR - UPPER (%):** Unknown

**SENSITIVITY TO MECHANICAL IMPACT:** No

### SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

### EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

### SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES

### ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

## 7. HANDLING AND STORAGE

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Avoid contact with skin, eyes and clothing. Keep away from children. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation. Product releases acetic acid during application and curing.

### STORAGE

Store away from heat, sources of ignition, and incompatibles.

## PFC500ALU Silicone sealant

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### ENGINEERING CONTROLS

Eyewash stations; Showers; Use only in well-ventilated areas.

#### RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

#### PROTECTIVE GLOVES

Rubber gloves

#### EYE AND FACE PROTECTION

Safety glasses

#### OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

#### Exposure Guidelines

<u>Component</u>	<u>CAS RN</u>	<u>Source</u>	<u>Value</u>
------------------	---------------	---------------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>BOILING POINT - C &amp; F:</b>	not applicable
<b>VAPOR PRESSURE (20 C) (MM HG):</b>	Unknown
<b>VAPOR DENSITY (AIR=1):</b>	no data available
<b>FREEZING POINT:</b>	not applicable
<b>PHYSICAL STATE:</b>	paste
<b>ODOR:</b>	Acetic acid.
<b>COLOR:</b>	translucent
<b>EVAPORATION RATE (BUTYL ACETATE=1):</b>	< 1
<b>SPECIFIC GRAVITY (WATER=1):</b>	ca. 1.05
<b>DENSITY:</b>	ca. 1.050 g/cm3
<b>ACID / ALKALINITY (MEQ/G):</b>	no data available
<b>pH:</b>	not applicable
<b>SOLUBILITY IN WATER (20 C):</b>	insoluble

# Material Safety Data Sheet

Version: 1.0  
06/03/2014

## PFC500ALU Silicone sealant

**SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):** Soluble in toluene  
**VOLATILE ORGANIC CONTENT:** 2.8 %(m)  
**VOC EXCL. H2O & EXEMPTS (G/L):** 36 g/l

### 10. STABILITY AND REACTIVITY

#### STABILITY

Stable

#### HAZARDOUS POLYMERIZATION

Will not occur.

#### HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide (CO<sub>2</sub>); Carbon monoxide; Silicon dioxide.; Acetic acid.; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

#### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

#### CONDITIONS TO AVOID

None known.

### 11. TOXICOLOGICAL INFORMATION

#### ACUTE ORAL

Remarks: Unknown

#### ACUTE DERMAL

Remarks: Unknown

#### ACUTE INHALATION

Remarks: no data available

#### OTHER

None.

#### SENSITIZATION

no data available

#### SKIN IRRITATION

no data available

## PFC500ALU Silicone sealant

---

### EYE IRRITATION

no data available

### MUTAGENICITY

Unknown

### OTHER EFFECTS OF OVEREXPOSURE

Acetic acid released during curing.

## 12. ECOLOGICAL INFORMATION

### ECOTOXICITY

Ecotoxicological data for this product is not available.

### DISTRIBUTION

no data available

### CHEMICAL FATE

no data available

## 13. DISPOSAL CONSIDERATIONS

### DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORT INFORMATION

### Further Information:

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

## 15. REGULATORY INFORMATION

### Inventories

Japan Inventory of Existing & New Chemical Substances (ENCS)	y (positive listing)
Korea Existing Chemicals Inventory (KECI)	y (positive listing)
China Inventory of Existing	y (positive listing)

## **PFC500ALU Silicone sealant**

---

### Chemical Substances

Australia Inventory of Chemical Substances (AICS)	y (positive listing)	
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (positive listing)	
EU list of existing chemical substances	y (positive listing)	
Canada DSL Inventory	n (Negative listing)	
Canada NDSL Inventory	n (Negative listing)	
TSCA list	y (positive listing)	Not On TSCA Inventory

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

### US Regulatory Information

#### **SARA (311,312) HAZARD CLASS**

Acute Health Hazard

#### **SARA (313) CHEMICALS**

58-36-6, 10, 10'-oxybisphenoxarsine.

#### **CALIFORNIA PROPOSITION 65**

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

### Canadian Regulatory Information

#### **WHMIS HAZARD CLASS**

D2B - Toxic Material Causing Other Toxic Effects

## **16. OTHER INFORMATION**

### **OTHER**

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate., C = ceiling limit NEGL = negligible EST = estimated NF = none found  
NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor SKN = skin TS = trade secret R = recommended MST = mist NT = not tested STEL = short term exposure limit ppm = parts per million ppb = parts per billion By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).