Safety Data Sheet

24 Hour Emergency Phone Numbers Medical/Poison Control: In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison control center

Transportation/National Response Center:

> 1-800-535-5053 1-352-323-3500

NOTE: The National ResponseCenter emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

1. Identification

Product Name: PROFLO Aluminum Silicone Caulk

(PFC500ALUA)

Product UPC Number: PFC500ALUA

Manufacturer:

2400 Boston Street Suite 200 Baltimore, MD 21224-4723

888-327-8477 (non - emergency matters)

Revision Date: 5/22/2023

Supercedes Date: New SDS

Product Use/Class: Caulking Compound

SDS No: 6900962

Preparer: Regulatory and Environmental

Affairs

Emergency Telephone: 1-800-535-5053, 1-352-323-3500, 1-800-222-1222

2. Hazards Identification

EMERGENCY OVERVIEW: Under normal use conditions, this product is not expected to cause adverse health effects. High concentration of vapors may cause irritation to eyes and respiratory system.

GHS Classification

Not a hazardous substance or mixture.

Symbol(s) of Product

None

Signal Word

Not a hazardous substance or mixture.

Possible Hazards

7% of the mixture consists of ingredients of unknown acute toxicity

3. Composition/Information on Ingredients

Chemical Name CAS-No. Wt. % GHS Symbols GHS Statements

Hydrotreated middle distillate 64742-46-7 10-30 GHS07 H332

SDS Number: 6900962 SAP Number: Revision Date: 5/22/2023

Silica, amorphous 7631-86-9 3-7 GHS07 H332

Silanetriol, methyl-, triaceta 4253-34-3 1-5 GHS07 H302-312-315-319-332

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately,

Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog

Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN!DO NOT TAKE INTERNALLY. Avoid breathing vapor and contact with eyes, skin and clothing. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling. Remove contact lenses before using. Do not handle contact lenses until all sealant has been cleaned from fingertips, nails and cuticles. Residual sealant may transfer to contact lenses and cause severe eye irritation.

STORAGE: Avoid excessive heat and freezing. Do not store at temperatures above 120 °F (49 °C). Store away from caustics and oxidizers.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits **ACGIH-TLV STEL** Chemical Name ACGIH TLV-TWA **OSHA PEL-TWA** OSHA PEL-CEILING Hydrotreated middle distillate N.E. N.E. N.E. N.E. Silica, amorphous N.E. N.E. N.E. N.E. Silanetriol, methyl-, triaceta N.E. N.E. N.E. N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.



SKIN PROTECTION: Wear nitrile or neoprene gloves.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



HYGIENIC PRACTICES: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

Physical and Chemical Properties

Appearance: Aluminum Physical State: Paste

Odor Threshold: Not Established Odor: Acetic Acid Density, g/cm3: 0.96 - 0.96pH: Not Applicable Freeze Point, °C: Not Established Viscosity (mPa.s): Not Established Solubility in Water: Not Established Partition Coeff., n-octanol/water: Not Established Decomposition Temperature, °C: Not Established Explosive Limits, %: N.E. - N.E. Boiling Range, °C: 100 - 100 Auto-Ignition Temperature, °C Not Established Flash Point, °C: Vapor Pressure, mmHg: 100 Not Established Evaporation Rate: Slower Than n-Butyl Acetate Flash Method: Seta Closed Cup Flammability, NFPA:

Vapor Density: Heavier Than Air

Combustible Dust: Does not support combustion

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Oxidizing agents. Excessive heat and freezing. **INCOMPATIBILITY:** Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., COx, NOx.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Under normal use conditions, this product is not expected to cause adverse health effects. During application and cure, this product releases methanol. During application and cure, this product releases acetic acid. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury. Ingestion may result in obstruction when material hardens.

CARCINOGENICITY: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Repeated or prolonged exposure may cause mild irritation of eyes and skin. Constituents of this product include crystalline silica which ,if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

PRIMARY ROUTE(S) OF ENTRY: Skin Contact, Inhalation

Non-Flammable

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

| <u>CAS-No.</u> 64742-46-7 | Chemical Name Hydrotreated middle distillate | Oral LD50 7400 mg/kg Rat | Dermal LD50 >2000 mg/kg Rabbit | Vapor LC50 >20 mg/L |
|------------------------------|--|-----------------------------|-----------------------------------|------------------------|
| 7631-86-9 | Silica, amorphous | 7900 mg/kg Rat | >5000 mg/kg Rabbit | N.I. |
| 4253-34-3 | Silanetriol, methyl-, triaceta | 1602 mg/kg Rat | 1060 mg/kg Rabbit | 11.6 mg/L |

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

13. Disposal Information

DISPOSAL INFORMATION: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

14. Transport Information

DOT UN/NA Number: N.A.

DOT Proper Shipping Name: Not Regulated

DOT Technical Name: N.A.
DOT Hazard Class: N.A.
Hazard SubClass: N.A.
Packing Group: N.A.

SPECIAL TRANSPORT PRECAUTIONS: No Information

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None Known

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

SDS Number: 6900962 Revision Date: 5/22/2023 SAP Number:

16. Other Information

Revision Date: 5/22/2023 Supersedes Date: New MSDS

Periodic Update Reason for revision:

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health: Flammability: Reactivity: Personal Protection: 0 0 1

VOC Less Water Less Exempt Solvent, g/L: 28.9

VOC Material, g/L: 29

X

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 3.00

VOC Actual, Wt/Wt%: 3.0

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

| H302 | Harmful if swallowed. | |
|---------------------------------|-------------------------------|--|
| H312 | Harmful in contact with skin. | |
| H315 | Causes skin irritation. | |
| H319 Causes serious eve irritat | | |
| H332 | Harmful if inhaled | |

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS07



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

We believe the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.