FRIGIDAIRE.



FFAP5034W1

50 Pint Dehumidifier with Pump (Energy Star Most Efficient)

The Frigidaire 50 Pint Dehumidifier with Built-In Pump saves you time and energy normally spent manually emptying a water bucket by allowing the unit to discharge moisture in an upward direction, either into a sink or out of a window. Capture dust from the air and keep your dehumidifier working efficiently with our easy-to-clean washable filter. Front loading bucket with carrying handle and splash guard makes cleaning hassle-free.

Version: 05/23

Consumer Benefits

Easy-to-Clean Washable Filter

Capture dust from the air and keep your dehumidifier working efficiently with our easy-to-clean washable filter.

Custom Humidity Control

Maximize your comfort with customized control over the amount of humidity in your room.

Built-In Pump

Save time and energy normally spent manually emptying a water bucket! The built-in pump allows the unit to discharge moisture in an upward direction, either into a sink or out of a window.

Continuous Drain Option

Skip emptying the water bucket -- this unit continuously drains your dehumidifier so that you don't have to lift a finger.

Automatic Shut Off

Unit shuts off automatically when the water bucket is full.

Front Loading Bucket with Carrying Handle and Splash Guard

A water bucket is conveniently located in the front of the unit for easy access, while the carry handle and splash guard make emptying your bucket hassle-free.

Product Photography



Product Specifications

| Dehumidifier | | Performance | |
|--------------------------------|-------------|-------------------------------------|-------------|
| Air CFM (Low) | 174 CFM | Bucket Capacity | 2.2 Gallons |
| Air CFM (Med) | 191 CFM | Dehumidification - Pints per Day | 50 |
| Air CFM (High) | 235 CFM | Relative Humidity Minimum | 35 % |
| Fan Speeds - Fan | 3 | Relative Humidity Maximum | 85 % |
| Noise Level dBA (Low) | 47 dBA | Integrated Energy Factor (L/kWh) | 1.9 |
| Noise Level dBA (Med) | 49 dBA | | |
| Noise Level dBA (High) | 51 dBA | Controls | |
| Motor RPM (Low) | 890 RPM | Child Lock | No |
| Motor RPM (Med) | 980 RPM | Control Type | Electronic |
| Motor RPM (High) | 1160 RPM | | |
| Air Discharge | Top of Unit | Electrical Specifications | |
| Container Full Indication | Yes | Voltage Rating | 115 V |
| Digital Humidity Readout | Yes | Totalge Fatting | 110 (|
| Filter Access Location | Back | General Specifications | |
| Filter Check Indicator | Yes | Product Weight | 42 lbs |
| Low Temperature Operation | Yes | Prop 65 Label | Yes |
| Option for Advanced Filtration | No | Refrigerant Type | R-32 |
| Pump Feature | Yes | Warranty - Labor | 1 Year |
| Quick Glance Light | No | Warranty - Parts | 1 Year |
| Functions | | Commontinitus | |
| 24-Hour On/Off Timer | Yes | Connectivity Wi-Fi Enabled | N.T. |
| Auto Restart | Yes | wi-ri guadied | No |
| Auto Shut-Off | Yes | | |
| Clean Air Ionizer | No | Safety Certifications and Approvals | |
| Continuous Drain Operation | Yes | UL Listed | Yes |
| • | | cUL Listed | Yes |
| Dimensions and Volume | | | |
| Height | 24 3/4" | | |
| Width | 16" | | |
| Depth | 12 1/4" | | |

78''

Yes

Yes

Yes

InstallationPower Cord Length

Performance Certifications and Approvals

Energy Efficiency Verification (Canada)

ENERGY STAR Certified

ENERGY STAR Most Efficient