

VISUAL COMFORT & Co.

14210S-15: 6in Traverse Direct Round T24 3000K 90CRI Dimensions:
White



Diameter: 6.62"
Height: 1.12"
Weight: 0.4 lbs.

Wire: 6.5" (color:Black/White)
Mounting Proc.: Key Slots
Connection: Mounted To Box
Bulb Type: Modules
Bulb Type: Integrated
Volts: 120
Watts: 12
Watts Consumed: 12
Watts Rated: 12
Hours Rated: 50000
Lumens: 857
Bulb Temp: 3000 °K
CRI: 90

Bulbs:

1 - LEDIntegrated Modules 12.0w Max. 120v included

Features:

- Product complies with NEC 410.16 code and is closet rated.
- ENERGY STAR® Qualified
- This fixture is classified as a directional light source
- This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.
- Meets Title 24 energy efficiency standards
- Integrated LED fixtures that meet the high efficacy LED standards set forth in Title 24 and are listed in the California Energy Commission Appliance database.

Collection: Traverse Direct

Dimming range: 5%-100%

Featured in the decorative Traverse LED Lyte collection

ENERGY STAR® Qualified

This fixture is classified as a directional light source

This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.

UPC #:785652130557

Finish: White (15)

Material List:

1 Body - Steel - White

Safety Listing:

Safety Listed for Wet Locations

Instruction Sheets:

English (990TRAVIDRCT)

Shade / Glass / Diffuser Details:

Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
Lens	Polycarbonate	Frosted	1	640210-97			0.75	4.38				

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Frts. Class	UPS Ship
Individual	14210S-15	1	785652130557	4.0	4.1	2.1	0.02	0.45	65	Yes
Master Pack		20	10785652130554	14.9	13.0	7.7	0.86	12.0	65	Yes
NJ Pallet		1620		48.0	40.0	77.0	85.56	729.0		No
NV Pallet		1620		48.0	40.0	77.0	85.56	729.0		No