



#### ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V
Lumens:	1000L
CRI:	90
CCT (Kelvins):	2700K/3000K/3500K/4000K/5000K
Temperature:	Warm White to Natural Light
Beam Spread :	110
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 10 percent
Incandescent Equivalent :	75W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Replaceable Light Source :	No
Connection:	Direct Wired
Warranty:	5 Year Limited - Fixtures

#### PACKAGING

Each UPC:	045923118739
Each Quantity:	1
Each Dimensions:	8.46 x 3.74 x 7.68
Case UPC:	10045923118736
Case Quantity:	12
Case Dimensions:	17.32 x 11.81 x 15.94

#### INFO

Installation Note:	Driver Dimensions: 4.27 x 3.62 x 1.44
--------------------	---------------------------------------

Project/Job Name:

Location:

Fixture Type:

Notes:

**S11873** - 15 Watt LED Low Profile Recessed Baffle Downlight; 6 Inch; Remote Driver; CCT Selectable; Square Shape; White Finish; 120 Volt

- Air Tight
- Has Driver
- CCT Selectable
- IC Rated



#### PHYSICAL

Finish:	White
Lens Finish:	White
Lens Material:	Polystyrene (PS)
Finish Family:	White
Dimensions:	L:7.17" W:7.17" H:1.29"
Weight (Lbs.):	1.38
Material:	Aluminum

#### COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Wet
Indoor/Outoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2408270
Energy Star Lamp Category:	Downlight Recessed
DLC Approved:	No
UL/ETL Standard:	ANSI/UL 1598; CSA-C22.2 No. 250.0
CA Prop 65:	Lead
Closet Rated:	No
FCC Compliant:	Yes
IP Rating:	IP65
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions



**S11873** - 15 Watt LED Low Profile Recessed Baffle Downlight; 6 Inch; Remote Driver; CCT Selectable; Square Shape; White Finish; 120 Volt

## ACCESSORIES

---



**80-944** 6" Rough-In Remote Driver Mounting Plate

---



**80-951** Rough-In Mounting Plate; 6" with Junction Box

---



**80-985** 6 FOOT REMOTE DRIVER 3-PIN EXT

---