

13/0/15 14/13 4



100% MADE IN THE USA







GelCopper® Line Sets PREINSULATED COPPER ROLLS

APPLICATIONS

GelCopper® Line Sets provide the perfect size combination for applications requiring both suction and liquid lines to be insulated, such as ductless mini-splits, VRF and heat pumps.

TECHNICAL SPECS

INSULATION

Low Density Polyethylene Closed Cell Foam ASTM C 1427-07 compliant

Type I (tubular)

Grade I (insulation material for use on typical commercial system non-crosslinked)

CFC and HCFC gas free

ASME B35.1 and ANSI B9.1 compliant

Water vapor permeability: ASTM E96-00 compliant

Working temperature: ASTM C 1427-07 compliant from

-94 F to +250 F Wall thickness: 1/2"

Surface burning characteristics: UL723 CERTIFIED R39562 (ASTM E84 25/50), surface burning characteristics: flame spread 0, smoke developed 10. UL 94, top rated.

R-Value: 4.0

UV: This product is UL PERFORMANCE VERIFIED for UV resistance and successfully tested internally for UV resistance against any major degradation, discoloration or deterioration for a minimum of 5 years.

COPPER

Made in USA seamless anti corrosion copper tube for air conditioning and refrigeration. Manufactured according to ASTM B280 / ASTM B1003 - C12200 DHP - 700 PSI - 99.9% pure.



SPECIAL FEATURES

Anti-Corrosion Copper: Cu29BA patent pending technology provides strong anticorrosion properties to copper tubes reducing any risk of formicary/pitting corrosion.

Outer Jacket: Additional white polyethylene jacket cover protects foam insulation from tearing during installation process.

Foot Marking: Insulation incrementally marked every foot to reduce copper waste and ensure accurate initial unit charge.

R410: Can be used in applications where high-pressure gases are used as a refrigeration source.

Colors: Available in black or white insulation.

Paintable: The insulation can be painted to match the surroundings.



12/0/5 14:13 4









GelCopper® Line Sets PREINSULATED COPPER ROLLS

TRY IT, LOVE IT®

PRODUCT TABLE

PDM® PART NUMBER (both lines insulated)	LL	SL	INSULATION	LINE SETS (per pallet)	LENGTH (of coils)
F100.LSIN143812050	1/4	3/8	1/2	12	50 FT
F100.LSIN141212050	1/4	1/2	1/2	10	50 FT
F100.LSIN145812050	1/4	5/8	1/2	8	50 FT
F100.LSIN385812050	3/8	5/8	1/2	8	50 FT
F100.LSIN383412050	3/8	3/4	1/2	8	50 FT
F100.LSIN387812050	3/8	7/8	1/2	8	50 FT

Pallet quantities subject to change without notice.