

GAMMA™-FLEX XLPE









Cross-Linked Polyethylene Chemical Hose

Designed to handle a wide range of chemicals, solvents and corrosive liquids in both pressure and suction service.



TECHNICAL DATA

Tube	Clear, cross-linked polyethylene	
Cover	Green, EPDM (corrugated)	
Reinforcement	High tensile tire cord plies; dual helix wire	
Safety Factor	4:1	
Temperature	-40°F to +212°F	
Branding	TEXCEL® GAMMA™-FLEX XLPE - CHEMICAL SUCTION AND DISCHARGE HOSE 200 PSI W.P. XLPE TUBE	
Safety Note	Temperature rating depends on specific chemical conveyed and concentration	
Features	Exceptional flexibility	

 I.D.	 Part Number	 O.D.	 Std. Length	 Working Pressure (psi)	 Vacuum (in./HG)	 Bend Radius	 Lbs./Ft.
1"	GXL20F1-1.0	1- ³⁹ / ₆₄ "	100'/200'	200	29	2.5"	0.56
1-½"	GXL20F1-1.5	1- ⁶² / ₆₄ "	100'/200'	200	29	3"	0.80
2"	GXL20F1-2.0	2- ³² / ₆₄ "	100'/200'	200	29	4"	1.15
2-½"	GXL20F1-2.5	3"	100'/200'	200	29	5"	1.41
3"	GXL20F1-3.0	3- ³⁵ / ₆₄ "	100'/200'	200	29	6"	1.89
4"	GXL20F1-4.0	4- ³⁹ / ₆₄ "	100'/200'	200	29	8"	2.69