

# Engineering Data Book



# TABLE OF CONTENTS

<b>4-WAY CASSETTE BASIC INFORMATION.....</b>	<b>3</b>
Specifications.....	3
Accessories.....	7
<b>PIPING DIAGRAM.....</b>	<b>8</b>
<b>DIMENSIONS.....</b>	<b>9</b>
<b>WIRING DIAGRAM.....</b>	<b>10</b>
<b>ELECTRICAL CHARACTERISTICS.....</b>	<b>12</b>
<b>AIR THROW CHARTS.....</b>	<b>13</b>
<b>SOUND DATA.....</b>	<b>21</b>
Sound Pressure Levels.....	21
NC Curves.....	22
<b>CAPACITY DATA TABLES.....</b>	<b>24</b>

## 4-WAY CASSETTE BASIC INFORMATION

### Specifications

**Table 1 —Data Table**

MODEL			40VMF009A--3	40VMF012A--3
Power Supply	V/Ph/Hz	208/230-1-60		
Total Cooling Capacity *1	Btu/h	9,000	12,000	
Sensible Cooling Capacity *1	Btu/h	8,620	10,880	
Heating Capacity *1	Btu/h	10,000	13,500	
MCA	A	0.73	0.91	
MOCP	A	15		
Panel / Grille	40VMF001----			
Dimensions of Unit (H x W x D)	in.	9 x 33-1/8 x 33-1/8		
Dimensions of Panel / Grille (H x W x D)	in.	1-3/4 x 37-3/8 x 37-3/8		
Net Unit Weight	lbs	54		
Net Panel / Grille Weight	lbs	13.2		
Filter	Dimensions L x H x D	in.	19-5/8 x 20-3-8 x 3/4	
	Qty	1 (Installed in Panel / Grille)		
Heat Exchanger	Inner Groove Copper Tube and Hydrophilic Aluminum fin			
Blower / Motor	Fan Type	Centrifugal		
	Motor Type	DC motor		
	Air Flow Rate (H/M/L)	CFM	460/390/330	560/460/390
	Sound Pressure Level (H/M/L)*2	dBa	36.7/34.0/32.1	41.4/37.3/33.0
	Motor Input	W	40	54
Min. External Static Pressure (Factory Setting)	in. WG	0		
Max. External Static Pressure	in. WG	0.12		
Piping Connections	Gas (Low) Pressure	in.	1/2	
	Liquid (High) Pressure	in.	1/4	
	Condensate	in.	1-1/4	
Condensate Lift	in.	29-1/2		
Refrigerant Control	Electronic Expansion Valve			
Connectable Outdoor Unit	38VMH – Heat Pump 38VMR – Heat Recovery 38VMH-1P – Single Phase Heat Pump			
Wiring	Power Wiring	AWG	Sized per NEC and Local Codes based on Nameplate Electrical Data	
	Control Wiring	AWG	2-core stranded shielded cable 18AWG	

**NOTES:**

- \* 1. Rated per AHRI (Air Conditioning, Heating, and Refrigeration Institute) 1230 Standard  
Cooling: Indoor 80°F (27°C) db / 67°F (20°C) wb; Outdoor 95°F (35°C) db  
Heating: Indoor 70°F (21°C) db; Outdoor 47°F (8°C) db / 43°F (6°C) wb
- \* 2. These values are measured in anechoic chamber at a distance of 4.6 feet below the unit.

**Table 2 —Data Table**

MODEL			40VMF015A--3	40VMF018A--3	
Power Supply		V/Ph/Hz	208/230-1-60		
Total Cooling Capacity *1		Btu/h	15,000	18,000	
Sensible Cooling Capacity *1		Btu/h	13,370	18,220	
Heating Capacity *1		Btu/h	17,000	21,000	
MCA		A	1.1	2.0	
MOCP		A	15		
Panel / Grille			40VMF001----		
Dimensions of Unit (H x W x D)		in.	9 x 33-1/8 x 33-1/8	11-3/4 x 33-1/8 x 33-1/8	
Dimensions of Panel / Grille (H x W x D)		in.	1-3/4 x 37-3/8 x 37-3/8		
Net Unit Weight		lbs	54.0	69.0	
Net Panel / Grille Weight		lbs	13.2		
Filter	Dimensions L x H x D		in. 19-5/8 x 20-3-8 x 3/4		
	Qty		1 (Installed in Panel / Grille)		
Heat Exchanger			Inner Groove Copper Tube and Hydrophilic Aluminum fin		
Blower / Motor	Fan Type		Centrifugal		
	Motor Type		DC motor		
	Air Flow Rate (H/M/L)		CFM	680/560/460	1000/700/610
	Sound Pressure Level (H/M/L)*2		dBA	45.6/41.5/37.0	52.5/43.1/40.2
	Motor Input		W	67	153.5
Min. External Static Pressure (Factory Setting)		in. WG	0		
Max. External Static Pressure		in. WG	0.12		
Piping connections	Gas (Low) Pressure		in.	1/2	5/8
	Liquid (High) Pressure		in.	1/4	3/8
	Condensate		in.	1-1/4	
Condensate Lift		in.	29-1/2		
Refrigerant Control			Electronic Expansion Valve		
Connectable Outdoor Unit			38VMH – Heat Pump 38VMR – Heat Recovery 38VMH-1P – Single Phase Heat Pump		
Wiring	Power Wiring		AWG	Sized per NEC and Local Codes based on Nameplate Electrical Data	
	Control Wiring		AWG	2-core stranded shielded cable 18AWG	

**NOTES:**

- \* 1. Rated per AHRI (Air Conditioning, Heating, and Refrigeration Institute) 1230 Standard  
Cooling: Indoor 80°F (27°C) db / 67°F (20°C) wb; Outdoor 95°F (35°C) db  
Heating: Indoor 70°F (21°C) db; Outdoor 47°F (8°C) db / 43°F (6°C) wb
- \* 2. These values are measured in anechoic chamber at a distance of 4.6 feet below the unit.

**Table 3 —Data Table**

MODEL			40VMF024A--3	40VMF030A--3
Power Supply		V/Ph/Hz	208/230-1-60	
Total Cooling Capacity *1		Btu/h	24,000	30,000
Sensible Cooling Capacity *1		Btu/h	18,350	22,330
Heating Capacity *1		Btu/h	27,000	34,000
MCA		A	1.3	1.7
MOCP		A	15	
Panel / Grille			40VMF001----	
Dimensions of Unit (H x W x D)		in.	11-3/4 x 33-1/8 x 33-1/8	
Dimensions of Panel / Grille (H x W x D)		in.	1-3/4 x 37-3/8 x 37-3/8	
Net Unit Weight		lbs	69.0	
Net Panel / Grille Weight		lbs	13.2	
Filter	Dimensions L x H x D	in.	19-5/8 x 20-3-8 x 3/4	
	Qty		1 (Installed in Panel / Grille)	
Heat Exchanger			Inner Groove Copper Tube and Hydrophilic Aluminum fin	
Blower / Motor	Fan Type		Centrifugal	
	Motor Type		DC motor	
	Air Flow Rate (H/M/L)	CFM	800/700/610	950/800/680
	Sound Pressure Level (H/M/L)*2	dBA	44.7/42.5/40.2	49.5/45.1/42.1
	Motor Input	W	85.4	131.7
Min. External Static Pressure (Factory Setting)		in. WG	0	
Max. External Static Pressure		in. WG	0.12	
Piping connections	Gas (Low) Pressure	in.	5/8	
	Liquid (High) Pressure	in.	3/8	
	Condensate	in.	1-1/4	
Condensate Lift		in.	29-1/2	
Refrigerant Control			Electronic Expansion Valve	
Connectable Outdoor Unit			38VMH – Heat Pump 38VMR – Heat Recovery 38VMH-1P – Single Phase Heat Pump	
Wiring	Power Wiring	AWG	Sized per NEC and Local Codes based on Nameplate Electrical Data	
	Control Wiring	AWG	2-core stranded shielded cable 18AWG	

**NOTES:**

- \* 1. Rated per AHRI (Air Conditioning, Heating, and Refrigeration Institute) 1230 Standard  
Cooling: Indoor 80°F (27°C) db / 67°F (20°C) wb; Outdoor 95°F (35°C) db  
Heating: Indoor 70°F (21°C) db; Outdoor 47°F (8°C) db / 43°F (6°C) wb
- \* 2. These values are measured in anechoic chamber at a distance of 4.6 feet below the unit.

**Table 4 —Data Table**


















MODEL			40VMF036A--3	40VMF048A--3
Power Supply		V/Ph/Hz	208/230-1-60	
Total Cooling Capacity *1		Btu/h	36,000	48,000
Sensible Cooling Capacity *1		Btu/h	26,240	32,390
Heating Capacity *1		Btu/h	40,000	54,000
MCA		A	2.3	2.4
MOCP		A	15	
Panel / Grille			40VMF001----	
Filter			Installed in Panel / Grille	
Dimensions of Unit (H x W x D)		in.	11-3/4 x 33-1/8 x 33-1/8	
Dimensions of Panel / Grille (H x W x D)		in.	1-3/4 x 37-3/8 x 37-3/8	
Net Unit Weight		lbs	69.0	
Net Panel / Grille Weight		lbs	13.2	
Filter	Dimensions L x H x D	in.	19-5/8 x 20-3-8 x 3/4	
	Qty		1 (Installed in Panel / Grille)	
Heat Exchanger			Inner Groove Copper Tube and Hydrophilic Aluminum fin	
Blower / Motor	Fan Type		Centrifugal	
	Motor Type		DC motor	
	Air Flow Rate (H/M/L)	CFM	1100/950/800	1200/1100/950
	Sound Pressure Level (H/M/L)*2	dBA	53.9/50.4/47.3	55.4/54.0/50.5
	Motor Input	W	182.7	202.3
Min. External Static Pressure (Factory Setting)		in. WG	0	
Max. External Static Pressure		in. WG	0.12	
Piping connections	Gas (Low) Pressure		in. 5/8	
	Liquid (High) Pressure		in. 3/8	
	Condensate		in. 1-1/4	
Condensate Lift		in.	29-1/2	
Refrigerant Control			Electronic Expansion Valve	
Connectable Outdoor Unit			38VMH – Heat Pump 38VMR – Heat Recovery 38VMH-1P – Single Phase Heat Pump	
Wiring	Power Wiring	AWG	Sized per NEC and Local Codes based on Nameplate Electrical Data	
	Control Wiring	AWG	2-core stranded shielded cable 18AWG	

**NOTES:**

- \* 1. Rated per AHRI (Air Conditioning, Heating, and Refrigeration Institute) 1230 Standard  
Cooling: Indoor 80°F (27°C) db / 67°F (20°C) wb; Outdoor 95°F (35°C) db  
Heating: Indoor 70°F (21°C) db; Outdoor 47°F (8°C) db / 43°F (6°C) wb
- \* 2. These values are measured in anechoic chamber at a distance of 4.6 feet below the unit.

## Accessories


**Table 5 —Table of Accessories**

NAME	SHAPE	QUANTITY	FUNCTION
Nut		8	To connect the construction cover board to the fan motor
Washer		8	To connect the construction cover board to the fan motor
Construction cover board		1	Used to cover the fan motor
Bolt		4	To connect the construction cover board to the fan motor
Insulation		2	For covering the coil stub outs
Insulation		1	For covering the condensate drain
Clamp		1	For connecting the drain
Tie rope		5	For insulation
Condensate connection		1	For connecting drain
PQ connection wire		2	To connect outdoor unit, indoor unit, and sub MDC
Copper Nut		1	Connect piping
Flexible conduit and connectors		1	Routing power lines
Field wiring conduit assembly instruction		1	Guide for installing the conduit assembly
Connection Wire		1	For connecting occupancy sensor
Copper pipe for gas side		1	For connecting refrigerant pipe
Copper pipe for liquid side		1	For connecting refrigerant pipe
No Beep Harness		1	Prevent beeping noise

**LEGEND:**

MDC – Multiport Distribution Controller

## PIPING DIAGRAM



**Fig. 1 —Piping**

**Table 6 —Piping**


NUMBER	SYMBOL	NAME
1	T1	Room temperature sensor
2	T2A	Inlet pipe temperature sensor
3	T2B	Outlet pipe temperature sensor
4	EEV	Electronic expansion valve

**Table 7 —Gas/Liquid Line Sizes**

MODEL	GAS	LIQUID
40VMF009A/012A/015A--3	1/2	1/4
40VMF018A/024A/030A/036A/48A--3	5/8	3/8



# DIMENSIONS




**NOTE:** All dimensions are shown in inches.

40VMF UNIT SIZE	DIMENSION A
009A	9
012A	
015A	
018A	11-3/4
024A	
030A	
036A	
048A	

**Fig. 2 —40VMF009A--3 to 40VMF048A--3**

# WIRING DIAGRAM



## LEGEND:



ACB	—	Auxiliary Control Board AUXH	FM	—	Indoor Fan Motor	T1	—	Inlet Air Temperature
AUXH	—	Output For Auxiliary Heat	GM	—	Louver Motor	T2A	—	Coil Temperature
CS	—	Condensate Switch	HTON	—	Output for Heating Operation	T2B	—	Evap. Outlet Temperature in Cooling Mode
CTON	—	Output for Cooling Operation	MDC	—	Multiport Distribution Controller	XP1-9	—	Plug
EEV	—	Electronic Expansion Valve	PUMP	—	Pump Motor	XS1-9	—	Jack
FAN	—	DC Indoor Fan				XP-7/XS7	—	Connector

# Wiring Diagram Definitions and Settings (40VMF009A--3 to 40VMF048A--3)



**Table 8 —Code / Title**

CODE	TITLE
FM	Indoor Fan Motor
T1	Room Temperature Sensor
T2A	Inlet Pipe Temperature Sensor
T2B	Outlet Pipe Temperature Sensor
ALARM	Warning Lamp
EEV	Electronic Extension Valve
XP1-8	Connectors
XS1-6	
XT1	Terminal
PUMP	Pump Motor
CS	Condensate Switch
GM	Swing Motor








**Table 9 —ENC1 / ENC2**

	Reserved		Reserved
---	----------	---	----------

**Table 10 —SW8 Definition**

	Reserved
	Reserved

**Table 11 —SW1 Definition**

	0 means auto addressing mode (Default)
	1 means factory test mode
	0 means normal mode (Default)
	1 means factory self-checking mode (Reserved)
	Reserved
	0 means standard indoor unit (Default)
	1 means main indoor unit (must be addressed #63)

**Table 12 —0/1 Definition**

	Means 0
	Means 1

**Table 13 —Error Code / Content**

dd	Heating / Cooling Conflict
E1	Communication Error with Outdoor Unit
E2	Temperature Sensor (T1) Error
E4	Temperature Sensor (T2B) Error
E5	Temperature Sensor (T2A) Error
E6	DC Fan Error
E7	EEPROM Error (Data Storage)
UU	MDC Error in Auto System-Check Mode
E9	Communication Error with Wired Controller
Eb	EEV Error
EC	Indoor Fan Error in Auto System-Check Mode
Ed	Outdoor Unit Error
EE	Condensate Error
FE	No Address when Powered On for the First Time

# ELECTRICAL CHARACTERISTICS

**Table 14 —Electrical Characteristics**

MODEL	POWER SUPPLY				IFM		
	Hz	VOLTS	VOLTAGE RANGE	MCA	MOCP	W	FLA
40VMF009A--3	60	208/230V	Max.253V Min.187V	0.73	15	80	0.59
40VMF012A--3				0.91	15	80	0.72
40VMF015A--3				1.1	15	170	0.81
40VMF018A--3				2.0	15	170	1.60
40VMF024A--3				1.3	15	170	0.98
40VMF030A--3				1.7	15	170	1.40
40VMF036A--3				2.3	15	170	1.80
40VMF048A--3				2.4	15	170	2.00

MCA: Minimum Circuit Amps (A)

MOCP: Maximum Over Current Protection (A)

SYMBOLS: W: Fan Motor Rated Output (W)

FLA: Full Load Amps (A)

IFM: Indoor Fan Motor

# AIR THROW CHARTS

40VMF009A--3




Fig. 4 —Cooling Velocity




Fig. 5 —Heating Velocity

Unit: m/s (ft/s)




Fig. 6 —Cooling mode with 60°swing

Unit: m/s (ft/s)




Fig. 7 —Heating mode with 60°swing

Unit: m/s (ft/s)




Fig. 8 —Cooling mode with 60°swing

Unit: m/s (ft/s)




Fig. 9 —Heating mode with 60°swing

Unit: m/s (ft/s)




Fig. 10 —Cooling mode with 60°swing

Unit: m/s (ft/s)




Fig. 11 —Heating mode with 60°swing



Unit: m/s (ft/s)




Fig. 12 —Cooling mode with 60°swing

Unit: m/s (ft/s)




Fig. 13 —Heating mode with 60°swing

Unit: m/s (ft/s)




Fig. 14 —Cooling mode with 60°swing

Unit: m/s (ft/s)




Fig. 15 —Heating mode with 60°swing

Unit: m/s (ft/s)




Fig. 16 —Cooling mode with 60°swing

Unit: m/s (ft/s)




Fig. 17 —Heating mode with 60°swing

Unit: m/s (ft/s)




Fig. 18 —Cooling mode with 60°swing

Unit: m/s (ft/s)





Fig. 19 —Heating mode with 60°swing

**SOUND DATA**

**Sound Pressure Levels**



**Fig. 20 —Overall Sound Levels**

**Table 15 —Cooling Mode**

MODEL	H	M	L
40VMF009A--3	36.7	34.0	32.1
40VMF012A--3	41.3	37.3	33.0
40VMF015A--3	45.2	41.5	36.9
40VMF018A--3	52.5	43.1	40.2
40VMF024A--3	44.6	42.5	40.2
40VMF030A--3	48.8	45.1	42.1
40VMF036A--3	53.4	50.0	47.3
40VMF048A--3	55.1	52.8	50.2


**NOTE:** Units are in dBA

**Table 16 —Heating Mode**


MODEL	H	M	L
40VMF009A--3	36.3	32.6	29.3
40VMF012A--3	41.4	36.5	32.6
40VMF015A--3	45.6	40.7	37.0
40VMF018A--3	52.8	42.7	39.4
40VMF024A--3	44.7	41.4	38.5
40VMF030A--3	48.9	44.7	41.4
40VMF036A--3	53.9	50.4	46.8
40VMF048A--3	55.1	54.0	50.5

**NOTE:** Units are in dBA


# NC Curves




**Fig. 21 —40VMF009A--3**



**Fig. 22 —40VMF012A--3**




**Fig. 23 —40VMF015A--3**




**Fig. 24 —40VMF018A--3**


# NC Curves (Cont.)




**Fig. 25 —40VMF024A--3**



**Fig. 26 —40VMF030A--3**



**Fig. 27 —40VMF036A--3**



**Fig. 28 —40VMF048A--3**

# CAPACITY DATA TABLES

## Table 17 —Cooling Capacity

Model	Outdoor air temp.	Indoor air temp.													
		71 °FDB/59 °FWB		73 °FDB/61 °FWB		77 °FDB/64 °FWB		80 °FDB/67 °FWB		82 °FDB/68 °FWB		86 °FDB/72 °FWB		90 °FDB/75 °FWB	
9	68	8.2	8.1	8.7	8.5	9.2	9.0	9.8	9.3	10.0	9.7	10.7	9.7	11.2	10.1
	73	8.2	8.1	8.7	8.5	9.2	9.0	9.8	9.3	10.0	9.7	10.7	9.7	11.2	10.0
	77	8.1	8.1	8.7	8.5	9.2	8.9	9.7	9.2	9.9	9.6	10.5	9.6	11.0	9.9
	82	8.1	8.0	8.5	8.4	9.0	8.9	9.5	9.1	9.7	9.5	10.3	9.5	10.8	9.9
	86	8.1	8.0	8.4	8.4	8.9	8.8	9.4	9.0	9.6	9.4	10.2	9.4	10.6	9.8
	91	7.9	7.9	8.2	8.2	8.7	8.7	9.2	8.9	9.3	9.3	9.9	9.2	10.4	9.6
	95	7.8	7.8	8.1	8.1	8.6	8.6	9.0	8.8	9.2	9.2	9.7	9.1	10.2	9.5
	100	7.7	7.7	8.0	8.0	8.4	8.4	8.8	8.8	9.0	9.0	9.5	9.1	9.9	9.4
	104	7.6	7.6	7.8	7.8	8.2	8.2	8.6	8.6	8.8	8.8	9.3	9.0	9.7	9.3
	110	7.4	7.4	7.6	7.6	7.9	7.9	8.4	8.4	8.5	8.5	9.1	8.8	9.4	9.1
12	68	10.9	10.1	11.6	10.2	12.3	10.7	13.0	10.6	13.4	11.1	14.3	11.0	15.0	11.3
	73	10.9	10.1	11.6	10.2	12.3	10.6	13.0	10.5	13.3	11.1	14.2	10.9	14.9	11.3
	77	10.9	10.1	11.6	10.2	12.2	10.6	13.0	10.5	13.2	11.0	14.0	10.8	14.7	11.2
	82	10.8	10.0	11.4	10.1	12.0	10.5	12.7	10.3	12.9	10.9	13.7	10.7	14.4	11.1
	86	10.7	9.9	11.2	10.0	11.9	10.4	12.5	10.2	12.8	10.8	13.5	10.6	14.1	11.0
	91	10.6	9.8	11.0	9.8	11.6	10.3	12.2	10.1	12.4	10.7	13.2	10.4	13.8	10.8
	95	10.4	9.7	10.8	9.7	11.4	10.1	12.0	10.0	12.2	10.5	13.0	10.3	13.6	10.7
	100	10.2	9.6	10.6	9.6	11.2	10.0	11.8	9.8	12.0	10.4	12.7	10.2	13.2	10.6
	104	10.1	9.5	10.4	9.5	10.9	9.9	11.5	9.8	11.7	10.3	12.4	10.1	13.0	10.5
	110	9.9	9.4	10.2	9.4	10.6	9.7	11.2	9.7	11.4	10.1	12.1	9.9	12.6	10.3
15	68	13.6	12.4	14.5	12.6	15.4	13.1	16.3	13.0	16.7	13.7	17.8	13.5	18.7	13.9
	73	13.6	12.4	14.5	12.5	15.4	13.0	16.3	12.9	16.7	13.6	17.8	13.4	18.7	13.8
	77	13.6	12.3	14.5	12.5	15.3	13.0	16.2	12.9	16.6	13.5	17.5	13.3	18.4	13.7
	82	13.5	12.3	14.2	12.4	15.1	12.9	15.9	12.7	16.2	13.4	17.1	13.2	18.0	13.6
	86	13.4	12.2	14.0	12.3	14.9	12.8	15.6	12.6	16.0	13.2	16.9	13.0	17.7	13.5
	91	13.2	12.1	13.7	12.0	14.6	12.7	15.3	12.4	15.6	13.1	16.5	12.8	17.3	13.2
	95	13.0	12.0	13.5	11.9	14.3	12.4	15.0	12.3	15.3	12.9	16.2	12.7	17.0	13.1
	100	12.8	11.8	13.3	11.8	14.0	12.3	14.7	12.1	14.9	12.8	15.8	12.6	16.5	13.0
	104	12.6	11.7	13.0	11.7	13.7	12.2	14.4	12.0	14.6	12.6	15.5	12.4	16.2	12.8
	110	12.4	11.6	12.7	11.6	13.3	12.0	14.0	11.9	14.2	12.4	15.1	12.2	15.7	12.6
18	68	16.4	14.6	17.4	14.8	18.5	15.4	19.6	15.3	20.0	16.1	21.4	15.8	22.4	16.3
	73	16.3	14.6	17.4	14.8	18.4	15.4	19.5	15.2	20.0	16.0	21.3	15.8	22.4	16.3
	77	16.3	14.5	17.4	14.7	18.4	15.3	19.4	15.2	19.9	15.9	21.0	15.6	22.0	16.1
	82	16.2	14.5	17.1	14.6	18.1	15.2	19.1	14.9	19.4	15.7	20.6	15.5	21.6	16.0
	86	16.1	14.4	16.8	14.5	17.8	15.1	18.7	14.8	19.1	15.6	20.3	15.3	21.2	15.8
	91	15.9	14.2	16.5	14.2	17.5	14.9	18.4	14.7	18.7	15.4	19.8	15.1	20.7	15.5
	95	15.6	14.1	16.2	14.1	17.1	14.6	18.0	14.5	18.3	15.2	19.5	14.9	20.4	15.4
	100	15.4	13.9	16.0	13.9	16.7	14.5	17.6	14.2	17.9	15.0	19.0	14.8	19.8	15.2
	104	15.1	13.8	15.6	13.8	16.4	14.4	17.3	14.1	17.6	14.9	18.7	14.6	19.4	15.1
	110	14.9	13.7	15.2	13.6	15.9	14.1	16.8	14.0	17.1	14.6	18.2	14.4	18.8	14.8



Model	Outdoor air temp.	Indoor air temp.													
		71 °FDB/59 °FWB		73 °FDB/61 °FWB		77 °FDB/64 °FWB		80 °FDB/67 °FWB		82 °FDB/68 °FWB		86 °FDB/72 °FWB		90 °FDB/75 °FWB	
24	68	21.8	18.0	23.2	18.3	24.6	19.0	26.1	18.8	26.7	19.7	28.5	19.4	29.9	19.9
	73	21.8	18.0	23.2	18.2	24.6	18.9	26.0	18.8	26.6	19.6	28.5	19.3	29.9	19.9
	77	21.7	18.0	23.2	18.2	24.5	18.8	25.9	18.7	26.5	19.6	28.1	19.2	29.4	19.7
	82	21.6	17.9	22.7	18.1	24.1	18.7	25.4	18.4	25.8	19.3	27.4	19.0	28.7	19.5
	86	21.5	17.8	22.4	17.9	23.8	18.6	25.0	18.2	25.5	19.1	27.1	18.8	28.3	19.3
	91	21.2	17.6	21.9	17.5	23.3	18.4	24.5	18.1	24.9	18.9	26.5	18.5	27.6	19.0
	95	20.8	17.4	21.6	17.4	22.8	18.0	<b>24.0</b>	17.9	24.4	18.6	26.0	18.3	27.2	18.8
	100	20.5	17.2	21.3	17.2	22.3	17.9	23.5	17.5	23.9	18.4	25.3	18.1	26.4	18.6
	104	20.2	17.1	20.8	17.0	21.8	17.7	23.0	17.4	23.4	18.2	24.9	18.0	25.9	18.4
	110	19.9	16.9	20.3	16.8	21.2	17.3	22.4	17.2	22.8	17.9	24.2	17.6	25.1	18.1
30	68	27.3	21.3	29.0	21.7	30.8	22.4	32.6	22.2	33.4	23.2	35.7	22.8	37.4	23.4
	73	27.2	21.3	29.0	21.6	30.7	22.3	32.5	22.1	33.3	23.1	35.6	22.8	37.3	23.3
	77	27.1	21.2	28.9	21.5	30.6	22.2	32.4	22.0	33.1	23.0	35.1	22.6	36.7	23.1
	82	27.0	21.2	28.4	21.4	30.1	22.1	31.8	21.7	32.3	22.7	34.3	22.4	35.9	22.9
	86	26.8	21.0	28.0	21.2	29.7	21.9	31.2	21.5	31.9	22.5	33.9	22.1	35.4	22.7
	91	26.4	20.8	27.4	20.8	29.1	21.7	30.6	21.3	31.1	22.3	33.1	21.7	34.6	22.3
	95	26.0	20.6	27.0	20.6	28.5	21.3	<b>30.0</b>	21.1	30.5	21.9	32.5	21.5	34.0	22.1
	100	25.6	20.4	26.6	20.4	27.9	21.1	29.4	20.7	29.9	21.7	31.7	21.3	33.0	21.8
	104	25.2	20.2	26.0	20.1	27.3	20.9	28.8	20.5	29.3	21.4	31.1	21.1	32.4	21.6
	110	24.8	20.0	25.4	19.9	26.5	20.5	28.0	20.3	28.5	21.0	30.3	20.7	31.4	21.2
36	68	32.7	25.6	34.9	26.1	37.0	26.9	39.1	26.7	40.1	27.9	42.8	27.5	44.9	28.1
	73	32.7	25.6	34.8	26.0	36.9	26.8	39.0	26.6	40.0	27.8	42.7	27.4	44.8	28.0
	77	32.6	25.6	34.7	25.9	36.7	26.7	38.9	26.5	39.7	27.7	42.1	27.1	44.1	27.8
	82	32.5	25.5	34.1	25.7	36.1	26.6	38.2	26.1	38.8	27.3	41.1	26.9	43.1	27.5
	86	32.2	25.3	33.6	25.5	35.7	26.3	37.4	25.9	38.3	27.1	40.7	26.7	42.4	27.3
	91	31.7	25.0	32.9	25.0	34.9	26.1	36.7	25.6	37.3	26.8	39.7	26.2	41.5	26.8
	95	31.2	24.8	32.4	24.7	34.2	25.6	<b>36.0</b>	25.4	36.6	26.3	39.0	25.9	40.8	26.5
	100	30.8	24.5	31.9	24.5	33.5	25.3	35.3	24.9	35.9	26.1	38.0	25.7	39.6	26.3
	104	30.3	24.3	31.2	24.2	32.8	25.1	34.6	24.7	35.2	25.8	37.3	25.4	38.9	26.0
	110	29.8	24.0	30.5	24.0	31.8	24.6	33.6	24.4	34.2	25.3	36.3	24.9	37.7	25.5
48	68	43.6	31.6	46.5	32.2	49.3	33.2	52.2	32.9	53.4	34.2	57.1	33.7	59.8	34.3
	73	43.5	31.6	46.4	32.1	49.2	33.1	52.0	32.8	53.3	34.1	56.9	33.6	59.7	34.2
	77	43.4	31.6	46.3	32.0	49.0	32.9	51.8	32.7	53.0	33.9	56.1	33.3	58.8	33.9
	82	43.3	31.5	45.5	31.8	48.2	32.7	50.9	32.2	51.7	33.5	54.8	33.0	57.5	33.6
	86	43.0	31.2	44.9	31.5	47.5	32.4	49.9	31.9	51.0	33.2	54.2	32.7	56.6	33.3
	91	42.3	30.9	43.9	30.9	46.6	32.1	49.0	31.6	49.8	32.8	52.9	32.1	55.3	32.7
	95	41.7	30.6	43.2	30.6	45.6	31.5	<b>48.0</b>	31.3	48.8	32.2	52.0	31.8	54.4	32.4
	100	41.0	30.3	42.6	30.3	44.7	31.2	47.0	30.7	47.8	31.9	50.7	31.5	52.8	32.0
	104	40.3	30.0	41.6	30.0	43.7	30.9	46.1	30.4	46.9	31.6	49.7	31.2	51.8	31.7
	110	39.7	29.7	40.7	29.7	42.4	30.3	44.8	30.1	45.6	31.0	48.5	30.6	50.2	31.1

TC : Total Cooling

SC : Sensible Cooling

**Table 18 —Heating Capacity**

Model	Outdoor air temp.	Indoor air temp.			
		59 °DB	70 °DB	77 °DB	81 °DB
kbtu/h	degF D.B	TC	TC	TC	TC
9	5	5.9	6.4	6.1	5.8
	14	6.9	7.4	7.1	6.8
	23	8.0	8.4	8.1	7.5
	32	9.1	9.4	8.4	7.5
	37	9.7	10.0	8.4	7.5
	43	10.3	10.0	8.4	7.5
	47	10.7	10.0	8.4	7.5
	50	11.2	10.0	8.4	7.5
	55	11.6	10.0	8.4	7.5
	60	11.6	10.0	8.4	7.5
12	5	7.9	8.6	8.2	7.9
	14	9.4	10.0	9.6	9.2
	23	10.8	11.4	11.0	10.2
	32	12.2	12.7	11.4	10.2
	37	13.0	13.5	11.4	10.2
	43	13.9	13.5	11.4	10.2
	47	14.5	13.5	11.4	10.2
	50	15.1	13.5	11.4	10.2
	55	15.7	13.5	11.4	10.2
	60	15.7	13.5	11.4	10.2
15	5	9.9	10.9	10.4	9.9
	14	11.8	12.6	12.1	11.6
	23	13.6	14.3	13.8	12.8
	32	15.4	16.0	14.3	12.8
	37	16.4	17.0	14.3	12.8
	43	17.5	17.0	14.3	12.8
	47	18.3	17.0	14.3	12.8
	50	19.0	17.0	14.3	12.8
	55	19.7	17.0	14.3	12.8
	60	19.7	17.0	14.3	12.8
18	5	12.3	13.4	12.8	12.2
	14	14.6	15.5	14.9	14.3
	23	16.7	17.7	17.1	15.8
	32	19.0	19.8	17.7	15.8
	37	20.3	21.0	17.7	15.8
	43	21.6	21.0	17.7	15.8
	47	22.6	21.0	17.7	15.8
	50	23.5	21.0	17.7	15.8
	55	24.4	21.0	17.7	15.8
	60	24.4	21.0	17.7	15.8
65	24.4	21.0	17.7	15.8	

Model	Outdoor air temp.	Indoor air temp.			
		59 °DB	70 °DB	77 °DB	81 °DB
kbtu/h	degF D.B	TC	TC	TC	TC
24	5	15.8	17.3	16.4	15.7
	14	18.7	20.0	19.2	18.4
	23	21.5	22.7	22.0	20.4
	32	24.4	25.4	22.8	20.4
	37	26.1	27.0	22.8	20.4
	43	27.8	27.0	22.8	20.4
	47	29.0	27.0	22.8	20.4
	50	30.2	27.0	22.8	20.4
	55	31.3	27.0	22.8	20.4
	60	31.3	27.0	22.8	20.4
30	5	19.9	21.8	20.7	19.8
	14	23.6	25.2	24.2	23.1
	23	27.1	28.6	27.7	25.7
	32	30.8	32.0	28.7	25.7
	37	32.8	34.0	28.7	25.7
	43	35.0	34.0	28.7	25.7
	47	36.5	34.0	28.7	25.7
	50	38.0	34.0	28.7	25.7
	55	39.4	34.0	28.7	25.7
	60	39.4	34.0	28.7	25.7
36	5	23.4	25.6	24.4	23.3
	14	27.7	29.6	28.5	27.2
	23	31.9	33.7	32.5	30.2
	32	36.2	37.6	33.8	30.2
	37	38.6	40.0	33.8	30.2
	43	41.2	40.0	33.8	30.2
	47	43.0	40.0	33.8	30.2
	50	44.7	40.0	33.8	30.2
	55	46.4	40.0	33.8	30.2
	60	46.4	40.0	33.8	30.2
48	5	31.6	34.5	32.9	31.4
	14	37.4	40.0	38.4	36.8
	23	43.0	45.5	43.9	40.7
	32	48.9	50.8	45.6	40.7
	37	52.2	54.0	45.6	40.7
	43	55.7	54.0	45.6	40.7
	47	58.0	54.0	45.6	40.7
	50	60.3	54.0	45.6	40.7
	55	62.6	54.0	45.6	40.7
	60	62.6	54.0	45.6	40.7
65	62.6	54.0	45.6	40.7	

TC : Total Cooling

