

# Submittal Data Information

## -4 Heat Motor Zone Valves

Effective: March 29, 2023

Supersedes: NEW

Job: \_\_\_\_\_ Engineer: \_\_\_\_\_ Contractor: \_\_\_\_\_ Rep: \_\_\_\_\_

ITEM	QUANTITY	MODEL NUMBER	SIZE
------	----------	--------------	------

Models	Connection	Style	Dimensions & Weights									
			A		B		C		D		Ship Wt.	
			in.	mm	in.	mm	in.	mm	in.	mm	Lbs.	Kg.
571	3/4" Sweat	2-Way	3-3/8"	86	4-13/16"	122	15/16"	24	2-1/4"	57	2-1/4	1.0
572	1" Sweat	2-Way	3-5/8"	92	4-13/16"	122	15/16"	24	2-1/4"	57	2-1/4	1.0

Models	Electrical			Performance							Materials of Construction		
	Volts	Hz	Amps	Normal Flow Ranges (GPM)	Cv	Equiv. Ft. of Pipe	Min. Fluid Temp. (°F)	Max. Fluid Temp. (°F)	Max. Working Pressure (psi)	Pump Head Ft. of Water	Body	Stem / Seal	Seat Assy.
571	24	60	0.9	4 1/2 - 6	6.1	20	40°	240°	125	65	Brass	Bellows	Brass
572	24	60	0.9	6 - 10	7.0	60	40°	240°	125	65	Brass	Bellows	Brass

