


## Class 125 (Standard)

# FIG. 3358

## Straight Tee



For Listings/Approval Details and Limitations, visit our website at [www.anvilintl.com](http://www.anvilintl.com) or contact an Anvil® Sales Representative.

FIGURE 3358 - STRAIGHT TEE			
Nominal Size	Maximum Working Pressure <sup>▲</sup>	Dimension A	Approx. Wt. Each
<i>In. (mm)</i>	<i>PSI (kPa)</i>	<i>In. (mm)</i>	<i>Lbs. (kg)</i>
1	300	1.50	1.21
25	2065	38.10	0.55
1¼	300	1.75	1.87
32	2065	44.45	0.85
1½	300	1.94	2.51
40	2065	49.27	1.14
2	300	2.25	3.96
50	2065	57.15	1.80
2½	300	2.70	6.45
65	2065	68.58	2.93

▲ – Working Pressure Ratings are for reference only and based on Sch. 40 pipe. For the latest UL/ULC, and FM pressure ratings versus pipe schedule, please visit [anvilintl.com](http://anvilintl.com) or contact your local Anvil Representative.

### MATERIAL SPECIFICATIONS

Dimensions: ASME B16.4 Class 125  
 Material: ASTM A126  
 Finish: Black or Hot Dip Galvanized per ASTM A153 Class A  
 Threads: NPT per ASME B1.20.1  
 Agency Approvals: All cast iron threaded fittings are UL/ULC Listed and FM Approved.

PROJECT INFORMATION		APPROVAL STAMP	
Project:		<input type="checkbox"/> Approved	
Address:		<input type="checkbox"/> Approved as noted	
Contractor:		<input type="checkbox"/> Not approved	
Engineer:		Remarks:	
Submittal Date:			
Notes 1:			
Notes 2:			