



**WACKER  
NEUSON**  
*all it takes!*

# Pumps

Trash, Diaphragm, Dewatering



## The right pump for the job

Trash pumps are ideal for fast removal of water with some solid content. Diaphragm pumps are excellent for moving water with mud and slurries. For smaller and clear water removal jobs, the dewatering pumps are both simple and efficient.



## Reliable water removal

Remove water from flooded basements, construction sites and excavations; drain ponds or transport fresh water with reliable engine driven Wacker Neuson pumps.

## Trash Pumps

- Versatile PT series of self-priming centrifugal trash pumps available in 2", 3", 4" and 6" models are ideal for commercial and construction dewatering needs



## Diaphragm Pumps

- Designed to move almost anything that flows, the 2" and 3" PDT diaphragm pumps are built with high quality components to provide years of top performance and durability

## Dewatering Pumps

- Remove clean water fast and economically with the compact 2" and 3" PG self-priming dewatering pumps

## Performance Data

	Unit	PT2A	PT3A	PTS4V	PT6V
<b>Suction &amp; discharge diameter</b>	in	2	3	4	6
<b>Length x width x height</b>	in	21.7 x 18.3 x 19.7	26.5 x 20 x 22.5	45.3 x 29.5 x 70.9	84.8 x 58.7 x 67.5
<b>Operating weight</b>	lbs	94.8	147.7	330.7	1,918
<b>Max. head</b>	ft	105	96.8	105	88.6
<b>Max. discharge</b>	gpm	140.3	326	689.2	1,137
<b>Max. suction lift</b>	ft	24.6	24.6	29.2	26
<b>Solid size capacity</b>	in	1	1.5	2	2
<b>Engine</b>		Honda, air-cooled, 4-cycle, single-cylinder, gasoline engine.			Vanguard, air-cooled, 4-cycle, 2 cylinder, gasoline engine.
<b>Displacement</b>	in³	9.9	16.5	29.2	77.3
<b>Max. rated power at rated speed</b>	hp rpm	4.8 @ 3,600	7.9 @ 3,825	16 @ 3,600	24.7 @ 2,700
<b>Fuel capacity</b>	gal	0.82	1.4	4.6	23.8
<b>Max. fuel consumption</b>	gal/hr	0.5	0.6	1.4	1.3

	Unit	PDT2A	PDT3A	PG2A	PG3A
<b>Suction &amp; discharge diameter</b>	in	2	3	2	3
<b>Length x width x height</b>	in	39.2 x 22.2 x 23.2	42 x 26.5 x 23.2	18.9 x 14.8 x 15.5	20.2 x 15.9 x 18.2
<b>Operating weight</b>	lbs	131	140	55	64
<b>Max. head</b>	ft	25	25	88	88
<b>Max. discharge</b>	gpm	50	88	169	290
<b>Max. suction lift</b>	ft	25	25	25	25
<b>Solid size capacity</b>	in	1.5	1.625	0.25	0.25
<b>Engine type</b>		Honda, air-cooled, 4-cycle, single-cylinder, gasoline engine.			Honda, air-cooled, 4-cycle, single-cylinder, gasoline engine.
<b>Displacement</b>	in³	7.2	7.2	7.2	9.9
<b>Operating speed</b>	rpm	2,800	2,800	3,600	3,600
<b>Max. rated power at rated speed</b>	hp rpm	3.5 @ 3,600	3.5 @ 3,600	3.5 @ 3,600	4.8 @ 3,600
<b>Fuel consumption</b>	qt/hr	1.2	1.2	1.4	1.9
<b>Fuel capacity</b>	qt	2.6	2.6	2.6	3.8



[www.wackerneuson.com](http://www.wackerneuson.com)

©Wacker Neuson 2025. Right to make technical amendments reserved.



Facebook



Instagram



YouTube



LinkedIn

0986269  
2 / 2025