



Project/Job Name:

Location:

Fixture Type:

Notes:

**67-122** - Combination Red Exit Sign/Emergency Light, 90min Ni-Cad backup, 120/277V, Dual Head, Single/Dual Face, Universal Mounting, Remote Compatible

- Has Emergency Battery



## ELECTRICAL

|                            |                             |
|----------------------------|-----------------------------|
| Technology:                | LED                         |
| Watts:                     | 3.5W                        |
| Volts:                     | 120V/277V                   |
| Lumens:                    | 150L                        |
| Lamp Base :                | Integrated                  |
| Lamp Shape :               | Integrated LED              |
| CRI:                       | 70                          |
| CCT (Kelvins):             | 5700K                       |
| Dimmable:                  | Non-Dimmable                |
| Incandescent Equivalent :  | 10W                         |
| Operating Temperature :    | +10C (+50F) to +40C (+104F) |
| Lamp Included :            | Integrated                  |
| Number of Lamps :          | 2                           |
| Replaceable Light Source : | No                          |
| Voltage Type:              | Dual Voltage                |
| Warranty:                  | 2 Year Limited              |

## PACKAGING

|                  |                       |
|------------------|-----------------------|
| Each UPC:        | 045923675768          |
| Each Quantity:   | 1                     |
| Each Dimensions: | 15.98 x 7.56 x 3.43   |
| Case UPC:        | 10045923675765        |
| Case Quantity:   | 6                     |
| Case Dimensions: | 19.69 x 17.32 x 15.16 |

## INFO

|                     |                                                                                                                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional Info:    | Input Wattage: 3.5W; Output Wattage: 1.5W; Energy Used in Maintenance Mode: 3.3W                                                                                                                 |
| Specification Note: | UL94V-0, Thermoplastic, 3.6V AA900mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C, Remote Compatible; Letter Height: 6 in.; Letter Stroke: 0.75 in.; Path of Egress: 6 Ft. |
| Includes:           | Mounting hardware and accessories                                                                                                                                                                |

## PHYSICAL

|                |                    |
|----------------|--------------------|
| Finish:        | White              |
| Lens Finish:   | Clear              |
| Lens Material: | Polycarbonate (PC) |
| Finish Family: | White              |
| Dimensions:    | W:19.00" H:7.25"   |
| Height Max:    | 120                |
| Weight (Lbs.): | 2.99               |
| Material:      | Thermoplastic      |

## COMPLIANCE

|                        |                   |
|------------------------|-------------------|
| Safety Listing:        | cULus - Certified |
| Location Rating:       | Damp              |
| Indoor/Outdoor:        | Indoor            |
| Energy Star Qualified: | No                |
| CA Prop 65:            | Lead              |
| BAA Compliant:         | No                |
| FCC Compliant:         | Yes               |
| RoHS Compliant:        | Yes               |
| Restrictions:          | No Restrictions   |