



Project/Job Name:

Location:

Fixture Type:

Notes:

S18800 - LED Retrofit Downlight; 5/6/7.5 Wattage Selectable; CCT and Lumens Selectable; 120 Volt; ColorQuick and PowerQuick Technology; Round; White Finish

- Wattage Selectable
- CCT Selectable
- Has Driver



ELECTRICAL

Technology:	LED
Watts:	5W/6W/7.5W
Volts:	120V
Lumens:	500L/600L/700L
CRI:	90
CCT (Kelvins):	2700K/3000K/3500K/4000K/5000K
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Triac
Incandescent Equivalent :	60W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Replaceable Light Source :	No
Number of LEDs :	24
Connection:	Connector or Adapter
Power Factor :	0.9
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923188008
Each Quantity:	1
Each Dimensions:	5.51 x 3.07 x 5.51
Case UPC:	10045923188005
Case Quantity:	16
Case Dimensions:	13.19 x 11.81 x 11.81

INFO

Includes:	E26 Adapter included (S9001)
-----------	------------------------------

PHYSICAL

Finish:	White
Lens Finish:	Frost
Lens Material:	Polycarbonate (PC)
Finish Family:	White
Dimensions:	H:2.90" DIA:5.31"
Weight (Lbs.):	0.47
Material:	SPCC Steel

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2623030
Energy Star Lamp Category:	Downlight Solid State Retrofit
UL/ETL Standard:	ANSI/UL 1598C; ANSI/UL 1993; CSA-C22.2 No. 250.1; CSA-C22.2 No. 1993
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions



S18800 - LED Retrofit Downlight; 5/6/7.5 Wattage Selectable; CCT and Lumens Selectable; 120 Volt; ColorQuick and PowerQuick Technology; Round; White Finish

ACCESSORIES



80-980 4 Inch Recessed Can; For New Construction



80-981 4 Inch Recessed Can; For Remodeling



S8999 GU24 Socket Adapter For Recessed Down Light



S9000 GU10 Socket Adapter For Recessed Down Light



S9538 4" Recessed Can; For New Construction



S9539 4" Recessed Can; For Remodeling



S18800 - LED Retrofit Downlight; 5/6/7.5 Wattage Selectable; CCT and Lumens Selectable; 120 Volt; ColorQuick and PowerQuick Technology; Round; White Finish

DIMMER COMPATIBILITY

Leviton	6672
Leviton	6674
Leviton	66DF-10W
Leviton	66ELV
Leviton	66EV-10W
Satco	80/2699
Satco	80/2700
Satco	80/2701
Satco	80/2702
Satco	80/2703
Satco	80/2704
Satco	86/103
Legrand	ADTP703TU
Lutron	AYCL-153P
Lutron	AYCL-253P
Lutron	CTCL-153P
Lutron	CTRP-253P
Eaton	DALo6P-C2
Leviton	DDL06
Leviton	DDMX1
Leviton	DG6HD
Leviton	DH6HD
Leviton	DL6HD
Leviton	DSEo6-10Z
Leviton	DSL06
Leviton	DSL06-1LZ

Leviton	DSM10
Eaton	DULo6P-C2
Lutron	DVCL-153P
Lutron	DVCL-253P
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	DZ6HD
Lutron	HQRA-PRO
Lutron	HQRD-10D
Lutron	HQRD-10NBD
Lutron	HQRD-6ND
Lutron	HQRD-HN6BRL
Lutron	HQRD-PRO
Lutron	HRST-PRO-N
Leviton	IPEo4-1L
Leviton	IPLo6
Lutron	LECL-153P
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MACL-LFQ
Lutron	MRF2S-6ELV
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Hubbell	NXFRD-UNV
Lutron	PD-10NXD
Lutron	PD-5NE
Lutron	PD-6WCL

Lutron	RCL-153PNL
Eaton	RF9640-ND
Legrand	RH703PTUTC
Legrand	RHCL450PTC
Leviton	RNL06-10Z
Lutron	RRD-10D
Lutron	RRD-6CL
Lutron	RRD-6ND
Lutron	RRD-H6BRL
Lutron	RRD-PRO
Lutron	RRST-PRO-N
Satco	S11268
Eaton	SAL06P
Lutron	SCL-153P
Lutron	ST-PRO-N
Lutron	STCL-153M
Eaton	SUF7
Eaton	TAL06P-C2
Lutron	TGCL-153PH
Leviton	TSL06
Leviton	TSM10
Lutron	TTCL-100H
Eaton	VSUL06D
Acuity	WSX-PDT-WH
Legrand	WWRL50WH