SMMSu / SHRMu VRF Indoor Unit MMU-UP0241HP-UL—4-Way-Cassette



Submittal Data

Job Name ₋	 Location	
Tag		



INDOOR UNIT MODEL	MMU-UP0241HP-UL	
PERFORMANCE		
Cooling Rated Capacity	Btu/h	24,000
Heating Rated Capacity	Btu/h	27,000
Fan Type (Qty)		Turbo (1)
Airflow (H / M / L)	CFM	670 / 540 / 490
Sound Pressure (H / M / L)	dBA	38 / 33 / 31
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (Input)	kW	0.036
Full Load Amps (FLA)	Α	0.87
Minimum Circuit Amps (MCA)	Α	1.09
Maximum Overcurrent	Α	15.0
Protection (MOCP)		10.0
MOTOR		
Motor Type	DC	
Motor Watts	W	60

ACCESSORIES (Optional)

- ☐ Wired Remote Controller (7-Day Programmable) RBC-AMS54E-UL / RBC-AWSU52-UL
- ☐ Simple Wired Remote Control RBC-AS41UL
- ☐ Wireless Receiver Kit RBC-AXU33UP-UL
- ☐ Wireless Controller Kit RBC-AXU31UP-UL
- ☐ Remote Sensor TCB-TC41U-UL

SMMSu /	SHRMu	VRF	4-Way	Cassette	Features
---------	-------	-----	-------	----------	----------

- R-410A refrigerant
- Eleven sizes from 7,500 to 54,000 Btu/h
- · Optional fresh air intake
- · Quiet operation (as low as 29 dBA)
- · Standard condensate pump with 26 in. lift capacity
- · Independent louver control (fixed or swing)
- · Optional wired or wireless controls
- · Auto or manually set three fan speeds
- Easy to remove cleanable filter
- Five-year parts limited warranty

PHYSICAL DATA			
Pipe Connection Size - Liquid	in.	3/8 (Flare)	
(High Pressure)			
Pipe Connection Size - Gas (Low	in.	5/8 (Flare)	
Pressure)			
Pipe Connection Size - Drain (OD)	in.	1-1/4	
Pipe Connection Size - Drain (ID)	in.	1	
Refrigerant		R-410A	
External Finish		Zinc Hot Dipped	
External i illisti		Steel Plate	
Unit Width	in.	33-1/8	
Unit Height	in.	10-1/8	
Unit Depth	in.	33-1/8	
Unit Net Weight	lb	51	
Panel Width	in.	37-3/8	
Panel Height	in.	1-3/16	
Panel Depth	in.	37-3/8	
Panel Net Weight	lb	10	
FILTER (Included)		•	
Туре	Washable		
Quantity	1		
MERV rating	5		
Dimensions	in.	21-3/8 x 21-7/8 x 3/4	

ш	Gille Fallel RDG-032FGF-0L
	Spacer for Height Adjustment TCB-SP1602UUL
	Air Discharge Direction Kit TCB-BC1602UUL
	Fresh Air Chamber TCB-GFC1602UUL
	Fresh Air Inlet Box TCB-GB1602UUL
	Auxiliary Fresh Air Flange TCB-FF101URUL
	Occupancy Sensor TCB-SIR33UP-UL

Crilla Danal DDC LISSDCD LII

© 2023 Carrier. All rights reserved.

Edition Date: 01/23


Form No: MMU-UP0241HP-UL_01

A Carrier Company

Printed in U.S.A.

Replaces: New

DIMENSIONAL DRAWING INDOOR UNIT 4-WAY CASSETTE MMU-UP0241HP-UL



A210767

