

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

875-247C ¹	2X1/2	10	0	090	326.61
875-248C ¹	2X3/4	10	0	090	326.61
875-249C ¹	2X1	10	0	090	326.61
875-250C ¹	2X1-1/4	10	0	090	326.61
875-251C ¹	2X1-1/2	10	0	090	326.61
875-335C ¹	3X1	5	0	090	1343.49
875-336C ¹	3X1-1/4	5	0	090	1343.49
875-337C ¹	3X1-1/2	5	0	090	1343.49
875-338C ¹	3X2	4	0	090	1343.49
875-339C ¹	3X2-1/2	5	0	090	1343.49
875-420C	4X2	4	0	090	1358.54
875-421C ¹	4X2-1/2	4	0	090	1429.52
875-422C	4X3	4	0	090	1358.54
875-528C ¹	6X2	5	0	090	1720.75
875-528CF ²	6X2	1	3	097	1350.03
875-530C ¹	6X3	5	0	090	1720.39
875-530CF ²	6X3	1	2	097	1501.03
875-532C	6X4	5	0	090	1313.65
875-578C ¹	8X2	2	0	090	4550.35
875-578CF ²	8X2	1	2	097	1814.84
875-579CF ²	8X2-1/2	1	2	097	1902.14
875-580C ¹	8X3	2	0	090	4550.35
875-580CF ²	8X3	1	2	097	1859.98
875-582C	8X4	2	0	090	4550.35
875-582CF ²	8X4	1	2	097	1910.23
875-585C ¹	8X6	1	0	090	4170.06
875-585CF ²	8X6	1	0	097	2653.52
875-621CF ²	10X2	1	0	097	2021.72
875-623CF ²	10X3	1	0	097	2152.31
875-624CF ²	10X4	1	0	097	2630.25
875-626C	10X6	1	0	091	4700.81
875-626CF ²	10X6	1	0	097	2986.46
875-628C	10X8	1	0	091	4949.47
875-628CF ²	10X8	1	0	097	3516.85
875-661CF ²	12X2	1	0	097	3335.68
875-663CF ²	12X3	1	0	097	3504.41
875-664CF ²	12X4	1	0	097	3997.52
875-666CF ²	12X6	1	0	097	4158.51
875-668CF ²	12X8	1	0	097	4389.29
875-670CF ²	12X10	1	0	097	5404.07
875-694CF ²	14X4	1	0	097	8947.58
875-696CF ²	14X6	1	0	097	9827.68
875-698CF ²	14X8	1	0	097	10631.06
875-700CF ²	14X10	1	0	097	12390.42
875-702CF ²	14X12	1	0	097	12951.09
875-754CF ²	16X4	1	0	097	11258.71
875-756CF ²	16X6	1	0	097	11854.86
875-758CF ²	16X8	1	0	097	13765.24
875-760CF ²	16X10	1	0	097	15470.20
875-762CF ²	16X12	1	0	097	16778.19
875-764CF ²	16X14	1	0	097	19932.60

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

875-784CF ²	18X4	1	0	097	11638.04
875-786CF ²	18X6	1	0	097	12791.33
875-788CF ²	18X8	1	0	097	14754.86
875-790CF ²	18X10	1	0	097	16290.59
875-792CF ²	18X12	1	0	097	18540.47
875-794CF ²	18X14	1	0	097	20338.09
875-796CF ²	18X16	1	0	097	21533.36

¹ Sized with Bushing
² Fiberglass reinforced



Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum internal Pressure Rating @ 73°F (23°C)

876-020CF ²	2	1	4	097	977.02
876-030CF ²	3	1	4	097	1246.17
876-040CF ²	4	1	2	097	2136.69
876-060CF ²	6	1	0	097	3725.34
876-080CF ²	8	1	0	097	6681.22
876-100CF ²	10	1	0	097	7250.59
876-120CF ²	12	1	0	097	10863.19

² Fiberglass reinforced
For larger sizes please contact your Regional Spears® Distribution Center.



Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-338C	3X2	5	0	090	1447.26
876-420CF ²	4X2	1	2	097	1820.63
876-421CF ²	4X2-1/2	1	2	097	1926.71
876-422CF ²	4X3	1	2	097	2074.38
876-528CF ²	6X2	1	3	097	3096.42
876-529CF ²	6X2-1/2	1	2	097	3134.96
876-530CF ²	6X3	1	2	097	3185.99
876-532CF ²	6X4	1	0	097	3538.09
876-578CF ²	8X2	1	2	097	5291.59
876-579CF ²	8X2-1/2	1	2	097	5369.77
876-580CF ²	8X3	1	0	097	5412.29
876-582CF ²	8X4	1	0	097	5826.73
876-585CF ²	8X6	1	0	097	6142.65
876-621CF ²	10X2	1	0	097	6379.81
876-622CF ²	10X2-1/2	1	0	097	6512.87
876-623CF ²	10X3	1	0	097	6628.46
876-624CF ²	10X4	1	0	097	6781.71
876-626CF ²	10X6	1	0	097	7261.28
876-628CF ²	10X8	1	0	097	7626.71
876-661CF ²	12X2	1	0	097	6868.69
876-662CF ²	12X2-1/2	1	0	097	7197.99
876-663CF ²	12X3	1	0	097	7324.99



Schedule 80 CPVC Product
CPVC Schedule 80 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing (continued)

Socket x Socket x Socket x Socket

876-664CF ²	12X4	1	0	097	7593.22
876-666CF ²	12X6	1	0	097	8311.15
876-668CF ²	12X8	1	0	097	9429.39
876-670CF ²	12X10	1	0	097	10267.17

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union 2000 - Socket/FKM

Socket x Socket with FKM O-ring Seal

1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-002C	1/4	25	150	090	85.09
857-003C	3/8	25	150	090	85.09
8057-005C	1/2	20	120	090	56.62
8057-007C	3/4	20	80	090	59.15
8057-010C	1	15	90	090	71.01
8057-012C	1-1/4	10	0	090	143.62
8057-015C	1-1/2	10	0	090	146.23
8057-020C	2	5	0	090	242.43
8057-025C	2-1/2	5	0	090	397.56
8057-030C	3	5	0	090	503.15
8057-040C	4	4	0	090	642.81
8057-060C	6	1	0	090	1428.51

Union 2000 - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-002C	1/4	25	150	090	84.07
897-003C	3/8	25	150	090	84.07
8097-005C	1/2	20	120	090	56.43
8097-007C	3/4	20	80	090	58.45
8097-010C	1	15	90	090	70.01
8097-012C	1-1/4	10	0	090	141.78
8097-015C	1-1/2	10	0	090	144.45
8097-020C	2	5	0	090	239.44
8097-025C	2-1/2	5	0	090	396.52
8097-030C	3	5	0	090	496.97
8097-040C	4	4	0	090	635.54
8097-060C	6	1	0	090	1412.27

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/Fipt/FKM

Socket x Fipt with FKM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005C	1/2	20	120	090	64.43
8059-007C	3/4	20	80	090	112.44
8059-010C	1	15	90	090	155.24
8059-012C	1-1/4	10	0	090	263.43
8059-015C	1-1/2	10	0	090	295.67
8059-020C	2	5	0	090	334.27
8059-025C	2-1/2	5	0	090	542.64
8059-030C	3	5	0	090	641.83
8059-040C	4	4	0	090	742.17
8059-060C	6	1	0	090	1429.73

Union 2000 - Socket/Fipt/EPDM

Socket x Fipt with EPDM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005C	1/2	20	120	090	62.84
8099-007C	3/4	20	80	090	111.14
8099-010C	1	15	90	090	153.28
8099-012C	1-1/4	10	0	090	292.01
8099-015C	1-1/2	10	0	090	292.01
8099-020C	2	5	0	090	330.09
8099-025C	2-1/2	5	0	090	472.88
8099-030C	3	5	0	090	633.94
8099-040C	4	4	0	090	731.28
8099-060C	6	1	0	090	1365.07

Union 2000 - Socket/Spigot/FKM

Socket x Spigot with FKM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8056-005C	1/2	20	160	090	56.62
8056-007C	3/4	20	160	090	59.15
8056-010C	1	15	90	090	71.01
8056-012C	1-1/4	10	0	090	143.62
8056-015C	1-1/2	10	0	090	146.23
8056-020C	2	5	0	090	242.43
8056-025C	2-1/2	5	0	090	442.94
8056-030C	3	5	0	090	503.15
8056-040C	4	4	0	090	642.81
8056-060C	6	1	0	090	1428.51

Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/Spigot/EPDM

Socket x Spigot with EPDM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8096-005C	1/2	20	160	090	56.43
8096-007C	3/4	20	80	090	58.45
8096-010C	1	15	90	090	70.01
8096-012C	1-1/4	10	0	090	141.78
8096-015C	1-1/2	10	0	090	144.45
8096-020C	2	5	0	090	239.44
8096-025C	2-1/2	5	0	090	396.52
8096-030C	3	5	0	090	496.97
8096-040C	4	4	0	090	635.54
8096-060C	6	1	0	090	1412.27



Union 2000 - Fipt/Mipt/FKM

Fipt x Mipt with FKM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8053-005C	1/2	20	120	090	56.62
8053-007C	3/4	20	0	090	59.15
8053-010C	1	15	90	090	71.01
8053-012C	1-1/4	10	0	090	143.62
8053-015C	1-1/2	10	0	090	146.23
8053-020C	2	5	0	090	242.43
8053-030C	3	5	0	090	503.15



Union 2000 - Fipt/Mipt/EPDM

Fipt x Mipt with EPDM O-ring Seal

8093-005C	1/2	20	120	090	56.43
8093-007C	3/4	20	0	090	58.45
8093-010C	1	15	90	090	70.01
8093-012C	1-1/4	10	0	090	141.78
8093-015C	1-1/2	10	0	090	144.45
8093-020C	2	5	0	090	239.44
8093-030C	3	5	0	090	496.97



Union 2000 - Fipt/Mipt/FKM- Reducing

Fipt x Mipt with FKM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8053-168C	1-1/4X1	10	0	090	160.94
-----------	---------	----	---	-----	--------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Fipt/Mipt/EPDM-Reducing

Fipt x Mipt with EPDM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8093-168C	1-1/4X1	10	0	090	158.42
-----------	---------	----	---	-----	--------



Union 2000 - Socket/Mipt/FKM

Socket x Mipt with FKM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8054-005C	1/2	20	120	090	56.62
8054-007C	3/4	20	0	090	59.15
8054-010C	1	15	90	090	71.01
8054-012C	1-1/4	10	0	090	143.62
8054-015C	1-1/2	10	0	090	146.23
8054-020C	2	5	0	090	242.43
8054-030C	3	5	0	090	503.15



Union 2000 - Socket/Mipt/EPDM

Socket x Mipt with EPDM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8094-005C	1/2	20	120	090	56.43
8094-007C	3/4	20	80	090	58.45
8094-010C	1	15	90	090	70.01
8094-012C	1-1/4	10	0	090	141.78
8094-015C	1-1/2	10	0	090	144.45
8094-020C	2	5	0	090	239.44
8094-030C	3	5	0	090	496.97



Union 2000 - Socket/Mipt/FKM-Reducing

Socket x Mipt with FKM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8054-168C	1-1/4X1	10	0	090	160.94
-----------	---------	----	---	-----	--------



Union 2000 - Socket/Mipt/EPDM -Reducing

Socket x Mipt with EPDM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8094-168C	1-1/4X1	10	0	090	158.42
-----------	---------	----	---	-----	--------





Schedule 80 CPVC Product
CPVC Schedule 80 Fittings

Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Special Reinforced Fipt/Spigot/FKM

SR Fipt x Spigot with FKM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8055-005CSR	1/2	20	160	096	74.52
8055-007CSR	3/4	20	160	096	78.41
8055-010CSR	1	15	90	096	99.96
8055-012CSR	1-1/4	10	0	096	160.63
8055-015CSR	1-1/2	10	0	096	183.89
8055-020CSR	2	5	0	096	282.52
8055-025CSR	2-1/2	5	0	096	533.23
8055-030CSR	3	5	0	096	563.47
8055-040CSR	4	4	0	096	727.86
8055-060CSR	6	1	0	096	865.87



Union 2000 - Fipt/EPDM

Fipt x Fipt with EPDM O-ring Seal

1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
898-002C	1/4	25	150	090	94.54
898-003C	3/8	25	100	090	94.54
8098-005C	1/2	20	120	090	59.87
8098-007C	3/4	20	80	090	105.86
8098-010C	1	15	90	090	145.97
8098-012C	1-1/4	10	0	090	278.33
8098-015C	1-1/2	10	0	090	278.33
8098-020C	2	5	0	090	314.40
8098-025C	2-1/2	5	0	090	442.94
8098-030C	3	5	0	090	881.25
8098-040C	4	4	0	090	1025.97
8098-060C	6	1	0	090	1436.06



Union 2000 - Special Reinforced Fipt/Spigot/EPDM

SR Fipt x Spigot with EPDM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8095-005CSR	1/2	20	120	096	73.83
8095-007CSR	3/4	20	160	096	76.36
8095-010CSR	1	15	90	096	97.93
8095-012CSR	1-1/4	10	0	096	150.43
8095-015CSR	1-1/2	10	0	096	170.85
8095-020CSR	2	5	0	096	257.82
8095-025CSR	2-1/2	5	0	096	511.71
8095-030CSR	3	5	0	096	551.65
8095-040CSR	4	4	0	096	696.11
8095-060CSR	6	1	0	096	844.61



Union 2000 - Socket/Special Reinforced Fipt/FKM

Socket x SR Fipt with FKM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005CSR	1/2	20	120	096	33.36
8059-007CSR	3/4	20	160	096	58.85
8059-010CSR	1	15	90	096	81.06
8059-012CSR	1-1/4	10	0	096	154.54
8059-015CSR	1-1/2	10	0	096	168.00
8059-020CSR	2	5	0	096	174.87
8059-025CSR	2-1/2	5	0	096	302.82
8059-030CSR	3	5	0	096	491.99
8059-040CSR	4	4	0	096	573.99
8059-060CSR	6	1	0	096	1572.60



Union 2000 - Fipt/FKM

Fipt x Fipt with FKM O-ring Seal

1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

858-002C	1/4	25	150	090	95.67
858-003C	3/8	25	150	090	95.67
8058-005C	1/2	20	120	090	60.61
8058-007C	3/4	20	80	090	107.16
8058-010C	1	15	90	090	147.78
8058-012C	1-1/4	10	0	090	281.57
8058-015C	1-1/2	10	0	090	281.57
8058-020C	2	5	0	090	318.29
8058-025C	2-1/2	5	0	090	512.75
8058-030C	3	5	0	090	972.97
8058-040C	4	4	0	090	1045.85
8058-060C	6	1	0	090	1493.60



Union 2000 - Socket/Special Reinforced Fipt/EPDM

Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005CSR	1/2	20	120	096	32.71
8099-007CSR	3/4	20	160	096	58.03
8099-010CSR	1	15	90	096	80.39
8099-012CSR	1-1/4	10	0	096	152.27
8099-015CSR	1-1/2	10	0	096	165.62
8099-020CSR	2	5	0	096	174.41
8099-025CSR	2-1/2	5	0	096	299.13
8099-030CSR	3	5	0	096	485.80
8099-040CSR	4	4	0	096	570.54
8099-060CSR	6	1	0	096	1532.95



Schedule 80 CPVC Product
CPVC Schedule 80 Fittings



Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Special Reinforced Fipt/FKM

SR Fipt x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar



1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005CSR	1/2	20	120	096	34.23
8058-007CSR	3/4	20	80	096	59.64
8058-010CSR	1	15	90	096	81.98
8058-012CSR	1-1/4	10	0	096	154.54
8058-015CSR	1-1/2	10	0	096	168.65
8058-020CSR	2	5	0	096	177.69
8058-025CSR	2-1/2	5	0	096	307.62
8058-030CSR	3	5	0	096	502.14
8058-040CSR	4	4	0	096	588.24
8058-060CSR	6	1	0	096	1579.19

Union 2000 - Special Reinforced Fipt/EPDM

SR Fipt x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar



1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8098-005CSR	1/2	20	160	096	33.07
8098-007CSR	3/4	20	80	096	59.09
8098-010CSR	1	15	90	096	81.06
8098-012CSR	1-1/4	10	0	096	153.03
8098-015CSR	1-1/2	10	0	096	167.33
8098-020CSR	2	5	0	096	175.93
8098-025CSR	2-1/2	5	0	096	304.07
8098-030CSR	3	5	0	096	494.35
8098-040CSR	4	4	0	096	572.33
8098-060CSR	6	1	0	096	1552.15

Union (Old Style) - Socket/FKM

Socket x Socket with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-005C	1/2	15	90	090	56.62
857-007C	3/4	10	60	090	59.15
857-010C	1	10	40	090	71.01
857-012C	1-1/4	5	20	090	143.62
857-015C	1-1/2	5	0	090	146.23
857-020C	2	5	0	090	242.43
857-025C	2-1/2	5	0	090	397.56
857-030C	3	5	0	090	503.15
857-040C	4	4	0	090	642.81

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union (Old Style) - Socket/EPDM

Socket x Socket with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-005C	1/2	15	90	090	56.43
897-007C	3/4	10	60	090	58.45
897-010C	1	10	40	090	70.01
897-012C	1-1/4	5	20	090	141.78
897-015C	1-1/2	5	0	090	144.45
897-020C	2	5	0	090	239.44
897-025C	2-1/2	5	0	090	396.52
897-030C	3	5	0	090	496.97
897-040C	4	4	0	090	635.54

Union (Old Style) - Socket/Fipt/FKM

Socket x Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005C	1/2	15	90	090	64.43
859-007C	3/4	10	40	090	112.44
859-010C	1	10	40	090	155.24
859-012C	1-1/4	5	20	090	263.43
859-015C	1-1/2	5	0	090	295.67
859-020C	2	5	0	090	334.27
859-025C	2-1/2	5	0	090	542.64
859-030C	3	5	0	090	641.83
859-040C	4	4	0	090	742.17

Union (Old Style) - Socket/Fipt/EPDM

Socket x Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-005C	1/2	15	90	090	62.84
899-007C	3/4	10	60	090	111.14
899-010C	1	10	40	090	153.28
899-012C	1-1/4	5	20	090	292.01
899-015C	1-1/2	5	0	090	292.01
899-020C	2	5	0	090	330.09
899-025C	2-1/2	5	0	090	472.88
899-030C	3	5	0	090	633.94
899-040C	4	4	0	090	731.28

Union - Socket/Brass Fipt/FKM

Socket x Fipt with Brass Thread Insert & FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005CBR	1/2	10	60	096	211.80
859-007CBR	3/4	10	20	096	302.21
859-010CBR	1	10	0	096	336.61
859-012CBR	1-1/4	5	0	096	564.27