



## General Product Specification

<b>Item No.</b>	GSMFL100-7
-----------------	------------

<b>Date</b>	5/3/2022
-------------	----------

<b>No. Pages</b>	1
------------------	---

### Product Description:

<b>Style</b>	Pads
<b>Item Size (each)</b>	15" x 18"
<b>Color</b>	Gray
<b>Composition</b>	100% Polypropylene
<b>Structure</b>	3-ply composition, spunbond/fine fiber outer layers on a straight meltblown
<b>Technology</b>	Meltblown
<b>Absorbency</b>	Universal (Hydrophilic)
<b>Bonding</b>	Thermal bonded

<b>Intended Application</b>	Universal (Hydrophilic) absorbent
-----------------------------	-----------------------------------

<b>Absorbency Capacity</b>	20.6 gallons per bale
----------------------------	-----------------------

### Packaging Description:

<b>Packages Per Pallet</b>	36
<b>Items Per Package</b>	100 Pads/bale
<b>Pallet Weight</b>	359 lbs

<b>Package Weight</b>	7.0 lbs
<b>Package Dimensions</b>	16" x 19" x 16"
<b>Pallet Dimensions</b>	48" x 40" x 85"

### Physical Properties:

<b>Parameter</b>	<b>MBT Test Method</b>	<b>Units</b>	<b>Nominal</b>	<b>(+/-) Tolerance</b>
Basis Weight	MBTTM001	LBS	7.0	10%
Absorbency** (med Oil)	MBTTM012	GAL	20.6	10%
3" Tensile Strength	MBTTM02	LBS	17	10%
Color	N/A			

The above properties are "nominal" values used for process control when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or environment being applied, stored, or shipped.

\*\* The "Absorbency" spec and "MBTTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

<b>Attributes</b>	Product will be free of foreign material contamination, rips, holes and tears.
<b>Labeling</b>	
<b>Certification</b>	Make no changes in basic process or composition without notifying customer.