




SYMMONS® Dia®







3593BTRM

Location:

Shower Trim

Specification Submittal

<p>Model Numbers</p>	<p>Modifications</p>
<p><input type="checkbox"/> 3593BTRM Shower System Trim</p> <p>Valve Options: - 261 Series Temtrol Shower Valve with TRM modifier. - 161 Series Temptrol Shower Valve requires TC modifier.</p>	<p><input type="checkbox"/> 15 1.5 gpm (5.7 L/min) flow rate restrictor</p> <p><input type="checkbox"/> 175 1.75 gpm (6.6 L/min) flow rate restrictor</p> <p><input type="checkbox"/> Delete Suffix B Chrome plastic escutcheon on valve with color graphics/indicators in place of standard brass escutcheon</p> <p><input type="checkbox"/> L2 Less hand shower (wand only)</p> <p><input type="checkbox"/> L7 Less handle</p> <p><input type="checkbox"/> TC Test Cap Trim (includes TA-10&T-12A) used with 161 Series Temptrol Valve</p> <p><input type="checkbox"/> STN Satin Nickel finish</p> <p><input type="checkbox"/> MB Matte Black finish</p> <p><input type="checkbox"/> BBZ Brushed Black Bronze</p> <p><input type="checkbox"/> 1L 1" Spindle Extension</p>
<p>Feature Highlights</p> <ul style="list-style-type: none"> • Dia Hand Shower Trim. • Requires Temptrol pressure balancing shower valve. • Features adjustable stop screw to limit handle turn. • 30" slide bar. • 60" flexible metal hose. • 7 mode hand shower with NPSO. • Standard 2.0 gpm (7.6 L/min) flow restrictors. • Components made from metal and nonmetallic materials plated in standard polished chrome finish. 	<p>Warranty</p> <p>Limited Lifetime - to the original end purchaser in consumer/residential installations.</p> <p>10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.</p> 
<p>Compliance</p> <p>-ASME A112.18.1/CSA B125.1 -WaterSense 1.5 gpm (5.7 L/min) 1.75 gpm (6.6 L/min) 2.0 gpm (7.6 L/min) -Lever handle meets ADA requirements for operation</p>   	

SKU Builder

Series	Finish	Modifier	Flow Rate	TRM (required)	TC	1L	Final SKU
3593B	STN		15	TRM			3593BSTN15TRM
3593	MB	L2		TRM	TC	1L	3593MBL2TRMTC1L

Note: No more than two modifiers (L1-L7) and modifier order will follow numerical order.

Architectural/Engineering Specification

Symmons Dia Hand Shower System _____ Includes Dia Shower Trim powered by the Temptrol® Pressure Balancing valve. Features include adjustable stop screw to limit handle turn, 30" slide bar, in-line vacuum breaker, 60" flexible metal hose, 7 mode hand shower and standard 2.0 gpm (7.6 L/min) flow restrictors. Components made from metal and nonmetallic materials plated in standard polished chrome finish. 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1 and WaterSense compliant. Lever handle meets ADA requirements. Available options: "15 - 1.5 gpm (5.7 L/min) flow restrictor", "175- 1.75 gpm(6.6 L/min) flow rate restrictor. Available options: "15 - 1.5 gpm (5.7 L/min) flow restrictor", "175- 1.75 gpm (6.6 L/min) flow rate restrictor "Delete Suffix B - Chrome plastic escutcheon, "TC - Test Cap Trim", "L2 - Less hand shower (wand only)", "L7 - Less handle", "STN - Satin Nickel finish", "BBZ - Brushed Bronze finish", "MB - Matte Black finish", and "1L- 1 inch Spindle Extension".

