



S3594BTRM
Tub/Hand Shower Trim
Specification Submittal

Location:

Model Numbers

- S3594BTRM**
Tub/Hand Shower Trim
- Valve options:**
-S262 series Temptrol Shower Valve with TRM modifier
-S162 series Temptrol Shower Valve requires TC modifier

Feature Highlights

- Dia Tub/Hand Shower Trim.
- Requires Temptrol® Pressure Balancing Shower Valve.
- Integral diverter control.
- Metal lever handle.
- 7" slip-on tub spout.
- 30" slide bar for hand shower.
- 60" flexible metal hose.
- 7 mode hand shower.
- Dual checks for backflow protection.
- Standard 2.0 gpm (7.6 L/min) flow restrictors.
- Components shall be metal and nonmetal construction, plated in standard polished chrome finish.

Compliance

- ASME A112.18.1/CSA B125.1
- WaterSense 1.5 gpm (5.7 L/min), 1.75gpm (6.6 L/min), 2.0 gpm (7.6 L/min)
- Lever handle meets ADA requirements for operation.



Options/ Modifications

- 15** 1.5 gpm (5.7 L/min) flow restrictor
- 175** 1.75 gpm (6.6 L/min) flow rate restrictor
- Delete Suffix B** Chrome plastic escutcheon on valve with color graphic/indicators in place of standard brass escutcheon
- L2** Less handshower
- L5** Less tub spout
- L7** Less handle
- BBZ** Brushed Bronze finish
- MB** Matte Black finish
- STN** Satin Nickel finish
- TC** Test Cap Trim (includes TA-10&T-12A) used with 161 Series Temptrol Shower Valve

Warranty

Limited Lifetime - to the original end purchaser in consumer/residential installations.
10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.



SKU Builder

Series	Finish	Modifier	Flow Rate	TRM (required)	TC	Final SKU
S3594B	STN		15	TRM		S3594BSTN15TRM
S3594	MB	L1		TRM	TC	S3594BMBL1TRMTC

Note: No more than two modifiers (L1-L7) and modifier order will follow numerical order.

Architectural/ Engineering Specification

Symmons Dia Tub and Hand Shower Trim _____ Includes Dia Tub and Hand Shower Trim powered by Temptrol® Pressure Balancing Valve. Features integral diverter control, metal lever handle, 7" slip-on tub spout, 30" slide bar for hand shower, 60" flexible metal hose, 7 mode hand shower, dual checks for backflow protection, and standard 2.0 gpm (7.6 L/min) flow restrictor. Components shall be metal and nonmetal construction, plated in standard polished chrome finish. 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1, WaterSense 1.5 gpm (5.7 L/min), 1.75 gpm (6.6 L/min), 2.0 gpm (7.6 L/min) compliant. Available options: "15 - 1.5 gpm (5.7 L/min) flow restrictor", "175 - 1.75 gpm (6.6 L/min) flow restrictor", "Delete Suffix B - Chrome plastic escutcheon", "L2 - Less hand shower", "L5 - Less hand shower system", "L6 - Less tub spout", "L7 - Less handle", "TC - Test Cap Trim", "STN - Satin Nickel finish", "MB - Matte Black finish", and "BBZ - Brushed Bronze finish".

