

Mueller Streamline Co. Headquarters

150 Schilling Blvd Suite 201

Collierville, Tennessee 38017

United States

Phone: 901 753 3200

Mueller Streamline Co. International

525 Okeechobee Blvd Suite 860 West Palm Beach, FL 33401

United States

Phone: 561 273 8300

ITEM # 61080400, STANDARD LINE SETS - NO OPTIONS

Streamline Standard and Mini-split Line Sets have been an industry leader for decades. We leverage our many years of experience and expertise producing copper tube in every line set we make. From liquid line and suction line handling to unique insulations applications and packaging, every Streamline Standard and Mini-split Line Set meets our rigorous standards for quality and consistency. With a broad offering of liquid line and suction line diameters, insulation, thicknesses, custom ends and



+ more

<u>Specifications</u> | <u>Dimensions</u> | <u>Details</u>

| Specifications - | | |
|---------------------|---|--|
| STANDARD | | |
| 15.4082 lb | | |
| 123.27 lb | | |
| C12200 | | |
| 685768286837 | | |
| Elastomeric (black) | | |
| | 15.4082 lb 123.27 lb C12200 685768286837 | |

| Liquid Line Size | 3/8" |
|-------------------------------------|---|
| Suction Line Size | 5/8" |
| Insulation Wall Thickness | 3/8" |
| 90° Bends | NO |
| Standards | ASTM B1003 For HVAC Applications Made in USA UL 700 PSI |
| Customization | Suction Line Insulation |
| Finish Option 1 - Flare Fittings | NO |
| Finish Option 2 - Cable Gage | NO |
| Finish Option 3 - Cable Strands | NO |
| | |
| Finish Option 4 - T-stat Wire Gauge | NO |

| Dimensions – | | | |
|--------------|----------------|----------|--|
| | Length | 040 ft | |
| | Overall Height | 33.5 in | |
| | Overall Length | 33.5 in | |
| | Overall Width | 5.125 in | |
| | SK Height | 34.5 in | |
| | SK Length | 34 in | |
| | SK Width | 45 in | |
| | | | |

| Det | Details - | | | |
|-----|-----------|-----|--|--|
| | EA/SK | 8 | | |
| | Style | 910 | | |

| Туре | 9010 |
|-----------------------|--------------------|
| Mueller Description 1 | STANDARD LINE SETS |
| Mueller Description 2 | 40-610-3/8 (8) |
| Mueller Description 3 | SLS - NO OPTIONS |
| | |