

# OPAL SERIES

## Surface Mounted or Retrofit

Opal LED luminaires are designed to surface mount over a junction box or retrofit with an accessory. Luminaires produce an even illumination with no diode image, from bright to dim. The low profile units are wet location rated and produce up to 2150 lumens at various color temperatures and finishes. Opal is an excellent energy efficient lighting solution for laundry rooms, closets, pantries, hallways and showers in residential and commercial retrofit or new construction applications.

### T24 FEATURES

- 700lm to 2150lm deliver lumens
- Dedicated CCT (2700K, 3000K, 4000K, 5000K)
- White, Natural Metal and Black finishes
- Certified to high efficacy requirements of California Title 24 JA8-2022

### REGRESSED FEATURES

- Regressed light source gives the appearance of a recessed luminaire
- 700lm (4") or 900lm (6")
- 2700K, 3000K or 4000K at 90+ CRI
- Certified to high efficacy requirements of California Title 24 JA8-2022

### MOTION SENSOR FEATURES

- PIR (passive infrared) motion sensor for easy on/off operation
- PIR sensor can detect motion up to 16' diameter pattern at 8' mounting height
- 1050lm / 15W
- 3000K or 4000K at 90+ CRI



AC OPAL SERIES 4", 6", 7" & 8" SURFACE MOUNT			
	SIZE / LUMENS / WATTAGE	CCT	FINISH
Title 24	<a href="#">NLOPAC-R4TW</a> / <a href="#">NLOPAC-R6TW</a>	4" / 700lm / 10W 6" / 1200lm / 16W	Selectable CCT (5 CCT in One) <b>B</b> Black (4") <b>NM</b> Natural Metal <b>W</b> White
	<a href="#">NLOPAC-R4509T24</a> <a href="#">NLOPAC2-R6509T24</a> <a href="#">NLOPAC-R8T24</a>	4" / 700lm / 10.5W 6" / 1100lm / 16.5W 8" / 2150lm / 30W	<b>27</b> 2700K <b>30</b> 3000K <b>40</b> 4000K <b>50</b> 5000K <b>B</b> Black <b>BZ</b> Bronze (4" & 8") <b>NM</b> Natural Metal (4" & 8") <b>W</b> White
	<a href="#">NLOPAC-R4REGT24</a> <a href="#">NLOPAC-R6REGT24</a>	4" / 700lm / 11W 6" / 950lm / 13W	<b>27</b> 2700K <b>30</b> 3000K <b>40</b> 4000K <b>W</b> White
	<a href="#">NLOPAC-R7MS</a>	7" / 1050lm / 15W	<b>30</b> 3000K <b>40</b> 4000K <b>W</b> White



Example: **NLOPAC-R8T2430W** - 8" AC Opal LED, 2150lm / 32W, 3000K, White finish

### OPTIONAL ACCESSORIES

[NLOPAC-4BKT-2](#) Universal bracket for mounting 4" Opal to 3" or 4" junction boxes. Universal bracket is included with R4509T24 series.



**NLOPAC-R7MS**  
7" AC Opal with PIR Motion Sensor



**NLOPAC-R4TW**  
4" AC Opal - Selectable CCT



**NLOPAC-R6REGT24**  
6" Regressed AC Opal T24 Series



**NLOPAC2-R6509T24**  
6" AC Opal T24 Series



**NLOPAC-R8T24**  
8" AC Opal T24 Series

