

# Industrial/Contractor

## 100% SILICONE SEALANT INDUSTRIAL GRADE RTV

High performance sealing and glazing compound that is ideal for use in most OEM and maintenance applications. Forms a strong, durable and weather-resistant seal and provides excellent adhesion to most non-porous surfaces. 50 year warranty. Solvent clean up. NSF listed.



- 0816/0I - 10.1 Fl. Oz. (300 mL) - White
- 0816/2I - 10.1 Fl. Oz. (300 mL) - Almond
- 0816/4I - 10.1 Fl. Oz. (300 mL) - Bronze
- 0816/5I - 10.1 Fl. Oz. (300 mL) - Gray
- 0816/6I - 10.1 Fl. Oz. (300 mL) - Black
- 0826/0I - 10.1 Fl. Oz. (300 mL) - Clear

Meets or exceeds the requirements of TT-S-00230C, TT-S-001543A, C.G.S.B. 19C9-9, Din 18540 Part 2, Mil. Spec 46106A, CEBTP 432.65 140-2, ASTM C920. USDA authorized for use in federally inspected meat and poultry plants.



## SILICONIZED ACRYLIC CAULK CONSTRUCTION GRADE - 35 YEAR

Superior sealant fortified with silicone for increased flexibility and extended life. It provides excellent adhesion to most interior and exterior surfaces. Mildew resistant, low odor and low VOC. 35 year warranty. Water clean up.

- 0846/0I - 10.1 Fl. Oz. (300 mL) - White
- 0846/2I - 10.1 Fl. Oz. (300 mL) - Almond
- 0846/4I - 10.1 Fl. Oz. (300 mL) - Brown
- 0846/5I - 10.1 Fl. Oz. (300 mL) - Gray
- 0846/6I - 10.1 Fl. Oz. (300 mL) - Black
- 0876/0I - 10.1 Fl. Oz. (300 mL) - Clear

Meets or exceeds the requirements of ASTM C834.



## NOISE PROOF™ ACOUSTIC SEALANT

Noise Proof™ Acoustic Sealant is a water-based, acrylic latex sealant that reduces sound transmission while sealing joints. It can be applied to all openings and areas where sound transmission may occur. It has a long-lasting, permanently flexible bond. Low VOC and low odor.

- 0586 - 10.1 Fl. Oz. (300 mL) - White
- 0589 - 28 Fl. Oz. (858 mL) - White

Meets or exceeds Federal Specifications ASTM-E90, ASTM-E84, ASTM-C834.



## BUTYL RUBBER SEALANT ARCHITECTURAL GRADE

A high-performance, rubber-like sealant that is ideal for tough outdoor jobs and below-grade applications. Use indoors or out, wherever a durable, flexible and watertight seal is required. Butyl rubber sealant adheres to most building surfaces and remains rubbery and flexible. Paintable. 10 year warranty.

- 0697/0I - 10.1 Fl. Oz. (300 mL) - White
- 0697/GI - 10.1 Fl. Oz. (300 mL) - Gray

Meets or exceeds the requirements of Federal Specifications TT-S-001657, TT-C-00598C, TT-C-1796A.



## R5™ WINDOW & DOOR ACRYLIC CAULK

R5™ Window & Door Siliconized Acrylic Caulk provides extra tight seals around windows, doors and other areas. This multi-purpose, paintable sealant can be used indoors or outdoors and helps increase energy efficiency by resisting thermal temperature changes and reducing drafts and cold spots. It also provides a barrier to the entry of dirt, insects and other pests.

- 0656 - 10.1 Fl. Oz. (300 mL)



## 100% SILICONE SEALANT HEAT RESISTANT RTV

Formulated with iron oxide to resist extreme heat exposure. Withstands temperatures up to 600°F and can be used on industrial ovens, heating elements, boilers, and more. 50 year warranty. Solvent clean up.

- 0809/0I - 10.1 Fl. Oz. (300 mL) - Red
- 0829/0I - 2.8 Fl. Oz. (183 mL) - Red

Meets or exceeds the requirements of TT-S-00230C, TT-S-001543A, C.G.S.B. 19C9-9, Din 18540 Part 2, Mil. Spec 46106A, CEBTP 432.65 140-2, ASTM C920. USDA authorized for use in federally inspected meat and poultry plants.

