

Fire Hydrant Repair Kits

4", 4-1/2", 4-1/4" Main Valve Opening

Hydrant Style	Bonnet Repair Kit	Safety Flange Repair Kit	Extension Kit	Shoe Repair Kit	Main Valve Repair Kit	Tamper Proof Retrofit Kit*	
						Left	Right
Super Centurion®350	-	A-300-35	A-319-35	-	-	284275	282476
Super Centurion 250 & 200	280355	A-300	A-319	280356	280358	284275	282476
Centurion®	280355	A-300	A-319	280356	280358	284275	284276
Improved	280360	A-300 (after 1972)	A-319-11 (after 1972)	280362 (4-1/4")	280365 (4-1/4")	284275	284276
		A-300-00 (prior to 1972)	A-319-00 (prior to 1972)	280363 (4-1/2")	280366 (4-1/2")		
Modern Improved	-	A-307	A-319-11	280391	280393	-	-
Mueller® 107	280368 (4")	A-300 (4")	A-319 (4")	280370 (4")	280372 (4")	-	-
Standard Post (A-413)	-	-	A-322 (4-1/4" and 4-1/2")	-	-	-	-
Standard Traffic (A-414)	-	A-306	A-337	-	-	-	-

5" and 5-1/4" Main Valve Opening

Hydrant Style	Bonnet Repair Kit	Safety Flange Repair Kit	Extension Kit	Shoe Repair Kit	Main Valve Repair Kit	Tamper Proof Retrofit Kit*	
						Left	Right
Super Centurion 350	-	A-301-35	A-320-35	-	-	284275	282476
Super Centurion 250 & 200	280355	A-301	A-320	280357	280359	284275	282476
Centurion	280355	A-301	A-320	280357	280359	284275	284276
Super Centurion Spin-In	280355	A-301	A-320	-	-	-	-
Centurion Spin-In	280355	A-301	A-320	-	-	-	-
Improved	280361	A-301 (after 1972)	A-320 (after 1972)	280364	280367	284275	284276
		A-301-00 (prior to 1972)	A-320-00 (prior to 1972)				
Modern Improved	-	-	A-320	280392	280394	-	-
Mueller 107	280369 (5")	A-301 (5")	A-320 (5")	280371 (5")	280373 (5")	-	-
Standard Post (A-413)	-	-	-	-	-	-	-
Standard Traffic (A-414)	-	A-308	-	-	-	-	-

* The A-374 Wrench (To operate Tamperproof Hydrant), A-384 Spanner Wrench (To assemble and disassemble Tamperproof Operating Nut Cap) and A-391 Wrench (To assemble and disassemble Tamperproof Cast Iron Hold Down Nut) are also required.


Mueller[®] Super Centurion 200, 250, and 350 Fire Hydrant Repair Kits



Bonnet Repair Kit - 280355

4-1/2" and 5-1/4"

- | | |
|---------------------------|--------------------------------------|
| (1) Bonnet gasket (Flat) | (1) Anti-friction washer |
| (1) Weather seal | (2) Stem O-rings |
| (1) Hold down nut o-rings | (1) 10.5 oz. hydrant lubricating oil |
| (1) Bonnet O-rings | (1) Instruction sheet |



Extension Repair Kit - A319-Length (4-1/2") / A320-Length (5-1/4") 350 PSI Hydrant - A319-35-Length (4-1/2") / A320-35-Length (5-1/4")

- | | |
|-----------------------|--|
| (1) Stem | (1) Bonnet gasket |
| (1) Barrel* | (1) Steel extension stem coupling |
| (1) Extension flange* | (2) Cotter pins |
| (1) Gasket | (1) 10.5 oz. can hydrant lubricating oil |
| (8) Bolts and nuts* | (1) Instruction sheet |
| (2) Clevis pins | Extension lengths: 0'6", 1'0", 1'6", 2'0", 2'6", 3'0", 3'6",
4'0", 4'6", 5'0" and 6'0" (*kits 3'-6" and longer include 2 barrels) |
| (3) O-rings* | |



Main Valve Repair Kit - 280358 (4-1/2") / 280359 (5-1/4")

- | | |
|-----------------------------|----------------------------------|
| (1) Top seat O-rings | (1) Bronze seat ring |
| (1) Bottom seat O-rings | (1) Reversible lower valve plate |
| (1) Reversible main valve § | (1) Instruction sheet |
| (1) Cap nut seals | (1) Lock washer |



Shoe Repair Kit - 280356 (4-1/2") / 280357 (5-1/4")

- | | |
|-------------------------------|--|
| (2) Drain valve facings | (1) Lock washer |
| (4) Drain valve facing screws | (6) Shoe bolts and nuts |
| (1) Drain ring housing gasket | (2) Drain ring bolts and nuts |
| (1) Top seat O-ring | (1) 10.5 oz. can hydrant lubricating oil |
| (1) Bottom seat O-ring | (1) Drain ring housing "O" ring. |
| (1) Reversible main valve § | (1) Reversible lower valve plate |
| (1) Cap nut seal | (1) Instruction sheet |



Safety Flange Repair Kit - A300 (4-1/2") / A301 (5-1/4")

350 PSI Hydrant - A300-35 (4-1/2") / A301-35 (5-1/4")

- | | |
|--|---------------------------------------|
| (1) Safety flange | (1) Bonnet gasket (Flat - A-300 only) |
| (1) Safety flange gasket (Flat - A-300 only) | (1) Bonnet "O" ring gasket |
| (8) Safety flange bolts and nuts | (1) Safety Flange "O" ring |
| (1) S.S. Safety stem coupling | (1) 10.5 oz. hydrant lubricating oil |
| (2) Clevis pins | (1) Instruction sheet |
| (3) Cotter pins | |

Tamper-proof Retrofit Repair Kit - 284275 (open left) / 284276 (open right)

- | | |
|-----------------------|--------------------------|
| (1) Bonnet O-ring | (2) Retainer clip |
| (1) Hold down nut | (1) Hold down nut O-ring |
| (1) Operating nut cap | (1) Anti-friction washer |
| (1) Ring retainer | (1) Weather seal |
| (1) Operating nut | (1) Instruction sheet |