

Cool Gel®

Heat barrier spray



Cool Gel® can be used to protect lead free valves during the soldering process and with any other soldering or brazing job to protect components and materials from costly heat damage. Cool Gel's unique, no-drip gelled formula evaporates within 48 hours, eliminating cleanup. Using Cool Gel is easier than using a heat blanket, and provides assurance the job can be completed without costly heat damage.

- Protects lead free valves during soldering
- Reduces the threat of costly heat damage to rubber seals and gaskets
- Protects components and materials during soldering to avoid heat damage
- Protects painted and finished surfaces from discoloration due to torch heat
- Unique gelled formula sticks to surfaces without dripping or running off
- Clear, non-staining gel leaves no residue, eliminating cleanup
- Safe, non-toxic, harmless to skin, and odorless
- Made in U.S.A.

For Use On:

- Lead free valves and fittings
- New construction and piping installation
- Shower valves installation and repair
- Trim work and cabinetry
- Drywall and studs
- Commercial rooftop repair
- Furnace repair and installation
- Refrigeration repair and installation
- Medical gas systems
- Valve installation and repair
- Welding

| | | |
|-------|--------|-------------|
| 11513 | 1 pt. | 24 per case |
| 11509 | 1 qt | 12 per case |
| 11503 | 5 gal. | 1 per case |

RIGHT
FOR
THE
JOB.™

LA-CO®

laco.com

LA-CO Industries Inc.
1201 Pratt Boulevard
Elk Grove Village, IL 60007-5746 USA
(1) 800.621.4025
(1) 847.956.7600
Customer Service@laco.com
LP97R00297

LA-CO Industries Europe S.A.S.
ALLEE DES COMBES
PI DE LA PLAINE DE L'AIN
01150 BLYES
France
Tel: +33 (0) 4 74 46 23 23
info@eu.laco.com

