


SPECIFICATION


Seamless die-drawn construction of type 304, 18-8 stainless steel. Interior and top surfaces polished to a non-porous Hand-Blended Just Finish with highlighted bowl rim. Fully coated underside insulates for sound, and reduces condensation. Straight-sided compartment with $1^{3}/_{4}^{\mu}$ radius corners provides greater capacity. Self-rimming top mount Grip-Rim Plus with 300 series stainless steel mounting channels. Conforms to ASME/ANSI A112.19.3M. Drain punch #35 centered for Just J-35 unless otherwise specified.

To be specified :

Faucet hole punching:

- (1) Hole Centered
- □ (2) Holes on 4" centers
- □ (3) Holes on 4 "centers(illustrated)
- □ (4) Holes on 4" centers
- Alternate Punching: Faucet Model: Punching required:





MODEL NO.	А	В	С	D	E	F	CUTOUT*
DL-1625-B-GR	16	25	10	10	4-1/2	2	15-1/4 x 24-1/4
DL-17537-B-GR	17-1/2	37	11-1/2	16	4-1/2	2	16-3/4 x 36-1/4
DL-1829-B-GR	18	29	12	12	4-1/2	2	17-1/4 x 28-1/4
DL-1925-B-GR	19	25	14	10	3-1/2	1-3/4	18-1/4 x 24-1/4
DL-1933-B-GR**	19	33	14	14	3-1/2	1-3/4	18-1/4 x 32-1/4
DL-2025-B-GR	20	25	14	10	4-1/2	2	19-1/4 x 24-1/4
DL-2037-B-GR	20	37	14	16	4-1/2	2	19-1/4 x 36-1/4
DL-2128-B-GR	21	28	16	11-1/2	3-1/2	1-3/4	20-1/4 x 27-1/4
DL-2228-B-GR	22	28	16	11-1/2	4-1/2	2	21-1/4 x 27-1/4
* Cutout dimensions shown (Front-to-Back) x (Left-to-Right) - Corners of cutout may be square or up to 1/2" radius.							

** This model has 1 1/8 center partition and 1 15/16 end flanges.

FUNCTIONAL DESIGN, QUALITY, AND SPECIFICATIONS LISTED DESCRIBE THE JUST STANDARD OF QUALITY. WHEN MAKING COMPARISONS WITH OTHER OFFERINGS, INSIST ON THE JUST QUAL ITY OF CONSTRUCTION. FOR ADDITIONAL INFORMATION REGARDING THE COMPLETE LINE OF JUST SINKS, FAUCETS AND DRAINS, VISIT OUR WEB SITE AT www.justmfg.com

 JUST MANUFACTURING COMPANY
 9233 KING STREET . FRANKLIN PARK . ILLINOIS . 60131-2111

 PH: 847-678-5150
 FAX: 847-678-6817
 E-MAIL: custserv@justmfg.com
 www.justmfg.com

REVISED-5/2004

()

₩ <