



SPECIFICATION  
SUBMITTAL SHEET  
Reviewed: 3/00

**TRADE NAME:**

**ECONOTHERM®**

**DESCRIPTION:**

Polymer Foam Insulation  
(A flexible, polymer based, low density,  
closed cell, chemically inert pipe insulation)

**PHYSICAL PROPERTIES:**

<b>Color</b>	Charcoal Gray	
<b>Temperature Limits</b>	Maximum 200°F	Minimum 0°F
<b>Density (Dry)</b>	1.5 lbs/ft <sup>3</sup>	
<b>Water Absorption</b>	Less than 1% (by volume)	
<b>Water Vapor Permeability</b>	Less than 0.05 perm-in	
<b>Shrinkage @ 200°F</b>	4%	
<b>Mold Growth/Humidity; Air Erosion</b>	No mold growth; No erosion	
<b>Flame Spread - ASTM E84</b>	25 or less (up to 1" wall)	
<b>Smoke Developed - ASTM E84</b>	50 or less (up to 1" wall)	
<b>Thermal Conductivity</b>	Mean Temperature °F 75°F	"k" Value 0.25 Btu-in/hr-ft <sup>2</sup> -°F

**Standard Sizes:**

1/4" CTS through 2 1/2" CTS;  
3/8", 1/2", 3/4", and 1" wall;  
6' lengths.

**Uses:**

Longitudinally semi-slit pipe insulation. Used primarily  
for domestic hot and cold water and HVAC/R piping.

**Specification Compliance:**

ASTM C 534\*, ASTM E 162, ASTM E 662,  
CAN/ULC-S102.2-M88 (25/50), NFPA 90A/B  
UL 94 HBF.

\*ASTM C 534 is limited to elastomeric materials. ECONOTHERM meets or exceeds  
the physical requirements listed in ASTM C 534 with the exception of density.



Nomaco K-Flex, 100 Nomaco Drive, Youngsville, North Carolina 27596 p 800-765-6475 f 800-765-6471