

For Commercial & Residential Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Quick'N Easy®

Braided Stainless Steel & Nylon Faucet Connectors

Features

- Available in 12", 16", 20", 30" and 36"
(305, 406, 508, 762 and 914mm) lengths


- NSF & IAPMO Listed  

Pressure – Temperature


Maximum Temperature: Stainless Steel: 180°F (82°C)

Nylon: 140°F (60°C)

Maximum Pressure: 125psi (8.75 bar)



Stainless Steel



Nylon

MODEL	✓ TO SUBMIT	DESCRIPTION	DIMENSIONS		MATERIAL
			A		
			in.	mm.	
381 2BSS		3⁄8" OD Compression x 1⁄2" Faucet Connection	12	305	Stainless Steel
381 2BSPB		3⁄8" OD Compression x 1⁄2" Faucet Connection	12	305	Stainless Steel w/Polished Brass Finish
381 2B		3⁄8" OD Compression x 1⁄2" Faucet Connection	12	305	Nylon
381 6BSS		3⁄8" OD Compression x 1⁄2" Faucet Connection	16	406	Stainless Steel
381 6B		3⁄8" OD Compression x 1⁄2" Faucet Connection	16	406	Nylon
382 0BSS		3⁄8" OD Compression x 1⁄2" Faucet Connection	20	508	Stainless Steel
382 0BSPB		3⁄8" OD Compression x 1⁄2" Faucet Connection	20	508	Stainless Steel w/Polished Brass Finish
382 0B		3⁄8" OD Compression x 1⁄2" Faucet Connection	20	508	Nylon
383 0BSS		3⁄8" OD Compression x 1⁄2" Faucet Connection	30	762	Stainless Steel
383 6BSS		3⁄8" OD Compression x 1⁄2" Faucet Connection	36	914	Stainless Steel
221 2BSS		1⁄2" OD Compression x 1⁄2" Faucet Connection	12	305	Stainless Steel
221 2B		1⁄2" OD Compression x 1⁄2" Faucet Connection	12	305	Nylon
221 6BSS		1⁄2" OD Compression x 1⁄2" Faucet Connection	16	406	Stainless Steel
222 0BSS		1⁄2" OD Compression x 1⁄2" Faucet Connection	20	508	Stainless Steel
222 0B		1⁄2" OD Compression x 1⁄2" Faucet Connection	20	508	Nylon
223 0BSS		1⁄2" OD Compression x 1⁄2" Faucet Connection	30	762	Stainless Steel
121 2BSS		1⁄2" FIPS x 1⁄2" Faucet Connection	12	305	Stainless Steel
121 6BSS		1⁄2" FIPS x 1⁄2" Faucet Connection	16	406	Stainless Steel
122 0BSS		1⁄2" FIPS x 1⁄2" Faucet Connection	20	508	Stainless Steel
122 0B		1⁄2" FIPS x 1⁄2" Faucet Connection	20	508	Nylon
123 0BSS		1⁄2" FIPS x 1⁄2" Faucet Connection	30	762	Stainless Steel
F381 2BSS		3⁄8" OD Flare x 1⁄2" Faucet Connection	12	305	Stainless Steel
F382 0BSS		3⁄8" OD Flare x 1⁄2" Faucet Connection	20	508	Stainless Steel
F38 20B		3⁄8" OD Flare x 1⁄2" Faucet Connection	20	508	Nylon
381 2SSD		3⁄8" OD Compression x 3⁄8" copper tube Delta connector	12	305	Stainless Steel
382 0SSD		3⁄8" OD Compression x 3⁄8" copper tube Delta connector	20	508	Stainless Steel
381 2WSS		3⁄8" OD Compression x 3⁄8" OD Compression	12	305	Stainless Steel
382 0WSS		3⁄8" OD Compression x 3⁄8" OD Compression	20	508	Stainless Steel

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



815 Chestnut St., No. Andover, MA 01845

Tel: 978.688.1811 • Fax: 978.794.1848

www.wattsbrass-tubular.com