

## HunkLite® Pad Concrete Equipment Pad

### Description

HunkLite® is a medium-weight pad designed to support HVAC outdoor units and other outdoor equipment. It provides the strength and durability of concrete, while being up to 18% lighter than solid concrete. Available in both 2" and 3", depending on local building code requirements.

### Application

- HVAC outdoor units
- Installation: pad should be placed on compacted level soil, gravel, or harder surfaces, including but not limited to concrete or asphalt.

### Features

- Medium-weight, durable, and optimized for HVAC outdoor unit weights
- Hollow bottom with rib supports to remove weight while keeping strength (18% lighter), with continuous 9-gauge steel reinforcement
- Environmentally friendly – made from 15% recycled material
- Non-skid surface
- No buoyancy – ideal for coastal regions
- Unaffected by water, soil, fungus, bacteria, UV exposure or extreme weather
- Concrete gray color
- Drillable for securing unit (¼ x 1-¼" Tapcon® recommended)

### Advantages

- 3000+ PSI reinforced concrete
- Recommended temperature range: -48°F min
- Heat/flame resistance:
  - Resists incidental torch contact
  - May be used under continuous heating devices, such as water heaters
- Tested per ASTM C67 (flawless performance under 25-cycle testing regimen)
- Tested per ASTM D2299. Does not crack, flake, or warp when subjected to...
  - R-22 or R134a refrigerant
  - Compressor oil
  - Salt solution (20% by volume)
  - Synthetic canine urine

### Made in USA by DiversiTech

### Warranty

Limited Lifetime Warranty



## General Specification

### 2" Thick Pads

CATALOG NUMBER	SIZE (IN.)	ESTIMATED ALLOWABLE LOAD	QUANTITY PER PALLET	PAD WEIGHT
L2424-2	24x24x2	1440 LBS	20	46 LBS
L2430-2	24x30x2	1680 LBS	20	53 LBS
L2432-2	24x32x2	1760 LBS	15	46 LBS
L2436-2	24x36x2	1920 LBS	20	55 LBS
L2626-2	26x26x2	1600 LBS	20	35 LBS
L2838-2	28x38x2	2160 LBS	20	82 LBS
L3036-2	30x36x2	2160 LBS	20	89 LBS
L3042-2	30x42x2	2400 LBS	20	102 LBS
L3143-2	31x43x2	2480 LBS	20	98 LBS
L3232-2	32x32x2	2080 LBS	20	81 LBS
L3237-2	32x37x2	2280 LBS	20	97 LBS
L3244-2	32x44x2	2560 LBS	15	113 LBS
L3636-2	36x36x2	2400 LBS	15	120 LBS
L3648-2	36x48x2	2880 LBS	15	145 LBS

### 3" Thick Pads

CATALOG NUMBER	SIZE (IN.)	ALLOWABLE LOAD	QUANTITY PER PALLET	PAD WEIGHT
L2424-3	24x24x3	1440 LBS	15	52 LBS
L2430-3	24x30x3	1680 LBS	20	70 LBS
L2436-3	24x36x3	1920 LBS	15	106 LBS
L3030-3	30x30x3	1920 LBS	15	69 LBS
L3036-3	30x36x3	2160 LBS	15	94 LBS
L3042-3	30x42x3	2400 LBS	15	131 LBS
L3048-3	30x48x3	2640 LBS	15	120 LBS
L3232-3	32x32x3	2080 LBS	15	87 LBS
L3244-3	32x44x3	2560 LBS	10	149 LBS
L3636-3	36x36x3	2400 LBS	10	105 LBS
L3642-3	36x42x3	2640 LBS	10	120 LBS
L3648-3	36x48x3	2880 LBS	10	135 LBS
L3842-3	38x42x3	2720 LBS	10	215 LBS