



DESIGN FEATURES

- Chloramine resistant washers
- Exclusive POWR-TIGHT 12 -point-crimp
- Chloramine resistant tubing
- Withstands dramatic changes in water pressure
- Easy installation, no special tools required

COMPLIANCES/LISTINGS

- IAPMO Certified File number 2111
- ASME A112.18.6/CSA B125.6

MATERIAL SPECIFICATIONS

- Working Pressure: 160 psi
- Operating Temperature: 33° F - 140° F
- Tubing: UltraCore
- Nuts & End Fittings: Brass
- Washers: NSF/ANSI 61 Compliant



3689 Arrowhead Drive, Carson City, NV 89706
 Phone (800) 854-3215 Fax (800) 243-1777
 E-mail sales@lspproducts.com Website www.lspproducts.com
 Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained.

**ULTRACORE
 WASHING MACHINE CONNECTOR
 Specification Sheet**

Front Load Washers

Part Number	Description	Length	ID	Braid	Liner
WAS-148-PP	3/4" FGHT X 3/4" FGHT	48"	1/2"	Engineered Polymer	Ultra-Core
WAS-160-PP		60"	1/2"	Engineered Polymer	
WAS-172-PP		72"	1/2"	Engineered Polymer	

3/8" ID for Top Load Washers

Part Number	Description	Length	ID	Braid	Liner
WAS-348-PP	3/4" FGHT X 3/4" FGHT	48"	3/8"	MightyFlex SS	Reinforced PVC
WAS-360-PP		60"	3/8"	MightyFlex SS	
WAS-372-PP		72"	3/8"	MightyFlex SS	

3/8" ID with 90 Degree F.G.H.T

Part Number	Description	Length	ID	Braid	Liner
WAS-448-PP	3/4" FGHT X 3/4" 90° FGHT	48"	3/8"	MightyFlex SS	Reinforced PVC
WAS-460-PP		60"	3/8"	MightyFlex SS	
WAS-472-PP		72"	3/8"	MightyFlex SS	
WAS-496-PP		96"	3/8"	MightyFlex SS	

Product Submittal	
Job Name:	
Date:	
Part Number	Quantity
Architect:	
Contractor:	