

# Velocity™ Wire Pulling Lubricant

- High cling factor
- Maximum friction reduction
- Specification grade
- Compatible with all cable types
- Temperature stable
- Non-combustible residue
- Environmentally safe — non-toxic, non-flammable and non-corrosive



| Description          | Part No. |
|----------------------|----------|
| 1-qt. Squeeze Bottle | 31-276   |
| 1-gal. Bucket        | 31-277   |
| 5-gal. Bucket        | 31-278   |

# Noalox® Anti-Oxidant

- Anti-oxidant compound improves efficiency and service life of aluminum electrical connections
- Suspended zinc particles penetrate and cut aluminum oxide
- Provides additional inner-strand and inner-conductor current paths for improved conductivity and cooler connections
- Carrier material excludes air to minimize further oxidation
- For use with pressure-type wire connectors including lugs, taps, service entrances and split-bolts
- Reduces galling and seizing when applied on aluminum conduit joints promoting good ground continuity



| Description          | Part No. |
|----------------------|----------|
| 1/2-oz. Tube         | 30-024   |
| 4-oz. Squeeze Bottle | 30-026   |
| 8-oz. Squeeze Bottle | 30-030   |
| 8-oz. Brush Cap      | 30-031   |
| 1-gal. Bucket        | 30-032   |
| 5-gal. Bucket        | 30-040   |
| 55-gal. Drum         | 30-1216  |

Compatible with aluminum to aluminum and aluminum to copper connections.

For a Safety Data Sheet on lubricants and other products visit us at [idealind.com](http://idealind.com).

