

Standard Series



1/4" Standard Charging Hose

750 psi working; 3000 psi burst

Ideal for use with all standard refrigerants (except high pressure)

Permeation can be detected and will vary with refrigerant type and time of exposure



STANDARD SERIES

STANDARD 1/4" X 1/4" CHARGING HOSE (PSI 750/3000)				
LENGTH	BLUE	YELLOW	RED	B/Y/R 3 PACK
36" (91cm)	CL-36B	CL-36Y	CL-36R	CCL-36
48" (122cm)	CL-48B	CL-48Y	CL-48R	CCL-48
60" (152cm)	CL-60B	CL-60Y	CL-60R	CCL-60
72" (182cm)	CL-72B	CL-72Y	CL-72R	CCL-72

Flexible Metal Hose



900 psi working; 3500 psi burst

Unlike charging hoses, flexible metal lines will not permeate under vacuum. Our metal lines feature finger-tight o-ring coupler ends.



D10472

PART NO.	DESCRIPTION
D10436	1/4" x 36" Flexible metal line (one 45° fitting)
D10472	1/4" x 72" Flexible metal line (one 45° fitting)
D10636	3/8" x 36" Flexible metal line (one 45° fitting)
D10660	3/8" x 60" Flexible metal line (one 45° fitting)
DV-294	1/4" x 10" Flexible metal line (one 45° fitting)
P90009	1/4" Replacement o-ring (10 pack)
P90012	3/8" Replacement o-ring (10 pack)

Hose Replacement Parts



CLSX-RH

33112RK

T21295

PART NO.	DESCRIPTION
33112RK	1/4" Secure Seal Rebuild Kit
33115RK	5/16" Secure Seal Rebuild Kit
CLSX-RK	CLSX Secure Seal Rebuild Kit
CLSX-RH	CLSX Replacement Head
T21295	Snap Ring Pliers for CLS Secure Seal Fittings, Includes 33112RK 1/4" Rebuild Kit
P90022	O-ring for T21295 and 33112RK (10 pack)
P511	Gasket for 1/4" CLE, CLV, CLB Series Hose (6 pack)
P90514	1/4" Depressor for CLE, CLV and CLB Series (5 pack) used with P509
P90016	Gasket for 3/8" Hose (10 pack)
P90008	Gasket for 1/2" Heavy-duty Black Charging Hose (5 pack)

Secure Seal Adapters



33112N

33113N

PART NO.	DESCRIPTION
33112N	1/4" QC x 1/4" SAE
33113N	1/4" QC x 1/4" SAE 90°
33115N	5/16" QC x 1/4" SAE
33116N	5/16" QC x 1/4" SAE 90°