DREA THERMOSTATIC SHOWER SYSTEM WITH DUAL SHOWERHEADS, SLIDE BAR AND HAND SHOWER

SKU: 955115

Code: SH6103, SHDR9005, SHHS4030G, SHH1010, SHDR9007, SHDR9009, SH6006, SH6040, SHRSB820RG, SHSB3040, SHWE2040, SHRSA122



FEATURES

Material: Metal Shower Head Swivel: Yes Shower Head Spray: Rainfall Connection Type: NPT Diverter Outlets: 3 Cartridge Type: Ceramic Disc

ASME A112.18.1/CSA B125.1, ASME A112.18.2/CSA B125.2, CEC Listed, WaterSense by IAPMO, Massachusetts Accepted, LISTED ID: SH6103, SH6006, SH6040, SHHS4030G*, SHRSB820RG*, SHH1010*, SHWE2040*, N/A, SHRSA122*, SHDR9005*, SHDR9009*, SHDR9007*



- Thermostatic technology keeps shower temperature within 1 degree Celsius.
- Temperature outlet factory calibrated to 104 degrees Fahrenheit and can be easily adjusted up or down to user's comfort level.
- Six total settings allow for shared water flow between outlets, giving you the ability to use two functions at once.
 Metal handles.
- Dual single function shower heads (full spray) with easy-clean silicone nozzles.
- Single function hand shower.
- 60" 72" stretchable metal shower hose.
- Adjustable angle for hand shower mount.
- Must be installed in accordance with provided installation instructions.
- Recommended valve installation depth 1-5/8" to 2-3/8".
- Included Rough-in valves:
 - Thermostatic rough-in valve features scald guard protection, high temperature limit stop, integral water stops and check valve, a ceramic cartridge, and a bronze valve body.
 - Volume control rough-in valve features a ceramic disc cartridge and brass valve body.
 - Diverter valve features a ceramic disc cartridge and brass valve body. An available Single-Function Diverter valve Cartridge restricts water flow to one outlet at a time.

DREA IN-WALL SHOWER DIVERTER TRIM

SKU: 953921 Code: SHDR9005, SHDR9005, SH6103



FEATURES

Material: Metal Required for Installation: Rough-in valve: SH6103 or SH6101


ASME A112.18.1/CSA B125.1, ASME A112.18.2/CSA B125.2, ICC/ANSI A117.1, Massachusetts Accepted, LISTED ID: SHDR9005*, SH6103



- Metal construction for ultimate strength and durability.
- Not intended as a shut off valve.
- Six total settings allow for shared water flow between outlets, giving you the ability to use two functions at once.
- Wall thickness range: 1" 1-3/4".
- Available Single-Function Diverter Valve Cartridge restricts water flow to one outlet at a time.
- Optional Rough-in Valve:
 - Brass valve body.
 - Ceramic cartridge.
 - Recommended valve installation depth 1-5/8" to 2-3/8".
 - \circ $\;$ Must be installed in accordance with provided installation instructions.

DREA IN-WALL SHOWER DIVERTER TRIM

SKU: 953921 Code: SHDR9005, SHDR9005, SH6103



8" MODERN ROUND RAINFALL SHOWER HEAD - 1.8 GPM

SKU: 948948-18 Code: SHRSB820RG, SH484203, SH485499



FEATURES

Material: ABS Shower Head Swivel: Yes Shower Head Spray: Rainfall

ASME A112.18.1/CSA B125.1, CEC Listed, WaterSense by IAPMO, Massachusetts Accepted, LISTED ID: SHRSB820RG*



ADDITIONAL FEATURES

- Single function shower head (full spray).
- Easy clean rubber nozzles.
- Brass ball joint.

CYLINDRICAL WALL-MOUNT SHOWER ARM

SKU: 953769 Code: SHRSA122, SH484204

FEATURES

Material: Metal Connection Type: 1/2" NPT



ASME A112.18.1/CSA B125.1, Massachusetts Accepted, LISTED ID: SHRSA122*




ADDITIONAL FEATURES

• Escutcheon included.

CYLINDRICAL WALL-MOUNT SHOWER ARM

SKU: 953769 Code: SHRSA122, SH484204



REVISED 9/17/2024

(ISI) SIGNATURE HARDWARE

See Website For Warranty Information signaturehardware.com/warranty

CONTEMPORARY SLIDE BAR FOR HAND SHOWER

FEATURES

SKU: 948919 Code: SHSB3040, SH484206, SH485501




LISTED ID: N/A

ADDITIONAL FEATURES

• Adjustable angle for hand shower mount.

CONTEMPORARY SLIDE BAR FOR HAND SHOWER

SKU: 948919 Code: SHSB3040, SH484206, SH485501



(ISI) SIGNATURE HARDWARE

CONTEMPORARY ROUND WATER SUPPLY ELBOW FOR HAND SHOWER

SKU: 932365 Code: SHWE2040, SH484207, SH485502

FEATURES

Material: Metal Connection Type: 1/2" NPT




ASME A112.18.1/CSA B125.1, Massachusetts Accepted, LISTED ID: SHWE2040*



- 1/2" Female wall connection.
- 1/2" Male hose connection.

CONTEMPORARY ROUND WATER SUPPLY ELBOW FOR HAND SHOWER

SKU: 932365 Code: SHWE2040, SH484207, SH485502



CONTEMPORARY TUBULAR HAND SHOWER

SKU: 948923 Code: SHHS4030G, SH488912



FEATURES

Material: ABS Hand Shower Spray: Full Hand Shower Flow Rate: 1.8 gpm (6.8 L/min) @ 80 psi

ASME A112.18.1/CSA B125.1, CEC Listed, WaterSense by IAPMO, Massachusetts Accepted, LISTED ID: SHHS4030G*




ADDITIONAL FEATURES

- Single function hand shower.
- Easy-clean spray nozzles.
- Factory installed backflow prevention check valve.
- Hose sold separately.

CONTEMPORARY TUBULAR HAND SHOWER

SKU: 948923 Code: SHHS4030G, SH488912





REVISED 9/17/2024

(ISI) SIGNATURE HARDWARE

See Website For Warranty Information signaturehardware.com/warranty

60" METAL HAND SHOWER HOSE

SKU: 948088 Code: SHH1010



FEATURES Connection Type: 1/2" IPS


ASME A112.18.1/CSA B125.1, Massachusetts Accepted, LISTED ID: SHH1010*




- Hand Sprayer sold seperately.
- 60" 72" stretchable metal shower hose.
- Double spiral constructed hose.

60" METAL HAND SHOWER HOSE

SKU: 948088 Code: SHH1010





REVISED 9/17/2024

(ISI) SIGNATURE HARDWARE

See Website For Warranty Information signaturehardware.com/warranty

3-WAY IN-WALL DIVERTER ROUGH-IN VALVE - 3/4"

SKU: 446519 Code: SH6103



FEATURES Material: Brass Cartridge Type: Ceramic Disc


IAPMO, ASME A112.18.1/CSA B125.1, ASME A112.18.2/CSA B125.2, Massachusetts Accepted, LISTED ID: SH6103



- Six total settings allow for shared water flow between outlets, giving you the ability to use two functions at once.
- Ceramic cartridge.
- Available Single-Function Diverter Valve Cartridge restricts water flow to one outlet at a time.
- Not intended as a shut off valve.
- For installations only requiring 2 outlets, the 3rd outlet may be looped into one of the existing pipes.
- Compatible with Beasley, Berwyn, Boca Raton, Drea, Edenton, Elita, Greyfield, Gunther, Hibiscus, Key West, Lentz, Lexia, Pendleton, Pinecrest, Provincetown, Rigi, Sefina, Vassor and Vilamonte Diverter Trims.

3-WAY IN-WALL DIVERTER ROUGH-IN VALVE - 3/4"

SKU: 446519 Code: SH6103



REVISED 10/11/2024

VOLUME CONTROL ROUGH-IN VALVE - 3/4" CONNECTION

SKU: 447696 Code: SH6040



FEATURES

Material: Bronze Connection Type: 3/4" NPT Cartridge Type: Ceramic Disc


IAPMO, ASME A112.18.1/CSA B125.1, Massachusetts Accepted, LISTED ID: SH6040



- Intended for use with a thermostatic valve and trim.
- Bronze valve body.
- Ceramic cartridge.
- Compatible with Beasley, Berwyn, Boca Raton, Drea, Edenton, Elita, Greyfield, Gunther, Hibiscus, Key West, Lentz, Lexia, Pendleton, Pinecrest, Provincetown, Rigi, Sefina, Vassor and Vilamonte Volume Control Trims.

VOLUME CONTROL ROUGH-IN VALVE - 3/4" CONNECTION

SKU: 447696 Code: SH6040



THERMOSTATIC ROUGH-IN VALVE - 3/4" CONNECTION

SKU: 447694 Code: SH6006



FEATURES

Material: Bronze Flow Rate: 18.2 gpm (68.9 L/min) @ 80 psi Connection Type: 3/4" NPT Cartridge Type: Thermostatic

IAPMO, ASME A112.18.1/CSA B125.1, Massachusetts Accepted, LISTED ID: SH6006



- Compatible with Beasley, Berwyn, Boca Raton, Drea, Edenton, Elita, Greyfield, Gunther, Hibiscus, Key West, Lentz, Lexia, Pendleton, Pinecrest, Provincetown, Rigi, Sefina, Vassor and Vilamonte Thermostatic Valve Trim.
- For proper installation, requires use of volume control valve and trim.
- Bronze valve body.
- Factory-calibrated comfort setting at 104 degrees Fahrenheit.
- Water inlet stops and check valve.
- Thermostatic technology keeps shower temperature ±1 degree Celsius.