



Carefree® Max ProX

Low Odor Floor Finish / Sealer

Carefree® Max ProX Low Odor Floor Finish / Sealer is a versatile multi-surface, multi-maintenance floor finish/sealer that simplifies floor care programs. Low odor finish ideal for 24 hour facilities.

Features & Benefits

- Versatile floor sealer/finish works with any maintenance method and equipment on all floor types
- Leaves finished floors with exceptional clarity, high gloss and excellent durability
- Meets ASTM D-2047 slip resistance requirement
- Easy to apply and remove from all floor types
- Product does not contain any intentionally added PFAS

Applications

- Responds beautifully to conventional, high-speed or UHS equipment and maintenance procedures
- May require a sealer on highly polished stone, glazed clay tile, and some rubber floors
- Not intended for use on cork, wood, or bamboo flooring unless specified by the manufacturer





Carefree[®] Max ProX

Low Odor Floor Finish / Sealer

Use Instructions

Applying Floor Finish

- Blockade areas to be stripped or finished. Floors will be very slippery until dry.
- Strip floor, using a Diversey stripper per the instructions on the stripper label.
- Apply 2-3 uniform coats using a clean mop.
- Allow 30 minutes drying time between coats. Temperatures, humidity and ventilation may affect drying time.

Maintenance

- Dust mop or sweep.
- Clean the floor with a mop or an automatic scrubber using the recommended Diversey brand cleaner according to label directions.
- To enhance appearance, use any of the following methods: *Spraybuff* with a Diversey Spray Buff, a red pad and 175-1500 rpm equipment. *Drybuff* using a medium to aggressive pad and 1000-1500 rpm equipment. *Ultra High Speed* burnish using a medium to aggressive pad and 2000 rpm equipment.

Before Recoating

- Dust mop or sweep.
- Clean the floor with a mop or an automatic scrubber using the recommended Diversey brand cleaner according to the label instructions.
- Blockade area and apply 1-2 uniform coats of finish using a clean mop.

Removal

- Remove using Diversey floor stripper according to label directions.

Best Results

- Do not dilute.
- Do not use on surfaces colder than 50°F (10°C) @ 15% RH.
- To avoid contamination, do not return unused product to original container.
- Not intended for use on wood.

Note: Floors will be slippery when wet or contaminated with foreign materials. Promptly clean-up spills and foreign materials. Not intended for use in outdoor areas. Meets ASTM D-2047 requirements for slip resistance.

Technical data	Carefree [®] Max ProX Low Odor Floor Finish / Sealer
Color/Form	Opaque off-white liquid
pH	8.45 - 8.65
Scent	Bland
Shelf Life	2 Years

Product	Pack size	Dilution	Product code	
Carefree [®] Max ProX Low Odor Floor Finish / Sealer	6 x 2.64 U.S. qt. / 2.5 L ProSpeed ^{TM/MC} BIB (Bag-in-Box)	Ready-to-use	101110018	
Carefree [®] Max ProX Low Odor Floor Finish / Sealer	4 x 1 gal. / 3.78 L Containers	Ready-to-use	101110017	
Carefree [®] Max ProX Low Odor Floor Finish / Sealer	1 x 5 gal. / 18.9 L Envirobox ^{TM/MC}	Ready-to-use	101110016	

Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at www.diversey.com or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate.