



The new degree of comfort.®



Residential Heavy Duty Gas  
**Professional Classic**  
Heavy Duty ULN Water Heaters

## Professional Classic® Heavy Duty Ultra Low NOx water heaters exceed ANSI standards for flammable vapor ignition resistance

### Performance

- Recovery Capacity: 72.8 gallons per hour\*\*
- FHR: 135 gallons for 75-gallon model and 150 gallons for 98-gallon model

### Guardian™ System

- Exclusive fuel shut-off device
- Maintenance free – no filter to clean
- Protective control system that disables the heater in the presence of flammable vapor accumulation

### Integrated Burner Safety System

- Bi-metal temperature sensor maintains safe burner operation

### High Altitude Compliant

- All models are certified for applications up to 10,000 feet above sea level

### Plus...

- Integrated self diagnostic system control for easy installation and service
- Eco-friendly burner, ultra low NOx design meets 14 ng/J NOx requirements
- Premium grade anode rod provides long-lasting tank protection
- Enhanced-flow brass drain valve
- Temperature and pressure relief valve included
- Low lead compliant
- Side water connections for space heating applications
- Standard replacement parts


### Warranty

- 6-Year limited tank and parts warranty\*
- With ProtectionPlus® the 6-year limited tank warranty becomes 10-year

\*See Warranty Certificate for complete information

**Efficiency** | All models tested according to ANSI test procedures, and meet or exceed the thermal efficiency and standby loss requirements of current ASHRAE standard (EPact). Also exceeds energy efficiency codes of all states including California Energy Commission (CEC).

**Safety and Construction** | Design certified by CSA: For operation at 160 degrees; meets all safety and construction requirements of ANSI Z21.10.3; as an automatic storage or instantaneous water heater; as an automatic circulating tank water heater; and for operation on combustible floors and in alcove installations. All models are North Carolina Code compliant. **Certified for 150 PSI maximum working pressure.**



**Professional Classic**  
**Heavy Duty Ultra Low NOx**  
75 and 98-Gallon Capacities  
75,100 BTU/h  
Natural Gas



DESCRIPTION				FEATURES			ROUGHING IN DIMENSIONS (SHOWN IN INCHES)										ENERGY INFO.
T Y P E	NOMINAL GALLON CAPACITY	RATED GALLON CAPACITY	MODEL NUMBER	GAS INPUT IN THOUS. BTU/H NAT.	RECOVERY IN G.P.H. 90° F RISE** NAT.	FIRST HOUR RATING (GALLONS)	HEIGHT TO VENT A	TANK HEIGHT B	DIAM. C	HT. TO GAS CONN. D	VENT SIZE E	WATER CONN. CENTER F	HT. TO SIDE T&P VALVE G	WATER CONN. SIZE H	FRONT TO BACK I	SHIP WT. (LBS)	UNIFORM ENERGY FACTOR (UEF)
Tall	75	73	PROG75-75U RH EC1	75.1	72.8	135	64	60	26-1/4	14-1/4	4	11	52-1/4	1	30-1/4	315	0.59
Tall	98	93	PROG98-75U RH EC1	75.1	72.8	150	67-7/8	64	27-1/4	14-1/4	4	11	57-3/8	1	31-1/8	356	0.57

Uniform Energy Factor and rated gallon capacity based on Department of Energy (DOE) requirements.

\*\*Recovery Capacity is based upon a 90° F water temperature rise and calculated per ANSI Z21.10.3 standards.

*In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.*

Rheem Water Heating • 1115 Northmeadow Parkway, Suite 100  
Roswell, Georgia 30076 • [www.rheem.com](http://www.rheem.com)



INTEGRATED HOME COMFORT