Honeywell Home



ElitePRO™ S1200 Smart ThermostatPremium design. Pro-grade performance.

The sleek Honeywell Home ElitePRO S1200 Smart Thermostat delivers modern design, customizable touchscreens, and advanced indoor air quality (IAQ) control.¹ Homeowners can even see and speak to visitors at the door directly from the thermostat — compatible with First Alert® and Ring® streaming doorbells.

Combined with the Pro-IQ platform, ElitePRO helps you compete at the top while super-charging your business.



Designed for pros. Built to impress.





















Doorbell integration

Built-in support for live video doorbells like First Alert® VX1 or Ring®.



Customizable display

Homeowners can personalize the idle screen theme and color combinations to match their home style.



Pro-IQ Your edge in every customer call

Pro-IQ is the platform behind every ElitePRO designed to help HVAC pros do more with less. From branded visibility to remote setup and system insights, it turns everyday installs and customer calls into lasting business relationships.

All managed in one place, via the Resideo pro app.

| | ELITEPRO™S1200 | ELITEPRO™ S1200 SMART | ELITEPRO™ S1200 SMART | ELITEPRO™ S1200 SMART |
|-----------------------------------|--|--|---|--|
| | SMART THERMOSTAT THX1200W5/U - WHITE THX1200B6/U - BLACK | THERMOSTAT WITH ROOM SENSOR YTHX1200W5/U - WHITE YTHX1200B6/U - BLACK | THERMOSTAT WITH EIM YTHX1200W7/U - WHITE YTHX1200B8/U - BLACK | THERMOSTAT FOR EIM SPARE ROOM THX1200W7S/U - WHITE THX1200B8S/U - BLACK |
| | 72 2 | 72 ½ | - 72 ½ | 72 1 |
| Dimensions | Device: 5.24"W x 3.54"H x 0.96"D 13.31cm x 8.99cm x 2.44cm Screen: 5" 12.7cm | Device: 5.24"W x 3.54"H x 0.96"D 13.31cm x 8.99cm x 2.44cm Screen: 5" 12.7cm | Device: 5.24"W x 3.54"H x 0.96"D 13.31cm x 8.99cm x 2.44cm EIM: 5.31"W x 8.07"H x 1.60"D 13.49cm x 20.50cm x 4.06cm Screen: 5" 12.7cm | Device: 5.24"W x 3.54"H x 0.96"D 13.31cm x 8.99cm x 2.44cm Screen: 5" 12.7cm |
| Stages | Up to 4H/2C heat pump or 3H/3C conventional | Up to 4H/2C heat pump or 3H/3C conventional | Up to 4H/2C heat pump or 3H/3C conventional | Up to 4H/2C heat pump or 3H/3C conventional |
| Applications | Residential & light commercial | Residential & light commercial | Residential & light commercial | Residential & light commercial |
| Customizable Display | Yes | Yes | Yes | Yes |
| Video Doorbell Streaming | Yes | Yes | Yes | Yes |
| Connectivity | Redlink™ WiFi Bluetooth® Matter | Redlink™ WiFi Bluetooth® Matter | Redlink™ WiFi Bluetooth® Matter | Redlink™ WiFi Bluetooth® Matter |
| Occupancy Sensor | Yes | Yes | Yes | Yes |
| Ambient Light Sensor | Yes | Yes | Yes | Yes |
| Works with Remote Room Sensor | Yes ¹ | Yes Included ³ | Yes ¹ | Yes ¹ |
| Works with EIM | Yes ² | Yes ² | Yes Included | Yes ² |
| Configurable Outputs ² | 2 Use to control IAQ devices, additional stages of heating / cooling, or fan speed | 2 Use to control IAQ devices, additional stages of heating / cooling, or fan speed | 4 ⁴ Use to control IAQ devices, additional stages of heating / cooling, or fan speed | 2 Use to control IAQ devices, additional stages of heating / cooling, or fan speed |
| IAQ Control ² | Humidity, VOC, & estimated CO2 | Humidity, VOC, & estimated CO2 | Humidity, VOC, & estimated CO2 | Humidity, VOC, & estimated CO2 |
| Private Label Opportunities | In-app & digital on-device | In-app & digital on-device | In-app & digital on-device | In-app & digital on-device |
| Works with Pro-IQ | Yes | Yes | Yes | Yes |
| Replaces These Models | THX321WF2003W/U, THX321WF2003W/UA, THX321WF3003W/U, THX321WF3003W/UA, TH8321WF1001/U, TH8321WF1001/UA | THX321WFS3024W/U,THX321WFS2001W/U, THX321WFS2001W/UA, THX321WFS3001W/U, THX321WFS3001W/UA | YTHM1004R3024/U, YTHM1004R3000/U, YTHM1004R3001/U, THX9421R5021WW/U, YTHX9421R7001WW/U, YTHX9421R5085WW/U, | THX9421R5021WW/U |


¹Sold separately, ²Additional HVAC equipment or accessories may be required. ³Additional sold separately, ⁴Three via the EIM, 1 via the thermostat (for hydronic heating).

A growth-engine platform built for pros





Get more done in less time. Techs can configure the thermostat installer set-up (ISU) on-app or apply saved templates.⁵ The streamlined workflow adds consistency and helps reduces errors.



Drive loyalty

Keep your contact info front and center - on the thermostat and in the homeowner's mobile app. Alerts help maintain and proactively identify issues before they escalate, helping you build trust and keep customers close.6



YTHX9421R5101WW/U.

Turn installs and service calls into income. Real-time insights help you spot maintenance needs and upsell IAQ or system add-ons — all part of a connected, whole-home solution.

More than a thermostat. A tool for growth.

The ElitePRO S1200 helps you stand out - with premium design for your customers, and powerful data-driven tools for you and your team.



Modern aesthetic

Design that fits in or stands out. Clean profiles and stylized interfaces elevate any room.



Premium finish

Available in white or black device color options to suit any style preference.



Large touchscreen

Big, clear, intuitive. Offer 5" touchscreen options for better visibility and easier control.



Customizable display

Homeowners can personalize the idle screen with clocks, weather, and other themes while selecting their preferred color combinations.



Expandable ecosystem

Flex with customer needs. Enhance the HVAC system or smart home integration with connected accessories, like a video doorbell.³



Redlink[™] technology ⁴

Connect wirelessly with room and outdoor sensors, equipment interface module (EIM), and more.



EIM compatible 4,5

Simplify the most complex jobs – helping to save time and costs. Expand applications with additional outputs and minimal wires.



Optional room sensors

Help prioritize the comfort of the room of choice and reduce hot and cold spots by pairing with Room Sensors.⁵



Indoor air quality

Comfort is more than just the perfect temperature. Maintain optimal IAQ with humidity and control ventilation to keep air fresh.²



Energy efficient

ENERGY STAR® certified. Proven to help save energy and eligible for rebates.



UWP® wall-mounting plate

Faster installations and upgrades. Leverage a standardized mounting system used in over 25 million homes already.



Powered by Pro-IQ

Save time on-the-job while retaining and growing your customer relationships. Get started with a free or paid Pro-IQ membership.



Video doorbell compatibility

See and speak to visitors at the front door directly from the thermostat. Works with First Alert® and Ring® video doorbells.¹



Occupancy detection

Smart thermostat senses and adjusts settings to help save energy and maximize comfort.



Configurable outputs

Control up to 2 IAQ devices² (humidifier, dehumidifier, or ventilators) or accommodate an additional heating or cooling stage.



HVAC system compatibility

Works with dual fuel, fan-coil, PTAC, and radiant systems.

¹ Sold separately. ² Additional HVAC equipment or accessories may be required. ³ Video doorbell integration only compatible with the ElitePRO S1200 model, doorbells sold separately. ^a Model compatibility varies; Redlink, and therefore EIM, is not compatible with ElitePRO S900. ⁵ Option to purchase as a kit with the ElitePRO S1200 or sold separately.

Get to know the ElitePRO S1200 and see how it can work for your business: resideo.com/elitepro

Resideo Technologies, Inc.

16100 N 71st Street, Suite 550 Scottsdale, Arizona 85254 Office: 480.573.5340 H_ElitePRO-S1200_EUCS| CP | 0625 © 2025 Resideo Technologies, Inc. All rights reserved. Honeywell Home is a trademark of Resideo Technologies, Inc. All rights reserved. Product features vary by model.

