



**PROFESSIONAL PRODUCTS...
SUPERIOR RESULTS™**

THE HARRIS PRODUCTS GROUP

Sterling®

Description: Sterling® premium lead-free solid wire solder

Sterling® lead-free solid wire solder meets the highest product standards. It has a tensile strength of 7130 psi and shear strength of 5970 psi. Meets or exceeds the requirements for lead-free plumbing solder set forth in the Federal Safe Drinking Water Act. It is 100% environmentally safe with no antimony or nickel.

Typical Application: General plumbing; Potable water applications



PN: 331755

DETAILS

Part Number	Size
327931	0.118" (3 mm) - 50 LB Spool
331755	0.118" (3 mm) - 50 LB Spool
331841	0.118" (3 mm) - 20 LB Spool
331895	1/16"/.062" (1.6 mm) - 50 LB Spool
331897	0.118" (3 mm) - 50 PK Spool
331898	0.118" (3 mm) - 50 EA Spool
331935	0.118" (3 mm) - 6 PK

TECHNICAL

Chemical Composition	NSF	ASTM	Tensile Strength	Shear Strength
Cu - 4-5% Sn - 91% Others - 1%	NSF/ANSI 61-G; NSF/ANSI 372	ASTM B-32; NSF/ANSI 61-G & 372	7130	5970

4501 Quality Place | Mason, Ohio 45040, USA | 513.754.2000 | ©2020 Harris Products Group. All rights reserved.