


MODEL	MTG HOLES	"X" DIM
1000	"G"	25-3/8" [645mm]
1001	"G"	25-3/8" [645mm]
1001	"G"	25-3/8" [645mm]
1025	"D"	28-1/8" [714mm]
1047	"E"	27-1/2" [699mm]
1075	"E"	28" [711mm]
1105	"H"	34-5/16" [872mm]
1109	"H"	27-5/16" [694mm]
1116	"G"	25-3/8" [645mm]
1001FR	"G"	25-3/8" [645mm]
1109FR	"H"	27-5/16" [694mm]
1075FR	"E"	28" [711mm]
1311	"E"	26-3/4" [679mm]
1107L	"F"	26-3/16" [665mm]

CAUTION

REGARDING CONCRETE/MASONRY WALL MOUNTING: DO NOT
SECURE MOUNTING PLATE TO SAME SIDE OF WALL AS FOUNTAIN.
AVOID COMPROMISING INTEGRITY OF WALL WHEN ANCHORING
FOUNTAIN. IT IS RECOMMENDED THAT INSTALLER CALL TECHNICAL
SUPPORT IF THERE ARE ANY QUESTIONS AS TO HOW TO OBTAIN A
PROPER ANCHOR IN CONCRETE/MASONRY WALLS. 1-800-766-5612



INFO FAX : 1-888-FAX-HAWS (1-888-329-4297)
1455 Kiappa Ln, Sparks NV, 89431
Phone: 775-359-4712 Fax: 775-359-7424
Haws Ag Buehler 3 CH-3401 Burgdorf Switzerland
Haws King Pte Ltd 74 Sungei Kodut Loop Singapore 729531
e-mail: Haws@hawsco.com website: www.hawsco.com

REF NO.	6700	MODEL(S):	6700
DATE:	09/03/03	DATE:	09/03/03
APPROVED:		APPROVED:	
SCALE:	1:1	SCALE:	1:1
INSTALLATION/BACK:		INSTALLATION/BACK:	

05387C00