

Pipe Protection Tape System

PASCO "All Weather" Pipe Protection Tape is a pure physical barrier that is moisture proof, inert and non-conducting. Whether the need is to protect overhead piping in industrial applications, exposed pipe anywhere, or direct burial piping, this tape gives a completely uniform coating all around.



PASCO can cut tape in any width. Contact us with your requirements. **PASCO**'s "All Weather" Pipe Protection Tape is a tough PVC plastic tape with special high tack adhesives formulated to resist corrosion. It is easy to apply by hand with no special tools or equipment. It provides positive protection against abrasion and corrosive action for steel pipe, fittings & electrical conduit systems.

Uses:

- Corrosion protection for metal piping systems above and below ground.
- Corrosion protection for fittings and joints on mill coated pipe.
- · Corrosion protection of electrical conduit & fittings.

Features:

- Resists corrosive action by salt water, soil acids, alkalies and salts.
- Prevents dielectric corrosion between buried steel pipe and soil minerals.
- Resists the effects of outdoor weathering and sunlight exposure.
- High abrasion resistance.
- Highly conformable over a wide temperature range.
- Excellent insulating properties.
- Resists commonly encountered chemicals and chemical vapors.
- · Protects against fungus and bacteria.
- Standard widths.

IMPORTANT: Always use PASCO Pipe Primer on ALL Pipe-wrapping Jobs!

BLACK PIPE WRAP TAPE PRINTED

PART NUMBER	WIDTH	MIL	LENGTH	ROLLS PER CASE
9051-R	1"	10	100'	48
9052-R	2"	10	100'	24
9054-R	4"	10	100'	12
9061-R	1"	20	100'	48
9062-R	2"	20	100'	24
9064-R	4"	20	100'	12



Pipe Wrap Primer

- **PASCO** Pipe Primer is a quick drying rubber base primer that permeates pits and irregularities on the pipe surface and prepares the metal for tape application.
- **PASCO** Pipe Primer is made to be compatible with the adhesives on **PASCO** Pipe Protection Tape.
- PASCO Pipe Primer is easily brushed on the pipe and fittings. The application of the primer enhances the surface preparation and adds strength adhesion at low cost.
- Pint and quart sizes with dauber.



IMPORTANT: Always use PASCO Pipe Primer on ALL Pipe-wrapping Jobs!				
PART NUMBER	SIZE	COVERAGE IN SQUARE FEET*		
9043	Pint	65		
9046	Quart	125		
* Approximate:				

Depends on surface condition of the pipe

Pipe Tape Coverage Chart

APPLICATION DIRECTIONS

- Surfaces to be wrapped must be clean and dry. Any oil or grease must be removed.
- Any burrs or sharp edges must be removed or smoothed.
- Before tape application, all bare pipe and fittings to be wrapped must be coated with PASCO PIPE PRIMER.
- Weld beads shall be covered with one wrap or layer of tape prior to spiral wrapping.
- Tape shall be spirally wrapped the length of the pipe using one half lap for double thickness or 1/2" overlap, depending on the individual installation.
- 6. When pipe is mill coated, tape must be used on the fittings and joints. To wrap a joint, first coat joint with primer. Joint shall be wrapped with tape spirally beginning on the mill coating 3" from joint. Cover joint and end tape on mill coating 3" past joint.

1 Square = 100 Square feet of tape

- 1" Width = 12 Rolls per square
- 2" Width = 6 Rolls per square
- 4" Width = 3 Rolls per square

Pipe Di	ameter	TARE	MIN.	MIN.		NO. OF SQUARE
ID	OD	TAPE WIDTH	TAPE OVER- LAP	OVER- LAP	HALF LAPPED	FT. PER 100 LIN- EAL FT. OF PIPE
1/2"	.84"	1"	1/4"	.294	.44	22.0
3/4"	1.05"	1"	1/4"	.367	.55	27.5
3/4"	1.05"	2"	3/8"	.338	.55	27.5
1"	1.32"	1"	1/4"	.461	.691	34.6
1"	1.32"	2"	3/8"	.425	.691	34.6
1"	1.32"	4"	1/2"	.395	.691	34.6
1-1/4"	1.66"	2"	3/8"	.535	.869	43.5
1-1/4"	1.66"	4"	1/2"	.497	.869	43.5
1-1/2"	1.90"	2"	3/8"	.612	.995	49.7
1-1/2"	1.90"	4"	1/2"	.568	.995	49.7
2"	2.38"	2"	3/8"	.767	1.246	62.3
2"	2.38"	4"	1/2"	.712	1.246	62.3
2-1/2"	2.88"	2"	3/8"	.928	1.508	75.4
2-1/2"	2.88"	4"	1/2"	.862	1.508	75.4
3"	3.50"	2"	3/8"	1.128	1.833	91.6
3"	3.50"	4"	1/2"	1.047	1.833	91.6
3-1/2"	4.00"	2"	3/8"	1.289	2.094	104.7
3-1/2"	4.00"	4"	1/2"	1.197	2.094	104.7
4"	4.50"	2"	3/8"	1.450	2.356	117.8
4"	4.50"	4"	1/2"	1.346	2.356	117.8
4-1/2"	5.00"	4"	1/2"	1.496	2.618	130.9
5"	5.75"	4"	1/2"	1.667	2.916	145.8
6"	6.63"	4"	1/2"	1.984	3.471	173.6
6"	6.63"	6"	1/2"	1.894	3.471	173.6
7"	7.63"	4"	1/2"	2.283	3.995	199.7
7"	7.63"	6"	1/2"	2.179	3.995	199.7
8"	8.63"	4"	1/2"	2.582	4.519	255.9
8"	8.63"	6"	1/2"	2.465	4.519	255.9



Pipe Thread Seal Tape - PTFE

- Seals and makes joints leaktight regardless of pipe material or fluid. Just a quick wind around male joint. This pure PTFE tape resists temperatures from -450° to +500° F. Ideal for steam lines, heating, cooling and cryogenic systems, oil refinery pipes, aircraft fittings and missile systems. Averages less than a cent per application, eliminates liquids, pastes and brushes.
- THE VERSATILE SEALANT **PASCO** PTFE tape will seal all threaded joints-any material: copper, brass, cast iron, aluminum, monel, stainless steel, plastic, synthetic rubber, glass, or ceramic. In addition to resisting high and low temperatures, it can be used for high pressure or vacuum-liquid or gas.
- **KEEPS THREADS INTACT** Self lubricating **PASCO** PTFE tape makes assembly or disassembly easy. Eliminates the need for over tightening. Prevents galling, seizing and cross threading.
- MINIMUM MAINTENANCE PTFE tape remains impervious to the most corrosive fluids for the life of the joint. Won't dry out, crack, melt, or dissolve. Stands up to maximum pressures and vibration.
- MEETS MIL SPEC T-27730A



Yellow Gas Line Thread Seal Tape - PTFE

- Specifically designed to seal threads in natural gas, propane, butane, kerosene and petroleum oil lines.
- MEETS MIL SPEC T-27730A
- For use on threads NOT exceeding 1-1/2"







Felt Pipe Wrap



Fiberglass Pipe Wrap

The most popular fiberglass insulation for insulating heat tapes or hot or cold pipes. Stops cold water pipes from sweating, prevents heat loss from hot water pipes. It's also perfect for caulking cracks. An ideal product for new installations. Also use to repair or replace insulation on pipe or ducting. · Available in two sizes: 3" or 6" width · Vapor seal material included • R-Value = 1.9 Two widths: 3" or 6" PART NUMBER THICK-NESS LENGTH WIDTH 16503 3" 1/2' 35 16506 6" 1/2" 35' Made in U.S.A.



Rapid Seal

· Forms a solid piece of rubber in 30 minutes **IMPORTANT NOTICE:** • Works on dirty, wet, oily, surfaces. No special surface Rapid Seal MUST NOT be used to seal preparation required. Stops leaks in copper, PVC, items that will come in contact or be • Galvanized, ABS, Brass, CPVC, PVC, Copper pipe. exposed to gasoline, hexane or toluene. Works under water · Self-bonding No messy epoxy UL listed Suitable for voltage to 600V Works at temperatures of -27° to 212° Holds up to 100 PSI Convenient size 1" x 16'

Cloth and Aluminum Foil Duct Tape

- · Prevents heating and cooling loses
- · Blocks odors and moisture
- 4 Mil.
- Sold by the roll
- · 24 Rolls per case





PART NUMBER 59054



Polyurethane Expanding Foam

- · Insulates to an R value of 5
- · UL classified
- · Easy to use, multi-purpose urethane foam
- Unlike ordinary sealants, it expands three times its original volume
- · Adheres to all building materials except Teflon, silicone and polyethylene
- · Seals by expanding into gaps, cracks and crevices





Plumbers Silicone Sealant FDA/USDA Approved

- FDA/USDA Approved
- 100 % Silicone
- Resistant to mold & mildew
- Excellent adhesion
- · Forms a waterproof seal
- Permanently flexible
- Resistant to household cleaning chemicals
- Will not yellow or discolor
- Fast cure



PART NUMBER	SIZE	COLOR
1708	3 oz. Tube	White
1710	3 oz. Tube	Clear
1712	10 oz. Cartridge	White
1713	10 oz. Cartridge	Clear

Plumbers Paintable Silicone Sealant

Formulated with water-based silicone technology.

- 100% Silicone
- · Easy to clean up with water
- · Outlasts any other type of
- sealant, including acrylics
- Will not crack or pull away
- · Permanently flexible
- Resists mildew, stains & color changes
- Applies smoothly in an easy to control bead



PART NUMBER	SIZE	COLOR
1715	10 oz. Cartridge	White

Butyl Rubber Caulk

- Excellent for sealing between shower pan liner and shower drains
- Can be used anywhere an economical, weather resistant, long life sealant is required



Plumbers Goop

Plumbers Goop Seals:

- · Dry porcelain
- Urinal spud washers
- · Tank-to-bolts
- Drain gaskets
- Ceramic tile
- · Bath overflow washers
- · Gaps around exposed hose bibbs

DECOMPOSITION OF A STATE OF A STA	SERANT SEALANT ADDE/FLEXIBLE GLUED	2 -
PART NUMBER	SIZE	
1711	3.7 oz. Tuł	ре

PART NUMBER	PAGE
12333	E-6
16503	E-4
16506	E-4
1708	E-7
1709	E-7
1710	E-7
1711	E-7
1712	E-7
1713	E-7
1715	E-7
24333	E-6
2640	E-4
59054	E-5
9000-100	E-3
9010-100	E-3
9014-100	E-3
9016-100	E-3
9018-50	E-3
9020-70	E-3
9024-70	E-3
9030-50	E-3
9034-50	E-3
9043	E-2
9046	E-2
9051-R	E-1
9052-R	E-1
9054-R	E-1
9056-R	E-1
9061-R	E-1
9062-R	E-1
9064-R	E-1
9066-R	E-1
9119-R	E-5
9123-R	E-5

DESCRIPTION	PAGE
ALUMINUM FOIL DUCT TAPE	E-5
BUTYL RUBBER CAULK	E-7
CONTRACTOR DUCT TAPE	E-5
DUCT TAPE	E-5
EXPANDING FOAM SEALANT	E-6
FELT PIPE WRAP	E-4
FIBERGLASS PIPE & DUCT WRAP	E-4
FOAM SEALANT	E-6
PAINTABLE SEALANT	E-7
PIPE PROTECTION TAPE	E-1
PIPE WRAP PRIMER	E-2
PIPE WRAP TAPE/ROLL	E-1
PLUMBERS GOOP	E-7
RAPID SEAL TAPE	E-5
SILICONE SEALANT	E-7
THREAD SEAL TAPE / PTFE	E-3
YELLOW GAS LINE THREAD SEAL TAPE / PTFE	E-3