

Float Valves - NO LEAD



NO LEAD Brass Float Valve Features:

- NO LEAD Brass or Bronze* body
 - Heavy Duty
 - NBR rubber seals
 - Threaded outlet up to 1". Plain over 1"
 - Tapped for 1/4"-20SAE rod up to 1"
 - Tapped for 3/8"-16UNC rod over 1"
 - Rated at 125 psi
 - **Third party certified to NSF61/ANSI 372.**
- * Bronze body third party certified to NSF/ANSI 372



NEW SIZES

Part Number	Size	Inlet	Outlet	Tapped	Ctn Qty
BFVNL3/8	3/8"	3/8" mpt	3/8" mpt	1/4"-20UNC	10/100
BFVNL1/2	1/2"	1/2" mpt	1/2" mpt	1/4"-20UNC	10/100
BFVNL3/4	3/4"	3/4" mpt	3/4" mpt	1/4"-20UNC	10/80
BFVNL1 *	1"	1" mpt	1" mpt	1/4"-20UNC	10/40
BFVNL11/4	1 1/4"	1 1/4" fpt	plain	3/8"-16UNC	2/20
BFVNL11/2	1 1/2"	1 1/2" fpt	plain	3/8"-16UNC	2/16
BFVNL2	2"	2" fpt	plain	3/8"-16UNC	2/12



BFVR Series

Stainless Steel Rods Features:

- Stainless Steel SAE
- Male thread both ends
- **Third party certified to NSF/ANSI 372.**



Part Number	Length	Thread	Fits Valve Size	Ctn Qty
BFVR8	8"	1/4"-20SAE	1/2" - 1"	50/400
BFVR10	10"	1/4"-20SAE	1/2" - 1"	50/300
BFVR12	12"	1/4"-20SAE	1/2" - 1"	50/300



BFVFP Series

Plastic Float Features:

- PVC, Corrosion resistant.
- Lightweight
- Up to 175°F
- For open tank service only
- Bronze or NO LEAD bronze threaded connection.
- **Third party certified to NSF/ANSI 372.**



Part Number	Float Diam.	Buoyancy	Female Connection	Ctn Qty
BFVFPNL5	5"	2.17 lbs.	1/4"-20SAE	100
BFVFPNL6	6"	3.8 lbs.	1/4"-20SAE	100
BFVFPNL8	8"	9.87 lbs.	1/4"-20SAE	20