

PEX COPPER CRIMP RING W/ POSITIONING CAP

Specifications

- Manufactured to the highest industry standards, Jones Stephens' F1807 crimp fittings provide precise, leak-free connections. The secure and reliable crimp fitting method provides full, immediate strength upon installation, with 360-degree uniform pressure. Approved for use with PEX piping.

Applications

- Commercial and residential non-potable water applications

Materials


- Copper
- Low density polyethylene

Dimensions and Product Offering

Part Code	Size	A - in (mm)	A - Tolerance \pm in (mm)	B - in (mm)	B - Tolerance \pm in (mm)	C - in (mm)	C - Tolerance \pm in (mm)
C76102	1/2	0.638 (16.20)	\pm 0.003 (0.08)	0.325 (8.26)	\pm 0.02 (0.51)	0.056 (1.42)	\pm 0.003 (0.08)
C76103	3/4	0.88 (22.35)	\pm 0.003 (0.08)	0.325 (8.26)	\pm 0.02 (0.51)	0.06 (1.52)	\pm 0.003 (0.08)
C76104	1	1.15 (29.21)	\pm 0.003 (0.08)	0.365 (9.27)	\pm 0.02 (0.51)	0.05 (1.27)	\pm 0.003 (0.08)
C76105	1-1/4	1.388 (35.25)	\pm 0.003 (0.08)	0.55 (14.00)	\pm 0.02 (0.51)	0.056 (1.42)	\pm 0.003 (0.08)
C76106	1-1/2	1.645 (41.78)	\pm 0.003 (0.08)	0.65 (16.51)	+0.008 (0.20) / -0.016 (0.41)	0.065 (1.65)	\pm 0.003 (0.08)
C76107	2	2.16 (54.86)	\pm 0.003 (0.08)	0.75 (19.05)	\pm 0.02 (0.51)	0.07 (1.78)	\pm 0.004 (0.01)

Certifications/Listings/Approvals

- ASTM F1807
- ASTM F877
- CSA B137.5
- NSF/ANSI 14



Job Name		
Location		
Engineer		
Contractor		
Tag	PO#	

