

# F1960 Brass PEX Ball Valve with Drop Ear and Drain

|            |                 |
|------------|-----------------|
| Job Name   | _____           |
| Location   | _____           |
| Engineer   | _____           |
| Contractor | _____           |
| Tag        | _____ PO# _____ |

## Specifications

- Includes drop ears and a drain
- Lead-free brass
- 5 year limited warranty
- Working pressure: 80 psi
- Max. pressure: 200 psi
- Working temperature: 73°F
- Max. temperature: 200°F
- Temperature and pressure ratings: 200 psi at 200°F

## Applications

- PEX Pipe

## Materials

- Metal
  - Handle- Steel
  - Body - Brass



## Dimensions and Product Offering

| Part Code        | Size | A             | B             | C             | D       | E       |
|------------------|------|---------------|---------------|---------------|---------|---------|
| <b>B65050LFD</b> | 1/2" | 3.78" ± 0.25" | 1.64" ± 0.25" | 2.92" ± 0.10" | Ø 0.38" | Ø 0.61" |
| <b>B65075LFD</b> | 3/4" | 3.78" ± 0.25" | 1.88" ± 0.25" | 3.60" ± 0.10" | Ø 0.60" | Ø 0.87" |
| <b>B65100LFD</b> | 1"   | 3.78" ± 0.25" | 2.01" ± 0.25" | 4.34" ± 0.10" | Ø 0.80" | Ø 1.10" |

## Certifications/Listings/Approvals

- Vermont Act 193 compliant
- Lead Law compliant
- IAPMO/ANSI Z1157
- ASME A112.4.14/CSA B125.14
- NSF/ANSI 14
- NSF/ANSI/CAN 372
- NSF/ANSI/CAN 61

