



SEDIMENT PLEATED REUSABLE FILTER CARTRIDGES

WPE SERIES



FEATURES/BENEFITS

- Manufactured from a durable, non-woven and reusable polyester fabric that is suitable for a wide range of filtration uses
- ♦ The filter media is pleated around a polypropylene core for added strength
- Pleated technology maximizes dirt-holding capacity and extends the time period between changes or cleaning*
- ◆ Cartridges are resistant to chemical attack, making them suitable for a variety of residential, commercial, and industrial applications*
- ♦ Available in nominal 30- and 50-micron ratings*
- ♦ Compatible with all Pentair housings
- ♦ For use on chlorinated and non-chlorinated drinking water supplies

SPECIFICATIONS AND PERFORMANCE

Filter Media

Non-woven polyester

Seal Type

10"BB Santoprene10" Vinyl plastisol

Temperature Rating

40-125°F (4.4-51.7°C)

MODEL#	PART #	MAXIMUM DIMENSIONS	MICRON Rating	INITIAL ΔP (PSI) @ FLOW RATE (GPM)**	APPLICATION	HOUSING SIZE
W30PE	155017-52	2.63" x 9.75" (67 mm x 248 mm)	30	1.0 psi @ 10 gpm (0.07 bar @ 38 Lpm)	UNDERSINK	10" Standard and Slim Line®
W50PE	155038-52	2.63" x 9.75" (67 mm x 248 mm)	50	1.0 psi @ 10 gpm (0.07 bar @ 38 Lpm)	UNDERSINK	10" Standard and Slim Line
W30PEHD	155101-51	4.5" x 9.75" (114 mm x 248 mm)	30	1.0 psi @ 10 gpm (0.07 bar @ 38 Lpm)	WHOLE HOUSE	10" Big Blue [®] , Heavy-Duty
W50PEHD	155053-51	4.5" x 9.75" (114 mm x 248 mm)	50	1.0 psi @ 10 gpm (0.07 bar @ 38 Lpm)	WHOLE HOUSE	10" Big Blue, Heavy-Duty

^{**}Pressure drop and flow rate based on housing without cartridge.
CAUTION: Protect against freezing to prevent cracking of the filter and water leakage.



13845 Bishops Dr. | Suite 200 | Brookfield, WI 53005 | United States P: 262.238.4400 | Customer Service: 800.279.9404 | tech-support@pentair.com | pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered trademarks and logos are the property of their respective owners.

^{*} Based on manufacturer's internal testing.