

SLIM LINE FILTER HOUSINGS

W38-PRA, W38-PRB, W385-PR SERIES



FEATURES/BENEFITS

- ◆ Perfect choice for undersink installations
- ◆ Slim, compact design
- ◆ Available in 5" and 10" sizes
- ◆ Include a reinforced polypropylene cap that offers a pressure-relief button on the inlet side to relieve pressure when changing filter cartridges
- ◆ Molded with reinforced polypropylene
- ◆ Equipped with 3/8" NPT inlet and outlet ports
- ◆ Accommodate a wide range of 2 1/4"-2-7/8" diameter, 5"-10" long cartridges
- ◆ Include installation hardware, sump wrench and manual

W38-PRB HOUSING

- ◆ The W38-PRB includes the Pentair 3G cap, with molded, integrated bracket, that simplifies installation

SPECIFICATIONS AND PERFORMANCE

Housing Material

Polypropylene

Cap




Polypropylene

Temperature Rating

40 -125°F (4.4-51.7°C)

Maximum Pressure

125 psi (8.6 bar)

MODEL #	PART #	MAXIMUM DIMENSIONS	INITIAL ΔP (PSI) @ FLOW RATE (GPM)**	PRESSURE-RELIEF VALVE	APPLICATION	CARTRIDGE SIZE
W38-PRA	152005	11.75" x 4.38" (298 mm x 111 mm)	2 psi @ 5 gpm (0.14 bar @ 19 Lpm)	YES		10"
W38-PRB	152086	13.75" x 5.38" (349 mm x 137 mm)	2 psi @ 5 gpm (0.14 bar @ 19 Lpm)	YES		10"
W385-PR	152007	7.38" x 4.38" (187 mm x 111 mm)	2 psi @ 3 gpm (0.14 bar @ 11 Lpm)	YES		5"

**Pressure drop and flow rate based on housing without cartridge.
CAUTION: Protect against freezing to prevent cracking of the filter and water leakage.