

# SEDIMENT POLYPROPYLENE STRING WOUND FILTER CARTRIDGES

## WW SERIES



### FEATURES/BENEFITS

- ◆ Manufactured from a durable polypropylene cord that is wound around a rigid polypropylene core
- ◆ Economical solution to reduce fine sediment, including sand, silt, rust, and scale particles
- ◆ Suitable for a wide variety of sediment filtration applications
- ◆ Capable of withstanding temperatures up to 165°F (73.9°C)\*
- ◆ String wound design reduces fine sediment from a variety of fluids
- ◆ Available in nominal 5-, 30- and 50-micron ratings\*
- ◆ Compatible with all Pentair 10" housings
- ◆ For use on chlorinated and non-chlorinated drinking water supplies

\*Based on manufacturer's internal testing.




### SPECIFICATIONS AND PERFORMANCE

#### Filter Media

Polypropylene fiber cord

#### Temperature Rating

40-165°F (4.4-73.9°C)

MODEL #	PART #	MAXIMUM DIMENSIONS	MICRON RATING	INITIAL ΔP (PSI) @ FLOW RATE (GPM)**	APPLICATION	HOUSING SIZE
W5W	155186-52	2.25" x 9.88" (60 mm x 251 mm)	5	1.0 psi @ 10 gpm (0.07 bar @ 38 Lpm)	 UNDERSINK	10" Standard and Slim Line®
W30W	155187-52	2.25" x 9.88" (60 mm x 251 mm)	30	1.0 psi @ 10 gpm (0.07 bar @ 38 Lpm)	 UNDERSINK	10" Standard and Slim Line
W50W	155214-51	2.25" x 9.88" (60 mm x 251 mm)	50	1.0 psi @ 10 gpm (0.07 bar @ 38 Lpm)	 UNDERSINK	10" Standard and Slim Line

\*\*Based on manufacturer's internal testing. Not Tested or Certified by NSF.

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.