

Hydraulic Royal® Model Flushometer

986
986-1
986-0.5



► Description

Exposed Hydraulically Operated Urinal Flushometer, for 3/4" top spud urinals.

► Flush Cycle

- Model 986 Water Saver (1.5 gpf/5.7 Lpf)
- Model 986-1 Low Consumption (1.0 gpf/3.8 Lpf)
- Model 986-0.5 (0.5 gpf/1.9 Lpf)

► Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Urinal Flushometer with the following features:

- Dual Filtered By-pass
- ADA Compliant Non-Hold-Open feature type Actuator (**specify Actuator type listed below**)
- 3/4" I.P.S. Screwdriver Bak-Chek™ Angle Stop
- Free Spinning Vandal Resistant Stop Cap
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker Flush Connection with One-piece Bottom Hex Coupling Nut
- Spud Coupling and Flange for 3/4" Top Spud
- Sweat Solder Adapter with Cover Tube and Cast Set Screw Wall Flange
- Diaphragm, Stop Seat and Vacuum Breaker to be molded from PERMEX™ rubber compound for Chloramine resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME 112.19.6, and Military Specification V-29193.

► Actuator Types: (please check one)

- FW** Fixture Wall Actuator (HY-33-A) (rear access required)
- MP** Metal Partition Actuator (HY-49-A)
- SW** Side Wall Mounted Actuator (HY-72-A)
- MBFW** Metal Button Fixture Wall Actuator (HY-100-A) (rear access required)
- MBPM** Metal Button Panel Mount (HY-108-A)

See Actuator Specification pages in this section for details on Actuators.

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.

► Hydraulic Flushometer can also be provided in Regal® Models. All rough-in dimensions remain the same. Consult the factory.



Listed by I.A.P.M.O.

This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.

Made in the U.S.A.

SLOAN

SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL 60131
PHONE: 1-800 982-5839 • FAX: 1-800 447-8329 • <http://www.sloanvalve.com>

