TOTO MS854114S(G)/MS853113S

UltraMax® One-Piece Toilet, 1.6GPF

FEATURES

- G-Max[®] flushing system, low consumption (1.6GPF/6.0LPF)
- Optional CeFiONtect™ ceramic glaze prevents debris and mold from sticking to ceramic surfaces, leading to fewer chemicals.
- One-piece decorative toilet with high-profile tank
- Elongated front bowl with SoftClose[®] seat (SS114) or round front bowl with SoftClose seat (SS113)
- 12" Rough-in
- Chrome trip lever

MODELS

- MS854114SG
 Elongated bowl with CeFiONtect and SoftClose seat (SS114)
- MS854114S
 Elongated bowl with SoftClose seat (SS114)
- MS853113S Round bowl with SoftClose seat (SS113)

COLORS/FINISHES

Standard
 #01 Cotton
 #03 Bone
 #11 Colonial White
 #12 Sedona Beige

PRODUCT SPECIFICATION

The one-piece G-Max flushing system toilet shall be 1.6GPF/6.0LPF. Toilet shall be of elongated front bowl (MS854) or round front bowl (MS853) with a low-profile tank and SoftClose seat. Toilet shall have chrome trip lever. Toilet shall have optional CeFiONtect ceramic glaze. Toilet shall be TOTO Model MS85_____.







CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others



UltraMax® One-Piece Toilet, 1.6GPF

SPECIFICATIONS

Water Use
Flush System
Min. Water Pressure
Water Surface
Trap Diameter
1.6 GPF/6.0LPF
8 psi (static)
10-1/4" x 8-1/4"
2-1/8"

Trap Diameter 2-1/8"
 Rough-in 12"
 Trap Seal 2-3/8"

• Warranty One Year Limited Warranty

• Material Vitreous china

 Shipping Weight MS854114S(G) 93 lbs. MS853113S(G) 91 lbs.

• Shipping Dimensions 30-3/4" L x 18-1/8"W

x 27-1/8" H

INSTALLATION NOTES

Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



